



Spectrogram



SDCM



Color Parameter:

x: 0.1549 y: 0.0365 u: 0.1981 v: 0.0700 u': 0.1981 v': 0.1050
R_ratio: 0.7 % G_ratio: 2.4 % B_ratio: 96.8 % RedRatio: 2.7 % GreenRatio: 29.5 % BlueRatio: 67.8 %

Ra: -43.3 AvgR: -43.4
R1: 28.7 R2: -27.0 R3: -99.0 R4: -94.2 R5: 34.0 R6: -30.8 R7: -55.3 R8: -43.6
R9: -99.0 R10: -99.0 R11: -99.0 R12: -86.3 R13: 14.9 R14: -33.2 R15: 37.8

CCT: 99999 K Flux: 402.190 lm PeakWave: 451.6 nm SDCM: 116.4
S/P: 17.2 CentralWave: 451.6 nm DominantWave: 457.1 nm CentroidWave: 457.0 nm
HalfWidth: 22.2 nm duv: 0.15983 purity: 96.4 % CQS: 0.3
LER(TM-30): 47.3 Ep: 8507.9 mw Rg: nan Rf: -nan(ind)
Red Ep: 62.5 mw Near red Ep: 20.3 mw Near infrared Ep: 7.9 mw

Electrical parameters:

Effic: 6.5 Lm/W Energy: 7.1 Effi: G
U: 220.8 V I: 0.462 A P: 62.060 W Pf: 0.611

Product model:
Product number:
Tester:
Remarks:

Manufacturer: Guangzhou Hotion Technology Co.,
Test unit:
Date of observation: 03/17/14

Spectrogram

Test — Ref

Intensity (0.0 to 1.0) vs. Wavelength (380 to 780 nm)

Wavelength (nm)	Test Intensity	Ref Intensity
380	0.00	0.78
410	0.00	1.00
430	0.05	0.95
450	0.50	0.90
460	1.00	0.85
470	0.50	0.80
480	0.10	0.70
500	0.02	0.55
530	0.00	0.45
580	0.00	0.30
630	0.00	0.25
680	0.00	0.22
730	0.00	0.18
780	0.00	0.15

ERROR: rangecheck
OFFENDING COMMAND: roll

STACK:

2
4
-2.14748e+011
-2.14748e+012