



HERO 700F

700W LED Moving Head Framing

HERO 700F is a 700W LED light source cutting moving head light. Color temperature 8000K, equipped with a 7-color color wheel, plus CMY, CTO color mixing system for linear color conversion and half-color rainbow effect. 5.5°~50° linear high-speed zoom, RDM/DMX two-way control technology is adopted in the control of linear aperture and double fogging effect (heavy fogging + light fogging). Rotating pattern 7+1 can be replaced or pre-selected, 1 fixed pattern plate with 15 kinds of patterns, variable speed jitter/two-way rotation, 1 dynamic fire plate for effect pattern, positive and negative and 360-degree infinite rotation, stunning simulation of dynamic and moving flames , gurgling water and other dynamic effects.

Main feature:

- LED 700W (white light)
- Color temperature 8000K
- RDM—DMX bidirectional control technology
- 1 rotating gobo wheel with 7 rotating gobos (optional gobos)
- 1 fixed gobo wheel with 15 gobos, variable speed jitter/bidirectional rotation
- 1 dynamic fire plate, reversible and 360 degree infinite rotation
- LCD liquid crystal display, can be reversed 180° display with touch screen effect, strobe with pulse strobe, synchronous asynchronous effect 1-25Hz per second fast strobe
- Independent rotation 3 prism effects, can be rotated in positive and negative directions, and has the function of prism positioning
- Adopt wind direction drainage and PWM temperature intelligent monitoring technology to automatically adjust the heat dissipation system
- 4 gratings to achieve fast and smooth cutting, the cutting direction and angle of each grating can be controlled individually, and a single piece can achieve complete light closure, the entire cutting module has an aperture (aperture 5%~100% smooth adjustment)



Technical parameter

Rated voltage:	AC100-240V, 50/60Hz	Control mode:	Auto, Sound, Master slave, DMX and RDM
Light source:	700W white LED	Shell:	Colour black, ABS+PC
Rated power:	800W	Size:	420 x 290 x 800 mm
Color temperature:	8000K	N.W.:	32.7 kg
CRI:	CRI ≥70 or CRI 95 optional	Dimming:	0%-100% dimming
Zoom Range:	5.5°~50° linear high-speed zoom	Light source life:	30000-50000 hours
Power Connection:	PowerCON in & out	Accessories(included):	safety rope, power cord, manual
Signal connection:	3-pin XLR in and out (optional 5-pin)	Accessories (optional):	One-piece folding light hook
DMX channel:	36	Environment:	IP 20

Applicable scene:

- Concert
 - Nightclub
 - Large venues
 - Large stage
- Fashion show
 - Auto show
 - Theater
 - Wedding

