

RDM

Control

ZOOM

Flicker Free

Panto 200T Profile 1530 is a 200W warm white + 200Watt cold white powered LED light . Lens 15°-30°. HD optics and four shutters to control the shape of the light. Fixture also equipped with powercon in & out connector.


Key features:

- 200W warm white + 200Watt cold white
- HD optical system, clean shutter cuts beam
- 15°-30° Zoom lens
- Smooth dimming, flicker free operation
- Flicker free with selectable PWM
- DMX control of dimmer
- Silent operation for studio and theatre use
- Aluminum housing, robust construction


Application:

- Broadcast, HD studio
- Theatre, chrucl
- Fashion show
- Museum
- Exhibition lighting

Accessories:



Gel frame



Gobo holder (opt.)



Panto 200T Profile 1530

200W LED profile



Technical Data

Power supply:	AC100 - 240V, 50/60Hz
Light source:	400W LED (200W WW + 200W CW)
Color temperature:	2800K - 6500K tunable
Fixed lens:	15°-30°
Color Rendition:	CRI 95
Power connection:	PowerCON in & out
Signal connection:	3-pin XLR in & out(5-pin opt.)
Control channels:	1/2/3

Housing:	Color black, aluminum
Size:	660*235*280mm
Control mode:	DMX, RDM
N.W.:	11.7kg
Accessories(incl.):	Power cable, Gel frame, Safety rope
Accessories(opt.):	Gobo holder, Clamp
Environment:	IP65