

G32 Integrated DC Charger

(320 ~ 800kW)

Main Features



Supports CCS1, CCS2 and GB/T charging standards



OCPP 1.6 compliant (upgradable to OCPP 2.0.1)



Remote Firmware Upgrade



Equipped with multi-level comprehensive protection functions

Application Scenarios

Bus station charging points, highway fast charging stations, fleet operation charging systems



G32 Integrated DC Charger



Parameter	Specification
Net Weight	Net weight approx. 460KG (modules excluded)
Dimensions (W×D×H)	1400*800*1900mm(W×D×H)
Output Current (Default Config.)	0~250A GB/T 0~200A CCS2 0~200A CCS1 Custom current specifications available upon contacting our company.
AC Input Voltage	3 phase+N+PE,400Vac±15% (Default) 3 phase+N+PE,480Vac±10% (Optional)
AC Input Frequency	50Hz/60Hz±10%
Output Voltage Range	200VDC~1000VDC
Power Distribution	Single gun: full power; Dual gun: equal power sharing
IP Protection Rating	IP54
Cooling Method	Air Cooling
Protection Features	Short circuit / Over-temperature / Over-current Under-voltage / Over-voltage / Emergency stop / Surge protection
Operating Temperature	-25°C~+50°C
Display Screen	7" / 10.1"
Altitude	≤2000m
Charging Cable Length	approx. 5 m (outside cabinet)
Peak Efficiency	≥95%
Power Factor	≥0.99