

1

2

3

4

5

6

7

8

9

G

F

E

D

C

B

A

Connector your can choose Alternative as HECON Standard Or Original JST. Molex,AMP, TE

C

4

0.8

5.6

7.95

4.9

9

2.5

1

A

B

16&15

11&10

6&5

9

1

P1

1

2

3

4

5

6

7

N

L±3~5

②③

①

②③

P2

1

2

3

4

5

6

7

N

Ordering Information

HC-WH 25-S-XX-SN-XX-XX-X-XXX-02

Wire Harness

Pitch
25=2.5 Pitch

S=Standard
C=Customized

No. of Pins
2P~20P

Contact Plating
SN=Plating Tin

CT=Cable Tie
TE=Tape
WD=Woven Braid
HT=Heat Shrink Tubing
SW=Spiral Wrap
TD=Twisted
IT=Insulation Tubing
SP=Special

Wire AWG
28=28AWG
26=26AWG
24=24AWG
22=22AWG

Wire Color
B=Black
BR=Brown
R=Red
O=Orange
Y=Yellow
GR=Green
BL=Blue
P=Purple
G=Grey
W=White

Length
100=100mm

Serial number

REMARKS:

1. 100% Open/Short test.

2. DC Test:300V/10ms.

3. Insulation Resistance:5.0M OHM/Min.

4. Conductance Resistance:5.0 OHM/Max.

3

2

1

NO.

XH2.5mm terminal,Plating Tin

XH2.5mm XP Housing,White

28AWG~22AWG XX Color

MATERIAL&SPECIFICATION

XPCS

2PCS

XPCS

Q'ty

OPERATION

X.X

±0.30

X.XX

±0.20

X.XXX

±0.10

DIM

TOL

DRAW

BoFeng

2020.04.20

CHECK

Jack L

2020.04.20

APPROVE

SCALE

FIT

UNIT

mm

SIZE

A4

SHEET

1/1

PROJ.

HECON

东莞市禾康电子有限公司

DONGGUAN HECON ELECTRONICS CO.,LTD

PART NO.

HC-WH25-S-XX-SN-XX-XX-X-XXX-02

TITLE:

XH2.5-XP TO XH2.5-XP

1

2

3

4

5

6

7

8

9

A0

2020.04.20

NEW DRAWING

REV

DATE

MODIFICATION DESCRIPTION

CHANGE