

WIRING DIAGRAM

P1		P2
1	Black	4
2	White	3
3	Yellow	10
4	Orange	9

REMARKS:
1. 100% Open/Short test.
2. DC Test:300V/10ms.
3. Insulation Resistance:5.0M OHM/Min.
4. Conductance Resistance:5.0 OHM/Max.

NO.	MATERIAL&SPECIFICATION	Q'ty
5	Black PVC Tube	1PCS
4	MX3.0 2*6P Housing,Black	1PCS
3	MX3.0 4P Housing,Black	1PCS
2	MX3.0 terminal,Plating Tin	8PCS
1	UL1061 26AWG Hook up wire	4PCS

REV	DATE	MODIFICATION DESCRIPTION	CHANGE
A0	2021.09.01	NEW DRAWING	

OPERATION		DRAW	BoFeng	2021.09.01	SCALE	FIT
X.X	±0.30				UNIT	mm
X.XX	±0.20	CHECK	Jack L	2021.09.01	SIZE	A4
X.XXX	±0.10				SHEET	1/1
DIM	TOL	APPROVE			PROJ.	

HECON 东莞市禾康电子有限公司
DONGGUAN HECON ELECTRONICS CO.,LTD

PART NO.	HC-WH3004SNB610-02
TITLE:	MX3.0-4P TO MX3.0-2*6P