

RoHS

SPECIFICATIONS

Rated Current:3.0AMP

Contact Resistance:20mΩ Max

Withstand Voltage:1000V AC/DC

Insulation Resistance:1000MΩ Min

Operation Temperature:-40°C to +105°C

Contact Material:Brass/Phosphor Bronze

Contact Plating:Au or Sn Over Ni

Insulator Material:Polyester(UL94V-0)

Standard: PBT

Max.Processing Temp: 180°C for 30-60 seconds
(200°C for 10 seconds)

Ordering Information

HC-DIP10 XX X XX X 01

No.of Pins 06~64P
Contact Material B=Brass P=Phosphor Bronze
Contact Plating SN:Tin G0:Gold Flash G2:5U"Gold G3:10U"Gold G4:15U"Gold G5:30U"Gold S0:Gold Flash/Tin
Color Type B=Black G=Grey

OPERATION

X.X ±0.30

X.XX ±0.20

X.XXX ±0.10

Angle ±3°

DIM TOL

DRAW

Ayang

CHECK

APPROVE

SCALE

FIT

UNIT

mm

SIZE

A4

SHEET

1/1

PROJ.

◆

HECON 东莞市禾康电子有限公司
DONGGUAN HECON ELECTRONICS CO.,LTD

PART NO.

HC-DIP10XXXXXX01

TITLE:

2.54mm Npin DIP Two Type