

	1	2	3	4	5	6	7	8	9																																																												
G	RoHS																																																																				
F							Technical Specs: Insulator: Black glass filled polyester PPS Flammability: UL 94V-O Sleeve: Brass (C36040) Contact clip(4 finger): Beryllium copper(C17300) Accepted pin: Ø0.70 to 0.90mm, 0.635mm Forces: --Insertion 2 N typ --Withdrawal 1 N typ Mechanical life: min 500 cycles Rated current: 3A Contact resistance: max 10mΩ Dielectric resistance: Min 1000MΩ Coplanarity SMD terminations: max 0.1mm(measured on 25mm long connectors)																																																														
E																																																																					
D																																																																					
C							Ordering Information HC-MF420 70 X XX S XX 117 01 Insulator Type Code 1: Single row 2: Double row No. of Pins 1x40 Pins 2x40 Pins Contact Plating SN: Tin G0: Gold Flash G2: 2U"Gold G3: 3U"Gold G4: 5U"Gold G5: 10U"Gold S0: Gold Flash/Tin Standard: G0 Pin Length 117=11.7mm																																																														
B																																																																					
A	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2"></th><th colspan="2"></th><th colspan="2">OPERATION</th><th rowspan="2">DRAW</th><th rowspan="2">Ayang</th><th rowspan="2">SCALE</th><th rowspan="2">FIT</th></tr> <tr> <th></th><th></th><th></th><th></th><th>X.X</th><th>±0.30</th></tr> </thead> <tbody> <tr> <td></td><td></td><td></td><td></td><td>X.XX</td><td>±0.20</td><td>CHECK</td><td></td><td>UNIT</td><td>mm</td></tr> <tr> <td>A0</td><td></td><td>NEW DRAWING</td><td></td><td>X.XXX</td><td>±0.10</td><td rowspan="2">APPROVE</td><td></td><td>SIZE</td><td>A4</td></tr> <tr> <td>REV</td><td>DATE</td><td>MODIFICATION DESCRIPTION</td><td>CHANGE</td><td>Angle</td><td>±3'</td><td></td><td>SHEET</td><td>1/1</td></tr> <tr> <td></td><td></td><td></td><td></td><td>DIM</td><td>TOL</td><td></td><td></td><td>PROJ.</td><td>☐</td></tr> </tbody> </table> HECON 东莞市禾康电子有限公司 DONGGUAN HECON ELECTRONICS CO.,LTD <table border="1" style="width: 100%; border-collapse: collapse; margin-top: 10px;"> <tr> <td>PART NO.</td><td>HC-MF42070XXXSXX11701</td></tr> <tr> <td>TITLE:</td><td>2.54x7.0mm Machine Female Header+H1.5 Plastic Straight L=11.7</td></tr> </table>														OPERATION		DRAW	Ayang	SCALE	FIT					X.X	±0.30					X.XX	±0.20	CHECK		UNIT	mm	A0		NEW DRAWING		X.XXX	±0.10	APPROVE		SIZE	A4	REV	DATE	MODIFICATION DESCRIPTION	CHANGE	Angle	±3'		SHEET	1/1					DIM	TOL			PROJ.	☐	PART NO.	HC-MF42070XXXSXX11701	TITLE:	2.54x7.0mm Machine Female Header+H1.5 Plastic Straight L=11.7
				OPERATION		DRAW	Ayang	SCALE	FIT																																																												
				X.X	±0.30																																																																
				X.XX	±0.20	CHECK		UNIT	mm																																																												
A0		NEW DRAWING		X.XXX	±0.10	APPROVE		SIZE	A4																																																												
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	Angle	±3'			SHEET	1/1																																																												
				DIM	TOL			PROJ.	☐																																																												
PART NO.	HC-MF42070XXXSXX11701																																																																				
TITLE:	2.54x7.0mm Machine Female Header+H1.5 Plastic Straight L=11.7																																																																				
	1	2	3	4	5	6	7	8	9																																																												

Ordering Information

Insulator Type Code	No. of Pins	Contact Plating	Pin Length
1: Single row	1x40Pins	G0:Gold Flash	117=11.7mm
2: Double row	2x40Pins	G2:2U"Gold	
		G3:3U"Gold	
		G4:5U"Gold	
		G5:10U"Gold	
		S0:Gold Flash/Tin	
		Standard:G0	

				OPERATION		DRAW	Ayang		SCALE	FIT	HECON 东莞市禾康电子有限公司 DONGGUAN HECON ELECTRONICS CO.,LTD	
				X.X	±0.30							
				X.XX	±0.20	CHECK			SIZE	A4	PART NO. HC-MF42070XXXSXX11701	
				X.XXX	±0.10							
A0		NEW DRAWING		Angle	±3'	APPROVE			SHEET	1/1	TITLE: 2.54x7.0mm Machine Female Header+H1.5 Plastic Straight L=11.7	
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	DIM	TOL							