

RoHS

Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE ± 0.05)

SPECIFICATIONS

Rated Current:1.0AMP

Contact Resistance:20m Ω Max

Withstand Voltage:500V AC/DC

Insulation Resistance:1000M Ω Min

Operation Temperature:-40°C to +105°C




Contact Material:Phosphor Bronze

Contact Plating:Au Over Ni

Insulator Material:Polyester(UL94V-0)

Standard: PA6T

Max.Processing Temp: 230°C for 30-60 seconds
(260°C for 10 seconds)



Ordering Information

HC-FH743 02 XX X N XX R U X 01

No.of Pins Per Row 2*50	Insulator Material Option	Contact Plating	Packing
A=BK-PBT	G0:Gold Flash	T=Tube	
B=BK-PA66	G2:5U" Gold	P=Tube+Cap	
C=BK-PA6T	G3:10U" Gold	R=Reel+Cap	
D=BK-PA46	G4:15U" Gold	M=Reel+Mylar	
F=BK-LCP	G5:30U" Gold		
	S0:Gold Flash/Tin		
	SN:Tin		

OPERATION

X.X ± 0.30

X.XX ± 0.20

X.XXX ± 0.10

Angle $\pm 3^\circ$

DIM TOL

DRAW

Ayang

CHECK

APPROVE

SCALE

FIT

UNIT

mm

SIZE

A4

SHEET

1/1

PROJ.

1/1

HECON 东莞市禾康电子有限公司
DONGGUAN HECON ELECTRONICS CO.,LTD

PART NO.

HC-FH74302XXXNXXRUX01

TITLE:

1.27mm H4.3 Dual Row Right Angle
Female Header

A0

REV

DATE

MODIFICATION DESCRIPTION

CHANGE

1

2

3

4

5

6

7

8

9