

<

Rated Current:1.5AMP
Contact Resistance:20mΩ Max
Withstand Voltage:500V AC/DC
Insulation Resistance:1000MΩ Min
Operation Temperature:-40℃ to +105℃

Contact Material:Brass
Contact Plating:Au or Sn Over Ni
Insulator Material:Polyester(UL94V-0)
Standard: PA6T
Max.Processing Temp: 230℃ for 30-60 seconds
(260℃ for 10 seconds)

HC-FH543 02 XX X X XX M U X 01

No. of Pins	Insulator Material	Post	Contact	Plating	Packing
Per Row	Option	W=With Post	G0:Gold	Flash	T=Tube
2*40	A=BK-PBT	N=W/O Post	G2:5U"	Gold	P=Tube+Cap
	B=BK-PA66		G3:10U"	Gold	R=Reel+Cap
	C=BK-PA6T		G4:15U"	Gold	M=Reel+Mylar
	D=BK-PA46		G5:30U"	Gold	
	F=BK-LCP		S0:Gold	Flash/Tin	
			SN:Tin		

				OPERATION		DRAW	Ayang		SCALE	FIT	HECON 东莞市禾康电子有限公司 DONGGUAN HECON ELECTRONICS CO.,LTD	
				X.X	±0.30				UNIT	mm		
				X.XX	±0.20	CHECK			SIZE	A4	PART NO.	HC—FH54302XXXXXXMUX01
				X.XXX	±0.10				SHEET	1/1		
A0		NEW DRAWING		Angle	±3'	APPROVE			PROJ.		TITLE:	2.0mm H4.3 Dual Row SMT Female Header
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	DIM	TOL							