

	1	2	3	4	5	6	7	8	9																																										
G	RoHS						SPECIFICATIONS Rated Current:1.0AMP Contact Resistance:20mΩ Max Withstand Voltage:500V AC/DC Insulation Resistance:1000MΩ Min Operation Temperature:-40°c to +105°c																																												
F				Recommended P.C.B Layout(Top Side) (PCB BOARD TOLERANCE±0.05)			Contact Material:Brass Contact Plating:Au or Sn Over Ni Insulator Material:Polyester(UL94V-0) Standard: PA6T Max.Processing Temp: 230°C for 30-60 seconds (260°C for 10 seconds)																																												
E																																																			
D																																																			
C	<table border="1"><caption>Dimension antitheses list</caption><thead><tr><th>ITEM</th><th>PA</th><th>PB</th><th>W</th><th>L</th></tr></thead><tbody><tr><td>Standard</td><td>1.80</td><td>2.50</td><td>4.50</td><td>6.20</td></tr><tr><td>Alternate</td><td></td><td></td><td></td><td></td></tr></tbody></table>			ITEM	PA	PB	W	L	Standard	1.80	2.50	4.50	6.20	Alternate								Ordering Information HC-PH720 11 XX X M XX N XXX X 01(2) <table border="1"><thead><tr><th>No.of Pins Per Row 1*1~1*50</th><th>Insulator Material Option A=BK-PBT B=BK-PA66 C=BK-PA6T D=BK-PA46 E=BK-PA9T F=BK-LCP</th><th>Contact Plating G0:Gold Flash G1:3U" Gold G2:5U" Gold G3:10U" Gold G4:15U" Gold G5:30U" Gold S0:Gold Flash/Tin SN:Tin</th><th>Pin Length</th><th>Packing O=PE Bag A=Tray T=Tube P=Tube+Cap R=Reel+Cap M=Reel+Mylar</th></tr></thead><tbody><tr><td></td><td></td><td></td><td></td><td></td></tr></tbody></table>			No.of Pins Per Row 1*1~1*50	Insulator Material Option A=BK-PBT B=BK-PA66 C=BK-PA6T D=BK-PA46 E=BK-PA9T F=BK-LCP	Contact Plating G0:Gold Flash G1:3U" Gold G2:5U" Gold G3:10U" Gold G4:15U" Gold G5:30U" Gold S0:Gold Flash/Tin SN:Tin	Pin Length	Packing O=PE Bag A=Tray T=Tube P=Tube+Cap R=Reel+Cap M=Reel+Mylar																						
ITEM	PA	PB	W	L																																															
Standard	1.80	2.50	4.50	6.20																																															
Alternate																																																			
No.of Pins Per Row 1*1~1*50	Insulator Material Option A=BK-PBT B=BK-PA66 C=BK-PA6T D=BK-PA46 E=BK-PA9T F=BK-LCP	Contact Plating G0:Gold Flash G1:3U" Gold G2:5U" Gold G3:10U" Gold G4:15U" Gold G5:30U" Gold S0:Gold Flash/Tin SN:Tin	Pin Length	Packing O=PE Bag A=Tray T=Tube P=Tube+Cap R=Reel+Cap M=Reel+Mylar																																															
B																																																			
A	<table border="1"><thead><tr><th>REV</th><th>DATE</th><th>MODIFICATION DESCRIPTION</th><th>CHANGE</th></tr></thead><tbody><tr><td>A0</td><td></td><td>NEW DRAWING</td><td></td></tr></tbody></table>			REV	DATE	MODIFICATION DESCRIPTION	CHANGE	A0		NEW DRAWING		<table border="1"><thead><tr><th colspan="2">OPERATION</th><th rowspan="2">DRAW</th><th rowspan="2">Ayang</th><th rowspan="2">SCALE</th><th rowspan="2">FIT</th></tr><tr><th>X.X</th><th>±0.30</th></tr></thead><tbody><tr><td>X.XX</td><td>±0.20</td><td>CHECK</td><td></td><td>UNIT</td><td>mm</td></tr><tr><td>X.XXX</td><td>±0.10</td><td rowspan="2">APPROVE</td><td rowspan="2"></td><td>SIZE</td><td>A4</td></tr><tr><td>Angle</td><td>±3'</td><td>SHEET</td><td>1/1</td></tr><tr><td>DIM</td><td>TOL</td><td>PROJ.</td><td></td><td>TITLE:</td><td></td></tr></tbody></table>			OPERATION		DRAW	Ayang	SCALE	FIT	X.X	±0.30	X.XX	±0.20	CHECK		UNIT	mm	X.XXX	±0.10	APPROVE		SIZE	A4	Angle	±3'	SHEET	1/1	DIM	TOL	PROJ.		TITLE:		<table border="1"><thead><tr><th>PART NO.</th><th>HC-PH72011XXXMXNX01(2)</th></tr></thead><tbody><tr><td>TITLE:</td><td>1.27mm H2.0 Single Row SMT Pin Header</td></tr></tbody></table>			PART NO.	HC-PH72011XXXMXNX01(2)	TITLE:	1.27mm H2.0 Single Row SMT Pin Header
REV	DATE	MODIFICATION DESCRIPTION	CHANGE																																																
A0		NEW DRAWING																																																	
OPERATION		DRAW	Ayang	SCALE	FIT																																														
X.X	±0.30																																																		
X.XX	±0.20	CHECK		UNIT	mm																																														
X.XXX	±0.10	APPROVE		SIZE	A4																																														
Angle	±3'			SHEET	1/1																																														
DIM	TOL	PROJ.		TITLE:																																															
PART NO.	HC-PH72011XXXMXNX01(2)																																																		
TITLE:	1.27mm H2.0 Single Row SMT Pin Header																																																		

Rated Current:1.0AMP
Contact Resistance:20mΩ Max
Withstand Voltage:500V AC/DC
Insulation Resistance:1000MΩ Min
Operation Temperature:-40℃ to +105℃

Contact Material:Brass
Contact Plating: Au or Sn Over Ni
Insulator Material:Polyester(UL94V-0)
Standard: PA6T
Max.Processing Temp: 230°C for 30-60 seconds
(260°C for 10 seconds)

HC-PH720 11 XX X M XX N XXX X 01(2)

No. of Pins	Insulator Material	Contact	Plating	Pin Length	Packing
Per Row	Option	G0:Gold	Flash		0=PE Bag
1*1~1*50	A=BK-PBT	G1:3U"	Gold		A=Tray
	B=BK-PA66	G2:5U"	Gold		T=Tube
	C=BK-PA6T	G3:10U"	Gold		P=Tube+Cap
	D=BK-PA46	G4:15U"	Gold		R=Reel+Cap
	E=BK-PA9T	G5:30U"	Gold		M=Reel+Mylar
	F=BK-LCP	S0:Gold	Flash/Tin		
		SN:Tin			

Dimension antitheses list				
ITEM	PA	PB	W	L
Standard	1.80	2.50	4.50	6.20
Alternate				

				OPERATION		DRAW	Ayang		SCALE	FIT	HECON 东莞市禾康电子有限公司 DONGGUAN HECON ELECTRONICS CO.,LTD	
				X.X	±0.30				UNIT	mm		
				X.XX	±0.20	CHECK			SIZE	A4	PART NO.	HC—PH72011XXXMXXNXXX01(2)
A0		NEW DRAWING		X.XXX	±0.10				SHEET	1/1		
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	Angle	±3°	APPROVE			PROJ.		TITLE:	1.27mm H2.0 Single Row SMT Pin Header
				DIM	TOL							