

1		2		3		4		5		6		7		8		9																																							
G		F		E		D		C		B		A		G		F		E		D		C		B		A																													
RoHS		Recommended P.C.B Layout(Top Side) (PCB BOARD TOLERANCE±0.05)										SPECIFICATIONS Rated Current:1.5AMP Contact Resistance:20mΩ Max Withstand Voltage:500V AC/DC Insulation Resistance:1000MΩ Min Operation Temperature:−40°c to +105°c Contact Material:Brass Contact Plating:Au or Sn Over Ni Insulator Material:Polyester(UL94V-0) Standard: PA6T Max.Processing Temp: 230°C for 30-60 seconds (260°C for 10 seconds)																																											
												Ordering Information HC-FH540 02 XX X N XX W U X 01 <table><tr><td>No.of Pins Per Row 2*2~2*40</td><td>Insulator Material Option A=BK-PBT B=BK-PA66 C=BK-PA6T D=BK-PA46 E=BK-PA9T F=BK-LCP</td><td>Contact Plating G0:Gold Flash G1:3U" Gold G2:5U" Gold G3:10U" Gold G4:15U" Gold G5:30U" Gold S0:Gold Flash/Tin SN:Tin</td><td>Packing A=Tray T=Tube P=Tube+Cap R=Reel+Cap M=Reel+Mylar</td></tr></table>										No.of Pins Per Row 2*2~2*40	Insulator Material Option A=BK-PBT B=BK-PA66 C=BK-PA6T D=BK-PA46 E=BK-PA9T F=BK-LCP	Contact Plating G0:Gold Flash G1:3U" Gold G2:5U" Gold G3:10U" Gold G4:15U" Gold G5:30U" Gold S0:Gold Flash/Tin SN:Tin	Packing A=Tray T=Tube P=Tube+Cap R=Reel+Cap M=Reel+Mylar																														
No.of Pins Per Row 2*2~2*40	Insulator Material Option A=BK-PBT B=BK-PA66 C=BK-PA6T D=BK-PA46 E=BK-PA9T F=BK-LCP	Contact Plating G0:Gold Flash G1:3U" Gold G2:5U" Gold G3:10U" Gold G4:15U" Gold G5:30U" Gold S0:Gold Flash/Tin SN:Tin	Packing A=Tray T=Tube P=Tube+Cap R=Reel+Cap M=Reel+Mylar																																																				
		<table><tr><td colspan="2">OPERATION</td><td rowspan="4">DRAW</td><td rowspan="4">Ayang</td><td rowspan="4">SCALE</td><td rowspan="4">FIT</td><td colspan="2" rowspan="4">HECON 东莞市禾康电子有限公司 DONGGUAN HECON ELECTRONICS CO.,LTD</td></tr><tr><td>X.X</td><td>±0.30</td></tr><tr><td>X.XX</td><td>±0.20</td></tr><tr><td>X.XXX</td><td>±0.10</td></tr><tr><td>A0</td><td>NEW DRAWING</td><td>Angle</td><td>±3'</td><td>APPROVE</td><td></td><td></td><td>PART NO.</td><td colspan="2">HC-FH54002XXXXXWUX01</td></tr><tr><td>REV</td><td>DATE</td><td colspan="2">MODIFICATION DESCRIPTION</td><td>CHANGE</td><td>DIM</td><td>TOL</td><td>PROJ.</td><td colspan="2">TITLE: 2.0mm H4.0 Dual Row Bottom Entry Female Header</td></tr></table>										OPERATION		DRAW	Ayang	SCALE	FIT	HECON 东莞市禾康电子有限公司 DONGGUAN HECON ELECTRONICS CO.,LTD		X.X	±0.30	X.XX	±0.20	X.XXX	±0.10	A0	NEW DRAWING	Angle	±3'	APPROVE			PART NO.	HC-FH54002XXXXXWUX01		REV	DATE	MODIFICATION DESCRIPTION		CHANGE	DIM	TOL	PROJ.	TITLE: 2.0mm H4.0 Dual Row Bottom Entry Female Header											
OPERATION		DRAW	Ayang	SCALE	FIT	HECON 东莞市禾康电子有限公司 DONGGUAN HECON ELECTRONICS CO.,LTD																																																	
X.X	±0.30																																																						
X.XX	±0.20																																																						
X.XXX	±0.10																																																						
A0	NEW DRAWING	Angle	±3'	APPROVE			PART NO.	HC-FH54002XXXXXWUX01																																															
REV	DATE	MODIFICATION DESCRIPTION		CHANGE	DIM	TOL	PROJ.	TITLE: 2.0mm H4.0 Dual Row Bottom Entry Female Header																																															
1		2		3		4		5		6		7		8		9																																							

Rated Current:1.5AMP
Contact Resistance:20mΩ Max
Withstand Voltage:500V AC/DC
Insulation Resistance:1000MΩ Min
Operation Temperature:-40°c to +105°c

Contact Material:Brass
Contact Plating:Au or Sn Over Ni
Insulator Material:Polyester(UL94V-0)
Standard: PA6T
Max.Processing Temp: 230°C for 30-60 seconds
(260°C for 10 seconds)

HC-FH540 02 XX X N XX W U X 01

Packing
A=Tray
T=Tube
P=Tube+Cap
R=Reel+Cap
M=Reel+Mylar

				OPERATION		DRAW	Ayang		SCALE	FIT	HECON 东莞市禾康电子有限公司 DONGGUAN HECON ELECTRONICS CO.,LTD						
				X.X	±0.30				UNIT	mm							
				X.XX	±0.20	CHECK			SIZE	A4	PART NO.	HC -FH54002XXXNXXWUX01					
				X.XXX	±0.10				SHEET	1/1							
A	AO	NEW DRAWING		Angle	±3'	APPROVE			PROJ.		TITLE:	2.0mm H4.0 Dual Row Bottom Entry Female Header					
	REV	DATE	MODIFICATION DESCRIPTION	CHANGE	DIM				TOL								
1		2		3		4		5		6		7		8		9	