

RoHS

Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE ± 0.05)

SPECIFICATIONS

Rated Current:3.0AMP

Contact Resistance:20m Ω Max

Withstand Voltage:1000V AC/DC

Insulation Resistance:1000M Ω Min

Operation Temperature:-40 $^{\circ}$ c to +105 $^{\circ}$ c





Contact Material:Brass

Contact Plating:Au or Sn Over Ni

Insulator Material:Polyester(UL94V-0)

Standard: PA6T

Max.Processing Temp: 230 $^{\circ}$ C for 30-60 seconds
(260 $^{\circ}$ C for 5 seconds)



Ordering Information

HC-PH425 2 2 XX X X XX M XXX X 02

No. of Pins Per Row 2x2~2x40	Insulator Material Option A=BK-PBT B=BK-PA66 C=BK-PA6T D=BK-PA46 E=BK-PA9T F=BK-LCP	Post W=With Post N=W/O Post	Contact Plating G0:Gold Flash G2:5U" Gold G3:10U" Gold G4:15U" Gold G5:30U" Gold S0:Gold Flash/Tin SN:Tin	Pin Length	Packing 0=PE Bag A=Tray T=Tube P=Tube+Cap R=Reel+Cap
------------------------------------	--	-----------------------------------	--	------------	---

Dimension antitheses list					
ITEM	PA	D	PB	W	L
Standard	6.00	1.20	6.90	7.50	14.8
Alternate					

OPERATION

X.X ± 0.30

X.XX ± 0.20

X.XXX ± 0.10

Angle $\pm 3^{\circ}$

DIM TOL

DRAW

Ayang

CHECK

APPROVE

SCALE

FIT

UNIT

mm

SIZE

A4

SHEET

1/1

PROJ.

1/1

HECON 东莞市禾康电子有限公司
DONGGUAN HECON ELECTRONICS CO.,LTD

PART NO.

HC-PH42522XXXXXXMXXXX02

TITLE:

2.54mm H2.5x2 Dual Row SMT Pin Header

A0

REV

DATE

MODIFICATION DESCRIPTION

CHANGE

DIM

TOL

NEW DRAWING

1

2

3

4

5

6

7

8

9