



RoHS

Technical Specs:

Flammability: PPS (UL 94V-O)
Sleeve: Brass
Contact clip(6 finger): C17200
Accepted pin: Ø0.31 to 0.48mm
Forces: (polished steel gauge Ø0.381mm)
--Insertion 0.6N typ
--Withdrawal 0.15N typ
Mechanical life: min500 cycles
Rated current: 1A
Contact resistance: max 20mΩ
Dielectric resistance: Min 500V RMS



Ordering Information

HC-MF724 41 1 XX R XX 089 02

Insulator Type
Code
1: Single row
2: Double row

No. of
Pins
1x40 Pins
2x40 Pins

Contact Plating
SN: Tin
G0: Gold Flash
G2: 2U" Gold
G3: 3U" Gold
G4: 5U" Gold
G5: 10U" Gold
S0: Gold Flash/Tin
Standard: G0

Pin
Length
089=8.9mm

OPERATION

X.X ±0.30

X.XX ±0.20

X.XXX ±0.10

Angle ±3°

DIM TOL

DRAW

Ayang

CHECK

APPROVE

SCALE

FIT

UNIT

mm

SIZE

A4

SHEET

1/1

PROJ.

◆

HECON 东莞市禾康电子有限公司
DONGGUAN HECON ELECTRONICS CO.,LTD

PART NO.

HC-MF724411XXRXX08902

TITLE:

1.27x4.1mm Machine Female Header Right
Angle L=8.9