



RoHS



Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)



SPECIFICATIONS

Rated Current:1.5AMP

Contact Resistance:20mΩ Max

Withstand Voltage:500V AC/DC

Insulation Resistance:1000MΩ Min

Operation Temperature:-40°c to +105°c


Contact Material:Brass

Contact Plating:Au or Sn Over Ni

Insulator Material:Polyester(UL94V-0)

Standard: PA6T

Max.Processing Temp: 230°C for 30-60 seconds
(260°C for 5 seconds)



Dimension antitheses list					
ITEM	PA	D	PB	W	L
Standard	4.00	0	3.50	6.50	9.30
Alternate					

Ordering Information

HC-PH515 2 2 XX X X XX M XXX X 02

No.of
Pins
Per Row
2*2~2*40

Insulator Material
Option
A=BK-PBT
B=BK-PA66
C=BK-PA6T
D=BK-PA46
F=BK-LCP

Post
W=With Post
N=W/O Post

Contact Plating
G0:Gold Flash
G1:3U" Gold
G2:5U" Gold
G3:10U" Gold
G4:15U" Gold
G5:30U" Gold
S0:Gold Flash/Tin
SN:Tin

Pin Length
Packing
0=PE Bag
A=Tray
T=Tube
P=Tube+Cap
R=Reel+Cap

OPERATION

X.X ±0.30

X.XX ±0.20

X.XXX ±0.10

Angle ±3°

DIM TOL

DRAW

Ayang

CHECK

APPROVE

SCALE

FIT

UNIT

mm

SIZE

A4

SHEET

1/1

PROJ.

1/1

HECON 东莞市禾康电子有限公司
DONGGUAN HECON ELECTRONICS CO.,LTD

PART NO.

HC-PH51522XXXXXXMXXXX02

TITLE:

2.0mm H1.5x2 Dual Row SMT Pin Header

A0

NEW DRAWING

REV

DATE

MODIFICATION DESCRIPTION

CHANGE