







RoHS



Dimension antitheses list					
ITEM	PA	PB	D	W	L
Standard	8.00	6.50	0.40	10.00	18.8
Alternate					

Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)



SPECIFICATIONS

Rated Current:7.0AMP

Contact Resistance:20mΩ Max

Withstand Voltage:500V AC/DC

Insulation Resistance:1000MΩ Min

Operation Temperature:-40°c to +105°c

Contact Material:Brass

Contact Plating:Au or Sn Over Ni

Insulator Material:Polyester(UL94V-0)

Standard: LCP

Max.Processing Temp: 230°C for 30-60 seconds
(260°C for 5 seconds)

Ordering Information

HC-PH225 21 XX F N XX M XXX X 01(2)

No.of
Pins
Per Row
1x1~1x20

Insulator Material
Option
A=BK-PBT
B=BK-PA66
C=BK-PA6T
D=BK-PA46
F=BK-LCP

Contact Plating
Option
G0:Gold Flash
S0:Gold Flash/Tin
SN:Tin
SM:Matte-Tin

Pin Length
Option
0=PE Bag
A=Tray
T=Tube
R=Reel+Cap

Packing
Option
0=PE Bag
A=Tray
T=Tube
R=Reel+Cap

OPERATION

X.X ±0.30

X.XX ±0.20

X.XXX ±0.10

Angle ±3°

DIM TOL

DRAW

Ayang

CHECK

APPROVE

SCALE

FIT

UNIT

mm

SIZE

A4

SHEET

1/1

PROJ.

Φ

HECON

东莞市禾康电子有限公司
DONGGUAN HECON ELECTRONICS CO.,LTD

PART NO.

HC-PH22521XXFNXXMXXX01(2)

TITLE:

5.08mm H2.5x2 Single Row SMT Pin Header

A0

REV

DATE

NEW DRAWING

MODIFICATION DESCRIPTION

CHANGE