




RoHS



Specifications:

Contact Resistance: 30mΩ max. at DC 100 mA

Insulator Resistance: 1000 MΩ min. at DC 500V

Current Rating: 5AMP.

Dielectric Withstanding

Voltage: AC 500V For 1minute

Operating Temperature: -55°C+105°C

Contact: Brass

Housing: PBT+30% Glass Fiber (UL94v-0)

PIN	A	B	C
9	30.80	24.99	16.90
15	39.20	33.30	25.25
25	53.10	47.04	38.96
37	69.34	63.50	55.42

Ordering Information

HC-6235-4	XX	M	XX	X	01
No. of Pins 09,15, 25,37P	Connector Type F=Female M=Male	Contact Plating G0=Gold Flash G1:3u" Gold G2:5u" Gold G3:10u" Gold G4:15u" Gold S0=Gold Flash/Ni	Color B=Black U=Blue		

OPERATION

X.X ±0.30

X.XX ±0.20

X.XXX ±0.10

Angle ±3°

DIM TOL

DRAW

Ayang

CHECK

APPROVE

SCALE

FIT

UNIT

mm

SIZE

A4

SHEET

1/1

PROJ.

◆

HECON 东莞市禾康电子有限公司
DONGGUAN HECON ELECTRONICS CO.,LTD

PART NO.

HC-6235-4XXMXX01

TITLE:

D_SUB NPin IDC TYPE
Male