

</

SPECIFICATIONS

Rated Current:1.5AMP

Contact Resistance: 20mΩ Max

Withstand Voltage:500V AC/DC

Insulation Resistance: 1000MΩ Min

Operation Temperature: -40°C to $+105^{\circ}\text{C}$

Contact Material:Brass

Contact Plating: Au or Sn Over Ni

Insulator Material: Polyester (UL94V-0)

Standard: PA6T

Max. Processing Temp: 230°C for 30–60 seconds
(260°C for 10 seconds)

HC-FH572 02 XX X N XX S U X 01

No. of Pins Per Row
2*40

Insulator Material
Option
A=BK-PBT
B=BK-PA66
C=BK-PA6T
D=BK-PA46
F=BK-LCP

Contact Plating
G0:Gold Flash
G2:5U" Gold
G3:10U" Gold
G4:15U" Gold
G5:30U" Gold
S0:Gold Flash/Tin
SN:Tin

Packing
0=Pe Bag
T=Tube
P=Tube+Cap

Dimension antitheses list	
ITEM	PC
Standard	2.50
Alternate	

OPERATION	
X.X	± 0.30
X.XX	± 0.20
X.XXX	± 0.10
Angle	$\pm 3^\circ$
DIM	TOL

DRAW

Ayang

SCALE	FIT
UNIT	mm
SIZE	A4
SHEET	1/1
PROJ.	

FIT

mm

SIZE	A4
------	----

QUEST	
-------	--

Sheet:	1/1

PROJ.	
-------	---

HECON

东莞市禾康电子有限公司
DONGGUAN HECON ELECTRONICS CO.,LTD

PART NO.

HC-FH57202XXXNXXSUX01

TITLE:

2.0mm H7.2 Dual Row Straight Female Header