

	1	2	3	4	5	6	7	8	9																																													
G	RoHS																																																					
F	No.of Pinsx1.27+0.41±0.30 (No.of Pins-1)x1.27±0.15 1.27±0.05 1.27±0.05 3.30±0.20				Technical Specs: Insulator: Flammability: Sleeve: Contact clip(3 finger): Accepted pin: Forces: --Insertion --Withdrawal Mechanical life: Rated current: Contact resistance: Dielectric resistance: Black glass filled polyester PPS UL 94V-0 Brass (H59-3) Beryllium copper(C17300) Ø0.38 to 0.50mm (polished steel gauge Ø0.41mm) 0.5 N typ 0.2 N typ min500 cycles 1A max 20mΩ Min 500V RMS																																																	
E																																																						
D	1.27±0.05 3.80±0.20				1.27±0.05 6.40±0.25 2.60±0.25 ø0.46																																																	
C					Ordering Information HC-MF724 38 2 XX S XX 064 01 Insulator Type Code 1:Single row 2:Doube row No.of Pins 1x40Pins 2x40Pins Contact Plating SN:Tin G0:Gold Flash G2:2U''Gold G3:3U''Gold G4:5U''Gold G5:10U''Gold S0:Gold Flash/Tin Standard:G0 Pin Length 064=6.4mm																																																	
B																																																						
A	<table border="1"><thead><tr><th colspan="2"></th><th colspan="2">OPERATION</th><th rowspan="2">DRAW</th><th rowspan="2">Ayang</th><th rowspan="2">SCALE</th><th rowspan="2">FIT</th><th colspan="2" rowspan="2">HECON 东莞市禾康电子有限公司 DONGGUAN HECON ELECTRONICS CO.,LTD</th></tr><tr><th colspan="2"></th><th>X.X</th><th>±0.30</th></tr></thead><tbody><tr><td colspan="2"></td><td>X.XX</td><td>±0.20</td><td rowspan="2">CHECK</td><td rowspan="2"></td><td rowspan="2">UNIT</td><td rowspan="2">mm</td><td colspan="2" rowspan="2">PART NO. HC -MF724382XXSX06401</td></tr><tr><td colspan="2"></td><td>X.XXX</td><td>±0.10</td></tr><tr><td colspan="2">A0</td><td colspan="2">NEW DRAWING</td><td rowspan="2">APPROVE</td><td rowspan="2"></td><td rowspan="2">SIZE A4</td><td rowspan="2">SHEET 1/1</td><td colspan="2" rowspan="2">TITLE: 1.27x3.8mm Machine Female Header Straight L=6.4</td></tr><tr><td colspan="2">REV</td><td>DATE</td><td>MODIFICATION DESCRIPTION</td><td>CHANGE</td><td>DIM TOL</td><td>PROJ.</td></tr></tbody></table>						OPERATION		DRAW	Ayang	SCALE	FIT	HECON 东莞市禾康电子有限公司 DONGGUAN HECON ELECTRONICS CO.,LTD				X.X	±0.30			X.XX	±0.20	CHECK		UNIT	mm	PART NO. HC -MF724382XXSX06401				X.XXX	±0.10	A0		NEW DRAWING		APPROVE		SIZE A4	SHEET 1/1	TITLE: 1.27x3.8mm Machine Female Header Straight L=6.4		REV		DATE	MODIFICATION DESCRIPTION	CHANGE	DIM TOL	PROJ.					
		OPERATION		DRAW	Ayang	SCALE	FIT	HECON 东莞市禾康电子有限公司 DONGGUAN HECON ELECTRONICS CO.,LTD																																														
		X.X	±0.30																																																			
		X.XX	±0.20	CHECK		UNIT	mm	PART NO. HC -MF724382XXSX06401																																														
		X.XXX	±0.10																																																			
A0		NEW DRAWING		APPROVE		SIZE A4	SHEET 1/1	TITLE: 1.27x3.8mm Machine Female Header Straight L=6.4																																														
REV		DATE	MODIFICATION DESCRIPTION							CHANGE	DIM TOL	PROJ.																																										
	1	2	3	4	5	6	7	8	9																																													

[illegible][illegible][illegible]

	1	2	3	4	5	6	7	8	9																																								
G	RoHS																																																
F	 No.of Pinsx $1.27\pm 0.41 \pm 0.30$ (No.of Pins-1)x 1.27 ± 0.15 1.27 ± 0.05 3.30 ± 0.20				Technical Specs: Insulator: Black glass filled polyester PPS Flammability: UL 94V-0 Sleeve: Brass (H59-3) Contact clip(3 finger): Beryllium copper(C17300) Accepted pin: $\varnothing 0.38$ to 0.50mm Forces:(polished steel gauge $\varnothing 0.41$ mm) --Insertion 0.5 N typ --Withdrawal 0.2 N typ Mechanical life:min500 cycles Rated current: 1A Contact resistance:max 20mΩ Dielectric resistance:Min 500V RMS																																												
E																																																	
D	 1.27 ± 0.05 3.80 ± 0.20 6.40 ± 0.25 2.60 ± 0.25 $\phi 0.46$																																																
C					Ordering Information HC-MF724 38 2 XX S XX 064 01 └─ Insulator Type Code ─┘ └─ No.of Pins ┘ Contact Plating SN:Tin G0:Gold Flash G2:2U''Gold G3:3U''Gold G4:5U''Gold G5:10U''Gold S0:Gold Flash/Tin Standard:G0 1:Single row 2:Doube row 1x40Pins 2x40Pins Pin Length 064=6.4mm																																												
B																																																	
A	<table border="1"><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2">OPERATION</td><td rowspan="2">DRAW</td><td rowspan="2">Ayang</td><td rowspan="2">SCALE</td><td rowspan="2">FIT</td><td rowspan="4">HECON 东莞市禾康电子有限公司 DONGGUAN HECON ELECTRONICS CO.,LTD</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td>X.X</td><td>±0.30</td><td rowspan="2">CHECK</td><td rowspan="2">UNIT mm</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td>X.XX</td><td>±0.20</td><td rowspan="2">APPROVE</td><td rowspan="2">SIZE A4</td><td>PART NO.</td><td>HC –MF724382XXSX06401</td></tr><tr><td colspan="2">REV</td><td colspan="2">DATE</td><td colspan="2">MODIFICATION DESCRIPTION</td><td colspan="2">CHANGE</td><td>SHEET 1/1</td><td>TITLE:</td><td>1.27x3.8mm Machine Female Header Straight L=6.4</td></tr></table>													OPERATION		DRAW	Ayang	SCALE	FIT	HECON 东莞市禾康电子有限公司 DONGGUAN HECON ELECTRONICS CO.,LTD					X.X	±0.30	CHECK	UNIT mm					X.XX	±0.20	APPROVE	SIZE A4	PART NO.	HC –MF724382XXSX06401	REV		DATE		MODIFICATION DESCRIPTION		CHANGE		SHEET 1/1	TITLE:	1.27x3.8mm Machine Female Header Straight L=6.4
				OPERATION		DRAW	Ayang	SCALE	FIT	HECON 东莞市禾康电子有限公司 DONGGUAN HECON ELECTRONICS CO.,LTD																																							
				X.X	±0.30						CHECK	UNIT mm																																					
				X.XX	±0.20	APPROVE	SIZE A4	PART NO.	HC –MF724382XXSX06401																																								
REV		DATE		MODIFICATION DESCRIPTION				CHANGE			SHEET 1/1	TITLE:	1.27x3.8mm Machine Female Header Straight L=6.4																																				

	1	2	3	4	5	6	7	8	9																																																												
G	RoHS																																																																				
F	No.of Pinsx1.27+0.41±0.30 (No.of Pins-1)x1.27±0.15 1.27±0.05 1.27±0.05 3.30±0.20																																																																				
E	3.80±0.20 1.27±0.05																																																																				
D	1.27±0.05 6.40±0.25 2.60±0.25 ø0.46																																																																				
C			Ordering Information HC-MF724 38 2 XX S XX 064 01 Insulator Type Code 1:Single row 2:Doube row No.of Pins 1x40Pins 2x40Pins Contact Plating SN:Tin G0:Gold Flash G2:2U"Gold G3:3U"Gold G4:5U"Gold G5:10U"Gold S0:Gold Flash/Tin Standard:G0 Pin Length 064=6.4mm																																																																		
B																																																																					
A			<table><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2">OPERATION</td><td rowspan="2">DRAW</td><td rowspan="2">Ayang</td><td rowspan="2">SCALE</td><td rowspan="2">FIT</td><td colspan="2" rowspan="2">HECON 东莞市禾康电子有限公司 DONGGUAN HECON ELECTRONICS CO.,LTD</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td>X.X</td><td>±0.30</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td>X.XX</td><td>±0.20</td><td rowspan="2">CHECK</td><td rowspan="2"></td><td rowspan="2"></td><td rowspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td>X.XXX</td><td>±0.10</td></tr><tr><td colspan="2">A0</td><td colspan="2">NEW DRAWING</td><td colspan="2"></td><td>Angle</td><td>±3'</td><td rowspan="2">APPROVE</td><td rowspan="2"></td><td rowspan="2"></td><td rowspan="2"></td></tr><tr><td colspan="2">REV</td><td colspan="2">DATE</td><td colspan="2">MODIFICATION DESCRIPTION</td><td colspan="2">CHANGE</td><td>DIM</td><td>TOL</td></tr></table>											OPERATION		DRAW	Ayang	SCALE	FIT	HECON 东莞市禾康电子有限公司 DONGGUAN HECON ELECTRONICS CO.,LTD						X.X	±0.30							X.XX	±0.20	CHECK										X.XXX	±0.10	A0		NEW DRAWING				Angle	±3'	APPROVE				REV		DATE		MODIFICATION DESCRIPTION		CHANGE		DIM	TOL
				OPERATION		DRAW	Ayang	SCALE	FIT	HECON 东莞市禾康电子有限公司 DONGGUAN HECON ELECTRONICS CO.,LTD																																																											
				X.X	±0.30																																																																
						X.XX	±0.20	CHECK																																																													
						X.XXX	±0.10																																																														
A0		NEW DRAWING				Angle	±3'	APPROVE																																																													
REV		DATE		MODIFICATION DESCRIPTION		CHANGE						DIM	TOL																																																								
	1	2	3	4	5	6	7	8	9																																																												

[illegible]