

L2KQ201LFA2-PT

2MP AI Smart Hybrid Light POE Network Metal Bullet Camera (Voice Intercom,Broadcast,TF Card



Model Number	L2KQ201LFA2-PT
Camera	
Image Sensor	1/2.9" color CMOS
Min. Illumination	Color: 0.001ux @F1.2, B/W: 0Lux with IR on
Lens	Special Starlight 3.6mm
Shutter Time	Auto
Feature	
Light Distance	Full Color Light Distance:10-15m,IR Distance:30-35m
IR LEDs	3pcs Infrared LEDs and Hybrid light core
Day & Night Mode	Hybrid Light Mode: B/W night vision, when alarm triggered hybrid light is on, and then full color vision
	Infrared Mode: B/W
	Full Color: the LEDs will auto-adjust its brightness according to the varying degrees of light brightness
White Balance	Auto / Manual
AGC	Low/Mid-Low/Mid/Mid-High/High
WDR	Digital WDR
DNR	2D/3D DNR
BLC	support
HLC	support

Video	
Max. Image Resolution	1080P(1920x1080)@25/30fps,3MP(2304*1296)@20fps
Video Compression	H265/H264
Frame Rate	Main code stream:1080P@25/30fps, 3MP@20fps Auxiliary stream: D1/VGA@25/30fps
Video Bit Rate	160Kbps-4000Kbps support self-adjustable as needed
Image Settings	Brightness,Contrast,Saturation,Exposure,Upside Down,Mirror Adjustable
Bit Superposition	Support OSD name, time and date information superposition
Web Access	Google Kernel Browser(Plugin Free)
Audio	
Audio Input	Support, built-in microphones
Audio Output	Support, built-in speaker
Voice Broadcast Alarm	Built-in 8 different broadcast options
Audio Compression	G.711/64k
Network	
Network Interface	1*RJ45 10M/100M Ethernet Port
Networking Protocol	TCP/IP,UDP,HTTP,HTTPS,DHCP,RTSP,NTP
ONVIF	ONVIF2.6
APP	Through the NVR
PC	Support
System	
Alarm	Motion detection alarm, AI humanoid detection and tracking
Human Detection	It can detect target ≤5 persons at the same time
	Humanoid pixel ≥40X40
	Support specified area detection, default full screen
	Error detection rate 2% or less
	Maximum detection frame rate is 5fps /s
Storage	Support TF card storage, max 512G
Motion Detection	22*18 windows motion detection areas can be setting (sensitivity setting 0-5)
Area Occlusion Alarm	Support
Video Mask	4 windows can be built to mask your private area
Action with Alarm	Relying on the NVR
General	
Language Support	CHN(S)/CHN(T)/ENG
POE	IEEE802.3af
Power Supply	DC12V±10% / POE
Power Consumption	Max 4W
Lightning Protection	6KV
Housing	Metal Bullet

Weather Proof	IP67
Working Temperature	-30 °C to 85 °C
Working Humidity	10%-95% (Non-condensing)

