


## T30-G1,G2,G3,G4,G5,G6

3.0MP Smart 4G Solar Battery Camera (Low Power Consumption Working Mode)



| Model             | T30-G1   T30-G2   T30-G3   T30-G4   T30-G5   T30-G6  |
|-------------------|------------------------------------------------------|
| <b>Camera</b>     |                                                      |
| Image Sensor      | 1/2.7" color CMOS                                    |
| Effective Pixels  | 3.0MP                                                |
| Synchronization   | Internal                                             |
| Code Format       | H265                                                 |
| Stream            | Dual-stream                                          |
| Min. Illumination | Color 0.01 lux@F1.2, 0 Lux IR Open                   |
| Day & Night Mode  | Color/B&W                                            |
| IR LEDs           | 4pcs Infrared LEDs and Dual light core               |
| Light Distance    | Full Color Light Distance:15-20m, IR Distance:15-20m |
| WDR               | Digital WDR                                          |
| Focal Length      | 2.8mm                                                |
| Lens Megapixel    | 3 Megapixel fixed lens                               |
| PTZ Angle         | Horizontal 355°, Vertical 100°                       |
| PTZ Speed         | Horizontal 55°/S, Vertical 40°/S                     |
| <b>Power</b>      |                                                      |

# Ubox 4G Solar Battery Camera Series | T30-G1,G2,G3,G4,G5,G6 **mapesen®**

|                                                      |                                                                        |
|------------------------------------------------------|------------------------------------------------------------------------|
| Power Supply Mode                                    | Solar panel + built-in batteries                                       |
| Solar Panel                                          | 6W monocrystalline silicon                                             |
| Battery                                              | 7800MA, 3pcs 18650 batteries                                           |
| Solar panel waterproof                               | IP66                                                                   |
| Solar connection                                     | Waterproof DC interface,Line length 3m                                 |
| Installation mode                                    | Installation of solar panels in one body or separate body              |
| <b>4G</b>                                            |                                                                        |
| 4G European Version<br>(Model: <b>T30-G1</b> )       | LTE-FDD B1/B3/B5/B7/B8/B20                                             |
| 4G US Version<br>(Model: <b>T30-G2</b> )             | LTE-FDD B2/B4/B5/B12/B13/B25/B26                                       |
| 4G Australia Version<br>(Model: <b>T30-G3</b> )      | LTE-FDD B1/B2/B3/B4/B5/B7/B8/B28/B66                                   |
| 4G Japan Version<br>(Model: <b>T30-G4</b> )          | LTE-FDD B1/B3/B8/B18/B19/B26                                           |
| 4G China Version<br>(Model: <b>T30-G5</b> )          | LTE-FDD B1/B3/B5/B8<br>LTE-TDD B34/B38/B39/B40/B41                     |
| 4G Southeast Asia Version<br>(Model: <b>T30-G6</b> ) | LTE -FDD B1/B3/B5/B8<br>LTE -TDD B34/B38/B39/B40/B41                   |
| <b>Functions</b>                                     |                                                                        |
| Intelligent Alarm                                    | PIR Human detection and AI Humanoid detection,0~12m detection distance |
| Working Mode                                         | Ultra-low power standby, quick wake up in 0.2 seconds                  |
| Detection Angle                                      | 105°                                                                   |
| Alarm Linkage                                        | The mobile detection alarm is pushed to the APP                        |
| Audio                                                | Built-in microphone and speaker, Support voice intercom                |
| Storage                                              | Built-in Micro SD card slot, Max 128G                                  |
| Cloud Storage                                        | Support                                                                |
| Video mode                                           | Alarm video                                                            |
| WIFI                                                 | No                                                                     |
| P2P                                                  | Support                                                                |
| Mobile Surveillance                                  | IOS, Android (Ubox)                                                    |
| PC                                                   | No                                                                     |
| ONVIF                                                | No                                                                     |
| <b>Interface</b>                                     |                                                                        |
| Ethernet                                             | No                                                                     |
| Power                                                | 1pcs DC female head (DC5V)                                             |
| Storage                                              | 1pcs Micro SD card                                                     |
| Antenna                                              | Built-in WiFi antenna                                                  |
| Reset                                                | Support                                                                |

| General             |                                |
|---------------------|--------------------------------|
| Charge voltage      | DC 5V                          |
| Power consumption   | Max 3W (work) 0.003W (standby) |
| Language Support    | ENG                            |
| Working Environment | Indoor /outdoor                |
| Weather Proof       | IP66                           |
| Working Temperature | -10 °C to +60 °C               |
| Working Humidity    | 10%-90% RH (Non-condensing)    |