

NVR-4K824128S-R

128CH 4K(8MP) 4U 24 HDD Network Digital Video Recorder



Model	NVR-4K824128S-R
System	
Operating System	Embedded LINUX
Max Preview Channel	64CH(Display Page Turnable)
Video & Audio Input	
Incoming Bandwidth	640Mbps
IPC Input	128CH*4K/5MP/3MP/2MP/960P/720P
Video & Audio Decoding	
IP channel Resolution	Main stream: up to 3840×2160 Auxiliary stream: D1/CIF
Video Decoding	H.265 /H.264
Audio Decoding	G.711A/G.711U/ACC
Preview/Playback	8MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Capability	4CH@4k,16CH@1080P
Recording & Playback	

Recording Mode	Timing recording or alarm recording, Time recording, Alarm recording, Stop recording
Playback	4CH@4k,16CH@1080P
Playback Mode	Search by time, calendar, event, channel
Backup Mode	USB Device/Network
Other Function	
Smart Functions	Humanoid Detection,Target Count, Object Left/Lost, Electronic Fence, Line Crossing, Retrograde Detection, Leave Position Detection (need front end IPC supported)
Motion Detection	Support
Online Upgrade	Supports online NVR upgrade
IPC Upgrade	Support (specified model IPC)
Storage	
SATA	24*SATA HDD
Capacity	Max 8T HDD
E-SATA	1pcs
Disk Array	RAID0,RAID1,RAID5,RAID6,RAID10
IPSAN	Support
Network	
Network Protocols	DDNS,EMAIL,UPNP,NTP,DHCP,RTSP,PPPoE,P2P
ONVIF	Support
APP	IPhone, Android
PC	Support
Interface	
Network Interface	2pcs RJ45 10M/100M/1000M self-adaptive Ethernet interface
USB Interface	3pcs USB Interfaces (1pcs 3.0)
Video Output	VGA: 1CH,1920×1080,1280×1024,1280×720,1024×768
	HDMI:1CH,3840*2160, 1920×1080,1280×1024,1280×720,1024×768
Audio I/O	1/1(RCA); HDMI Output
Alarm I/O	4/4
RS485	Support
General	
Installation	Desktop Installation
Power Supply	AC 110V-220V 200W 50-60HZ
Consumption	≤50W(without HDD)
Working Conditions	Temperature: -10°C- +55°C Humidity: 10%~90%

Dimensions	Equipment: 480X620X178mm, Packing: 726X551X275mm
Weight	N.W.: 21Kg; With Package: 22Kg(without HDD)