



YF-40RW

YF-05RW YF-20RW
YF-10RW YF-30RW
YF-15RW **YF-40RW**



EXCAVATOR

45-60_{ton}

PRODUCT APPLICATIONS

- Tunnels and roadways: excavation and treatment of walls, roofs, corners, contours, trenches, etc.;
- Road engineering: cutting or excavation of concrete structures, side trenches, slopes and auxiliary facilities, cleaning of damaged cement or asphalt pavements, etc.;
- Water conservancy project: concrete structure treatment, riverbed cleaning, cleaning or dismantling of damaged structures, etc.;
- Municipal engineering: excavation or treatment of pipeline trenches, foundations, structures, cleaning or dismantling of damaged municipal facilities, etc.;
- Open-pit coal mining: excavation and mining of coal mines and mines, etc.

PRODUCT PARAMETER (SPECIFICATION)

Max Power Output	140 kW	Output Torque	33450 Nm@320bar
Max Flow	550 LPM	Output Shaft Speed	60 RPM@500LPM
Recommended Flow	400-600 LPM	Weight	2100 kgs
Pressure	≤450 bar	Cutter Bit	64 pcs

Note: If oil specification is below 46 centistokes at 40 °C (ISO HV46) the performance must be down rated.
Please contact YICHEN for further information.



APPLICATIONS



Tunneling



Utility Work



Roadworks



Mining



Excavation



Structure-Shaping

*The data provided above is not binding, as the manufacturer reserves itself the right to make improvements to its products at any time and with no advance notice.