



YS-30DS

YS-30DS	YS-15SS
YS-20DS	YS-10SS
YS-20SS	YS-05SS



EXCAVATOR

30-45_{ton}

PRODUCT APPLICATIONS

- Building demolition, cutting reinforced concrete, cement pavement, highway construction and maintenance operations.
- Crushing operation after cutting hard rock.
- Excavation of foundation, rock and concrete of basement.
- Underground cable trench cutting operation.
- Quarry excavation operations, rock waste reshaping, cutting and other operations.
- Rocky tunnel excavation, rocky trench excavation and other operations.

PRODUCT PARAMETER (SPECIFICATION)

Max Power Output	120 kW	Weight	1350 kg
Max Flow	300 LPM	Saw Blade spec.	Φ 2200- 3500x9.5 mm
Recommended Flow	180- 300 LPM	Distance Between Blades	1 m
Max Pressure	450 bar		1.2 m
Output Torque	9850Nm@350bar		1.4 m
Output Shaft Speed	0- 250 RPM	Applicable Materials	granite, basalt, marble, reinforced concrete

Note: This dual blade rock saw can also work with only one saw.



APPLICATIONS



Demolition



Tunneling



Stone Production



Roadworks



Quarries



Trenching



Metal cutting

*The data provided above is not binding, as the manufacturer reserves itself the right to make improvements to its products at any time and with no advance notice.