SIEMENS

Data sheet 3KD3440-2NE10-0

Switch disconnector 160 A, Size 2, 4-pole Front operating mechanism left Basic unit without handle Box terminal

Model	
product brand name	SENTRON
product designation	3KD switch disconnector
design of the product	Switch
display version for switch position indicator door-coupling rotary operating mechanism	ON-OFF
design of the actuating element	Without handle
type of the driving mechanism	Front operating mechanism
type of the driving mechanism motor drive	No
General technical data	
number of poles	4
type of device	fixed mounting
size of switch disconnector	2
mechanical service life (operating cycles) typical	15 000
electrical endurance (operating cycles)	
● at AC-23 A at 690 V	1 500
● at DC-23 A at 440 V	1 000
I2t value	
● with closed switch at 1000 V for combination switch +gG/aM SITOR fuse maximum	19 815 $A^2 \cdot s$
● of the fuse at 500 V maximum permissible	223 005 $A^2 \cdot s$
● of the gG fuse at 690 V maximum permissible	226 005 $A^2 \cdot s$
● of the gG/aM SITOR fuse at 1000 V maximum permissible	48 000 $A^2 \cdot s$
● of the molded case circuit breaker at 415 V maximum permissible	560 000 $A^2 \cdot s$
position of the switch operating mechanism	at the left end
overvoltage in percent relative to the operating voltage at AC at 400, 500, 690 V at 50/60 Hz	10 %
overvoltage category	III
degree of pollution	3
Voltage	
operating voltage with current paths in series	
● with degree of pollution 2 at DC rated value	440 V / 3
● with degree of pollution 3 at DC rated value	440 V / 3
insulation voltage	
● rated value	1 000 V
surge voltage resistance rated value	8 kV
operational current at AC-22 A at 1000 V maximum	160 A
Protection class	
protection class IP	IP20
protection class IP	

Subject to change without notice
© Copyright Siemens

● with closed switch with cover or cable lug cover	IP20
● on the front	IP20
Dissipation	
power loss [W]	
● with conventional rated thermal current per pole	4.6 W
● with conventional rated thermal current per device	18.4 W
● for rated value of the current at AC in hot operating state per pole	4.6 W
Main circuit	
operating power	
● at AC-23 A at 500 V rated value	110 kW
operational current rated value	160 A
Auxiliary circuit	
number of connected NC contacts for auxiliary contacts	0
number of connected NO contacts for auxiliary contacts	0
number of connected CO contacts for auxiliary contacts	0
number of CO contacts for auxiliary contacts	4
number of NC contacts for auxiliary contacts	0
number of NO contacts for auxiliary contacts	0
Suitability	
suitability for use	
● main switch	Yes
● switch disconnector	Yes
● EMERGENCY OFF switch	Yes
● safety switch	Yes
● maintenance/repair switch	Yes
Product details	
product component	
● trip indicator	No
● voltage trigger	No
● undervoltage release	No
● undervoltage release with leading contact	No
product extension auxiliary switch	Yes
product extension optional	
● motor drive	No
● voltage trigger	No
Short circuit	
short-time withstand current (Icw) at 1000 V AC/440 V DC limited to 1 s rated value	4 kA
short-circuit current making capacity (Icm) for switch disconnector	
● at 400 V AC without fuse link rated value minimum	30 kA
● at 1000 V AC without fuse link rated value minimum	12 kA
● at DC 440 V without fuse link rated value minimum	12 kA
● without fuse link rated value minimum	12 kA
conditional short-circuit current with line-side fuse protection	
● at 415 V by molded case circuit breaker rated value	65 kA
● at 500 V by gG fuse rated value	100 kA
● at 690 V by gG fuse rated value	100 kA
Connections	
type of connectable conductor cross-sections with flexible busbar	3x (0.8x14 mm²)
type of connectable conductor cross-sections	
● for copper busbar	'1 x (3 x 14 mm²)
type of connectable conductor cross-sections for copper conductor	
● solid	1x (2.5 ... 16 mm²)
● finely stranded with core end processing	1x (2.5 ... 70 mm²)
● stranded	1x (10 ... 70 mm²)
type of electrical connection for main current circuit	box terminal
Mechanical Design	
height	126 mm

Subject to change without notice
© Copyright Siemens

width	148 mm
depth	68 mm
fastening method	Screw fixing and standard rail mounting 35 mm
fastening method	
● 4-hole front mounting	No
● front mounting with central attachment	No
● rail mounting	Yes
mounting position	any
net weight	1 431 g
Environmental conditions	
ambient temperature during operation	
● minimum	-25 °C
● maximum	70 °C
ambient temperature during storage	
● minimum	-50 °C
● maximum	80 °C
Certificates	
reference code according to IEC 81346-2	Q

Approvals Certificates

General Product Approval

UK CA	CE EG-Konf.	Confirmation	CCC	VDE	Miscellaneous

General Product Approval	Test Certificates	Marine / Shipping		other	
EAC	Type Test Certificates/Test Report	DNV	LRS	Confirmation	Miscellaneous

Environment

Environmental Confirmations

Further information

Siemens has decided to exit the Russian market (see here).
https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business
Siemens is working on the renewal of the current EAC certificates.
Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).
Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information- and Downloadcenter (Catalogs, Brochures,…)
http://www.siemens.com/lowvoltage/catalogs
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3KD3440-2NE10-0
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3KD3440-2NE10-0
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3KD3440-2NE10-0
CAx-Online-Generator
http://www.siemens.com/cax
Tender specifications
http://www.siemens.com/specifications

Subject to change without notice
© Copyright Siemens







Subject to change without notice
© Copyright Siemens

-CR



last modified: 9/23/2021

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens