



Contactor relay, 2 NO + 2 NC, 12 V DC, Size S00, screw terminal

|                                                                                       |                        |
|---------------------------------------------------------------------------------------|------------------------|
| product brand name                                                                    | SIRIUS                 |
| product designation                                                                   | Auxiliary contactor    |
| product type designation                                                              | 3RH2                   |
| <b>General technical data</b>                                                         |                        |
| size of contactor                                                                     | S00                    |
| product extension auxiliary switch                                                    | Yes                    |
| insulation voltage with degree of pollution 3 at AC rated value                       | 690 V                  |
| degree of pollution                                                                   | 3                      |
| surge voltage resistance rated value                                                  | 6 kV                   |
| shock resistance at rectangular impulse                                               |                        |
| • at DC                                                                               | 10g / 5 ms, 5g / 10 ms |
| shock resistance with sine pulse                                                      |                        |
| • at DC                                                                               | 15g / 5 ms, 8g / 10 ms |
| mechanical service life (switching cycles)                                            |                        |
| • of contactor typical                                                                | 30 000 000             |
| • of the contactor with added electronically optimized auxiliary switch block typical | 5 000 000              |
| • of the contactor with added auxiliary switch block typical                          | 10 000 000             |
| reference code acc. to IEC 81346-2                                                    | K                      |
| Substance Prohibition (Date)                                                          | 01.10.2009 00:00:00    |
| <b>Ambient conditions</b>                                                             |                        |
| installation altitude at height above sea level maximum                               | 2 000 m                |
| • ambient temperature during operation                                                | -25 ... +60 °C         |
| • ambient temperature during storage                                                  | -55 ... +80 °C         |
| <b>Main circuit</b>                                                                   |                        |
| no-load switching frequency                                                           |                        |
| • at AC                                                                               | 10 000 1/h             |
| • at DC                                                                               | 10 000 1/h             |
| <b>Control circuit/ Control</b>                                                       |                        |
| type of voltage of the control supply voltage                                         | DC                     |
| control supply voltage at DC                                                          |                        |
| • rated value                                                                         | 12 V                   |
| operating range factor control supply voltage rated value of magnet coil at DC        |                        |
| • initial value                                                                       | 0.8                    |
| • full-scale value                                                                    | 1.1                    |

|                                                                                                                                                                                                                              |                                                   |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------|
| <b>closing power of magnet coil at DC</b>                                                                                                                                                                                    | 4 W                                               |
| <b>holding power of magnet coil at DC</b>                                                                                                                                                                                    | 4 W                                               |
| <b>closing delay</b><br>• at DC                                                                                                                                                                                              | 30 ... 100 ms                                     |
| <b>opening delay</b><br>• at DC                                                                                                                                                                                              | 7 ... 13 ms                                       |
| <b>arcing time</b>                                                                                                                                                                                                           | 10 ... 15 ms                                      |
| <b>Auxiliary circuit</b>                                                                                                                                                                                                     |                                                   |
| <b>number of NC contacts for auxiliary contacts</b><br>• instantaneous contact                                                                                                                                               | 2<br>2                                            |
| <b>number of NO contacts for auxiliary contacts</b><br>• instantaneous contact                                                                                                                                               | 2<br>2                                            |
| <b>identification number and letter for switching elements</b>                                                                                                                                                               | 22 E                                              |
| operational current at AC-12 maximum                                                                                                                                                                                         | 10 A                                              |
| <b>operational current at AC-15</b><br>• at 230 V rated value<br>• at 400 V rated value<br>• at 500 V rated value<br>• at 690 V rated value                                                                                  | 10 A<br>3 A<br>2 A<br>1 A                         |
| <b>operational current at 1 current path at DC-12</b><br>• at 24 V rated value<br>• at 110 V rated value<br>• at 220 V rated value<br>• at 440 V rated value<br>• at 600 V rated value                                       | 10 A<br>3 A<br>1 A<br>0.3 A<br>0.15 A             |
| <b>operational current with 2 current paths in series at DC-12</b><br>• at 24 V rated value<br>• at 60 V rated value<br>• at 110 V rated value<br>• at 220 V rated value<br>• at 440 V rated value<br>• at 600 V rated value | 10 A<br>10 A<br>4 A<br>2 A<br>1.3 A<br>0.65 A     |
| <b>operational current with 3 current paths in series at DC-12</b><br>• at 24 V rated value<br>• at 60 V rated value<br>• at 110 V rated value<br>• at 220 V rated value<br>• at 440 V rated value<br>• at 600 V rated value | 10 A<br>10 A<br>10 A<br>3.6 A<br>2.5 A<br>1.8 A   |
| <b>operating frequency at DC-12 maximum</b>                                                                                                                                                                                  | 1 000 1/h                                         |
| <b>operational current at 1 current path at DC-13</b><br>• at 24 V rated value<br>• at 110 V rated value<br>• at 220 V rated value<br>• at 440 V rated value<br>• at 600 V rated value                                       | 10 A<br>1 A<br>0.3 A<br>0.14 A<br>0.1 A           |
| <b>operational current with 2 current paths in series at DC-13</b><br>• at 24 V rated value<br>• at 60 V rated value<br>• at 110 V rated value<br>• at 220 V rated value<br>• at 440 V rated value<br>• at 600 V rated value | 10 A<br>3.5 A<br>1.3 A<br>0.9 A<br>0.2 A<br>0.1 A |
| <b>operational current with 3 current paths in series at DC-13</b>                                                                                                                                                           |                                                   |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                                                                                                               |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>• at 24 V rated value</li> <li>• at 60 V rated value</li> <li>• at 110 V rated value</li> <li>• at 220 V rated value</li> <li>• at 440 V rated value</li> <li>• at 600 V rated value</li> </ul>                                                                                                                                                                                                                                                                                        | 10 A<br>4.7 A<br>3 A<br>1.2 A<br>0.5 A<br>0.26 A                                                                                              |
| <b>operating frequency at DC-13 maximum</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 1 000 1/h                                                                                                                                     |
| design of the miniature circuit breaker for short-circuit protection of the auxiliary circuit up to 230 V                                                                                                                                                                                                                                                                                                                                                                                                                     | C characteristic: 6 A; 0.4 kA                                                                                                                 |
| <b>contact reliability of auxiliary contacts</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 1 faulty switching per 100 million (17 V, 1 mA)                                                                                               |
| <b>UL/CSA ratings</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                                                                               |
| <b>contact rating of auxiliary contacts according to UL</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | A600 / Q600                                                                                                                                   |
| <b>Short-circuit protection</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                                                                                                               |
| design of the fuse link for short-circuit protection of the auxiliary switch required                                                                                                                                                                                                                                                                                                                                                                                                                                         | fuse gL/gG: 10 A                                                                                                                              |
| <b>Installation/ mounting/ dimensions</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                               |
| <b>mounting position</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | +/-180° rotation possible on vertical mounting surface; can be tilted forward and backward by +/- 22.5° on vertical mounting surface          |
| <b>fastening method</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | screw and snap-on mounting onto 35 mm standard mounting rail                                                                                  |
| <b>height</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 57.5 mm                                                                                                                                       |
| <b>width</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 45 mm                                                                                                                                         |
| <b>depth</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 73 mm                                                                                                                                         |
| <b>required spacing</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                                                                               |
| <ul style="list-style-type: none"> <li>• with side-by-side mounting <ul style="list-style-type: none"> <li>— forwards</li> <li>— upwards</li> <li>— downwards</li> <li>— at the side</li> </ul> </li> <li>• for grounded parts <ul style="list-style-type: none"> <li>— forwards</li> <li>— upwards</li> <li>— at the side</li> <li>— downwards</li> </ul> </li> <li>• for live parts <ul style="list-style-type: none"> <li>— forwards</li> <li>— upwards</li> <li>— downwards</li> <li>— at the side</li> </ul> </li> </ul> | 10 mm<br>10 mm<br>10 mm<br>0 mm<br><br>10 mm<br>10 mm<br>6 mm<br>10 mm<br><br>10 mm<br>10 mm<br>10 mm<br>6 mm                                 |
| <b>Connections/ Terminals</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                                                                                               |
| type of electrical connection for auxiliary and control circuit                                                                                                                                                                                                                                                                                                                                                                                                                                                               | screw-type terminals                                                                                                                          |
| <b>type of connectable conductor cross-sections</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                                                                                                                                               |
| <ul style="list-style-type: none"> <li>• for auxiliary contacts <ul style="list-style-type: none"> <li>— solid or stranded</li> <li>— finely stranded with core end processing</li> </ul> </li> <li>• at AWG cables for auxiliary contacts</li> </ul>                                                                                                                                                                                                                                                                         | 2x (0,5 ... 1,5 mm²), 2x (0,75 ... 2,5 mm²), 2x 4 mm²<br>2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²)<br>2x (20 ... 16), 2x (18 ... 14), 2x 12 |
| <b>Safety related data</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                               |
| B10 value with high demand rate acc. to SN 31920                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 1 000 000; With 0.3 x I <sub>e</sub>                                                                                                          |
| <b>proportion of dangerous failures</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                                                                               |
| <ul style="list-style-type: none"> <li>• with low demand rate acc. to SN 31920</li> <li>• with high demand rate acc. to SN 31920</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                   | 40 %<br>73 %                                                                                                                                  |
| failure rate [FIT] with low demand rate acc. to SN 31920                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 100 FIT                                                                                                                                       |
| product function positively driven operation acc. to IEC 60947-5-1                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Yes                                                                                                                                           |
| <b>T1 value for proof test interval or service life acc. to IEC 61508</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 20 y                                                                                                                                          |
| <b>protection class IP on the front acc. to IEC 60529</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | IP20                                                                                                                                          |
| <b>touch protection on the front acc. to IEC 60529</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | finger-safe, for vertical contact from the front                                                                                              |
| <b>Certificates/ approvals</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                                                                                                                               |

## General Product Approval

EMC


[KC](#)


## Declaration of Conformity

## Test Certificates

## Marine / Shipping



EG-Konf.

[Miscellaneous](#)
[Type Test  
Certificates/Test  
Report](#)
[Special Test  
Certificate](#)


ABS

BUREAU  
VERITAS

## Marine / Shipping

## other



LRS



PRS



RINA



RMRS

DNV-GL  
DNV GL CERTIFIED
[Confirmation](#)

## other



VDE

## Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RH2122-1BA40>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RH2122-1BA40>

Service&amp;Support (Manuals, Certificates, Characteristics, FAQs,...)




<https://support.industry.siemens.com/cs/ww/en/ps/3RH2122-1BA40>


Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)


[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RH2122-1BA40&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RH2122-1BA40&lang=en)
Characteristic: Tripping characteristics, I<sub>t</sub>, Let-through current
<https://support.industry.siemens.com/cs/ww/en/ps/3RH2122-1BA40/char>

Further characteristics (e.g. electrical endurance, switching frequency)

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RH2122-1BA40&objecttype=14&gridview=view1>







last modified:

12/15/2020 