

Thermomagnetic device circuit breaker - TMC 73D 63A



1020105

<https://www.phoenixcontact.com/us/products/1020105>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Thermomagnetic device circuit breaker, number of positions: 3, connection method: Screw, cross section: 1 mm² - 35 mm², AWG: 18 - 2, mounting type: DIN rail: 35 mm, Color: gray

Commercial Data

Item number	1020105
Packing unit	1 pc
Note	Made to Order (non-returnable)
Sales Key	C30
Product Key	CLA126
GTIN	4055626509846
Weight per Piece (including packing)	222.222 g
Weight per Piece (excluding packing)	222.222 g
Customs tariff number	85362010
Country of origin	CN

Technical Data

Product properties

Type	DIN rail module, one-piece
Product type	Thermomagnetic device circuit breakers
Number of positions	3
Mechanical service life	20000

Electrical properties

Service life electrical	6000
-------------------------	------


General

Operating voltage	277 V AC (277/480Y, 240D)
Rated current I_N	63 A
Tripping method	TM (thermomagnetic)
Rated short-circuit switching capacity I_{cn}	7.5 kA (277/480Y, 240D)
Fuse	D (curve)

Connection data

Tightening torque	... 2 Nm
Conductor cross section solid	1 mm ² ... 35 mm ²
Cross section AWG	18 ... 2 (converted acc. to IEC)
Conductor cross section flexible	1 mm ² ... 35 mm ²

Dimensions

Dimensional drawing	
Width	52.9 mm

Material specifications

Color	gray
-------	------

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-35 °C ... 70 °C
Humidity test	48 h, 95% RH, 40°C (IEC 60068-2-78)
Shock (operation)	30g (11 ms) (IEC 60068-2-11, test Ea)
Vibration (operation)	±0.38 mm (10-57 Hz), 5g (57...500 Hz) (Sinusoidal test to IEC 60068-2-6, Test Fc. 10 frequency cycles per axis)

Thermomagnetic device circuit breaker - TMC 73D 63A



1020105

<https://www.phoenixcontact.com/us/products/1020105>

Standards and regulations


Standards/specifications	UL 1077
Standards/specifications	IEC 60947-2

Mounting


Mounting type	DIN rail: 35 mm
---------------	-----------------

Drawings

Diagram



Dimensional drawing



Thermomagnetic device circuit breaker - TMC 73D 63A



1020105

<https://www.phoenixcontact.com/us/products/1020105>

Approvals



cUL Recognized

Approval ID: FILE E 140459



UL Recognized

Approval ID: FILE E 140459

cULus Recognized

Thermomagnetic device circuit breaker - TMC 73D 63A



1020105

<https://www.phoenixcontact.com/us/products/1020105>

Classifications

ECLASS

ECLASS-9.0	27141116
ECLASS-10.0.1	27141116
ECLASS-11.0	27141116

ETIM

ETIM 7.0	EC000899
----------	----------

UNSPSC

UNSPSC 21.0	39121410
-------------	----------

Thermomagnetic device circuit breaker - TMC 73D 63A



1020105

<https://www.phoenixcontact.com/us/products/1020105>

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
	Cadmium oxide 1306-19-0

Thermomagnetic device circuit breaker - TMC 73D 63A



1020105


<https://www.phoenixcontact.com/us/products/1020105>

Accessories

Wiring bridge

Wiring bridge - TMC 7 B3 80 57 C - 1022234

<https://www.phoenixcontact.com/us/products/1022234>




Bus bar for TMC 73... circuit breakers (three phase) 17.8 mm pitch, up to 57 positions. Rated for 80 A (end feed) 600 V AC/DC. UL 508 Listed for connection of UL 1077 rated circuit breakers.

Wiring bridge

Wiring bridge - TMC 7 B3 80 48 CA - 1025400

<https://www.phoenixcontact.com/us/products/1025400>



Bus bar for TMC 73... circuit breakers (two phase) with auxilliary switch. 17.8 mm pitch, up to 48 positions. Rated for 80 A (end feed) 600 V AC/DC. UL 508 Listed for connection of UL 1077 rated circuit breakers.

Thermomagnetic device circuit breaker - TMC 73D 63A



1020105

<https://www.phoenixcontact.com/us/products/1020105>

Terminal adapter

Terminal adapter - TMC 7 B2/3 TERM - 1022232

<https://www.phoenixcontact.com/us/products/1022232>



Feeder terminal adapter for TMC 72 or TMC 73 circuit breakers, two- or three-phase bus bars. Rated for 600 V AC/DC 115 A. Wire range 10...1/0 AWG. UL 508 Listed for connection to UL 1077 rated circuit breakers.

Wiring bridge end cover

Wiring bridge end cover - TMC 7 B2/3 END CAP - 1022229

<https://www.phoenixcontact.com/us/products/1022229>



Protective end covers for TMC 7 multi-pole bus bars

Thermomagnetic device circuit breaker - TMC 73D 63A



1020105

<https://www.phoenixcontact.com/us/products/1020105>

Protective cover

Protective cover - TMC 7 B BUS CAP - 1022224

<https://www.phoenixcontact.com/us/products/1022224>



Protective covers for TMC 7 single-pole bus bars. Cuttable, five positions, yellow.

Thermomagnetic device circuit breaker

Thermomagnetic device circuit breaker - TMC 7/8 AUX - 2908219

<https://www.phoenixcontact.com/us/products/2908219>



Thermomagnetic device circuit breaker, number of positions: 1, connection method: Screw, cross section: 1 mm²- 35 mm², AWG: 18 - 2, mounting type: Snaps on to side of circuit breaker, Color: gray

Thermomagnetic device circuit breaker - TMC 73D 63A



1020105

<https://www.phoenixcontact.com/us/products/1020105>

Thermomagnetic device circuit breaker

Thermomagnetic device circuit breaker - TMC 7/8 ALARM - 2908220

<https://www.phoenixcontact.com/us/products/2908220>



Thermomagnetic device circuit breaker, number of positions: 1, connection method: Screw, cross section: 1 mm² - 35 mm², AWG: 18 - 2, mounting type: Snaps on to side of circuit breaker, Color: gray

Thermomagnetic device circuit breaker

Thermomagnetic device circuit breaker - TMC 7/8 12VDC SHNT - 2908221

<https://www.phoenixcontact.com/us/products/2908221>



Thermomagnetic device circuit breaker, number of positions: 1, connection method: Screw, cross section: 1 mm² - 35 mm², AWG: 18 - 2, mounting type: Snaps on to side of circuit breaker, Color: gray

Thermomagnetic device circuit breaker - TMC 73D 63A



1020105

<https://www.phoenixcontact.com/us/products/1020105>

Thermomagnetic device circuit breaker

Thermomagnetic device circuit breaker - TMC 7/8 24VDC SHNT - 2908222

<https://www.phoenixcontact.com/us/products/2908222>



Thermomagnetic device circuit breaker, number of positions: 1, connection method: Screw, cross section: 1 mm² - 35 mm², AWG: 18 - 2, mounting type: Snaps on to side of circuit breaker, Color: gray

Thermomagnetic device circuit breaker

Thermomagnetic device circuit breaker - TMC 7/8 48VDC SHNT - 2908224

<https://www.phoenixcontact.com/us/products/2908224>



Thermomagnetic device circuit breaker, number of positions: 1, connection method: Screw, cross section: 1 mm² - 35 mm², AWG: 18 - 2, mounting type: Snaps on to side of circuit breaker, Color: gray

Thermomagnetic device circuit breaker - TMC 73D 63A



1020105

<https://www.phoenixcontact.com/us/products/1020105>

Thermomagnetic device circuit breaker

Thermomagnetic device circuit breaker - TMC 7/8 125VDC SHNT - 2908225

<https://www.phoenixcontact.com/us/products/2908225>



Thermomagnetic device circuit breaker, number of positions: 1, connection method: Screw, cross section: 1 mm² - 35 mm², AWG: 18 - 2, mounting type: Snaps on to side of circuit breaker, Color: gray

Thermomagnetic device circuit breaker

Thermomagnetic device circuit breaker - TMC 7/8 120VAC SHNT - 2908226

<https://www.phoenixcontact.com/us/products/2908226>



Thermomagnetic device circuit breaker, number of positions: 1, connection method: Screw, cross section: 1 mm² - 35 mm², AWG: 18 - 2, mounting type: Snaps on to side of circuit breaker, Color: gray

Thermomagnetic device circuit breaker - TMC 73D 63A



1020105

<https://www.phoenixcontact.com/us/products/1020105>

Thermomagnetic device circuit breaker

Thermomagnetic device circuit breaker - TMC 7/8 240VAC SHNT - 2908227

<https://www.phoenixcontact.com/us/products/2908227>



Thermomagnetic device circuit breaker, number of positions: 1, connection method: Screw, cross section: 1 mm² - 35 mm², AWG: 18 - 2, mounting type: Snaps on to side of circuit breaker, Color: gray

Thermomagnetic device circuit breaker

Thermomagnetic device circuit breaker - TMC 7/8 277VAC SHNT - 2908228

<https://www.phoenixcontact.com/us/products/2908228>



Thermomagnetic device circuit breaker, number of positions: 1, connection method: Screw, cross section: 1 mm² - 35 mm², AWG: 18 - 2, mounting type: Snaps on to side of circuit breaker, Color: gray

Thermomagnetic device circuit breaker - TMC 73D 63A



1020105

<https://www.phoenixcontact.com/us/products/1020105>

Label

Label - EML (10X4)R - 0815583

<https://www.phoenixcontact.com/us/products/0815583>



Label, Roll, white, unlabeled, can be labeled with: THERMOMARK ROLLMaster 300/600, THERMOMARK X1.2, THERMOMARK ROLL X1, THERMOMARK ROLL 2.0, THERMOMARK ROLL, mounting type: adhesive, lettering field size: 10 x 4 mm, Number of individual labels: 10000

Marking foil for zack marker strip

Marking foil for zack marker strip - TML (104X3,8)R - 0801833

<https://www.phoenixcontact.com/us/products/0801833>



Marking foil for zack marker strip, Roll, white, unlabeled, can be labeled with: THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMaster 300/600, THERMOMARK X1.2, mounting type: adhesive, for terminal block width: 104 mm, lettering field size: 104 x 3.8 mm, Number of individual labels: 2500

Phoenix Contact 2022 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA

586 Fulling Mill Road

Middletown, PA 17057, United States

(+717) 944-1300

info@phoenixcon.com