GT3-W

~40° wide beam



TECHNICAL SPECIFICATIONS:

Dimensions	Ø 35.0 mm
Height	9 mm
Fastening	glue, pin
ROHS compliant	yes

MATERIAL SPECIFICATIONS:


Component	Type	Material	Colour	Finish
GT3-W	Multi-lens	PMMA	clear	

ORDERING INFORMATION:


Component	Qty in box	MOQ	MPQ	Box weight (kg)
C10893_GT3-W » Box size: 300 x 250 x 250 mm	864	144	144	4.5

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

DATE
27.06.2018




Isometric view
Scale 1:1




Bottom view

Part no.s:
C10891_GT3-XP-S
C10891_GT3-XP-G-S
C10891_GT3-OSL-S
C10891_GT3-DD-S
C10891_GT3-RE-ES-M
C10891_GT3-Z5-S
C10892_GT3-XP-M
C10892_GT3-XP-G-M
C10892_GT3-OSL-M
C10892_GT3-DD-M
C10892_GT3-XP-M
C10892_GT3-Z5-M
C10893_GT3-XP-W
C10893_GT3-XP-G-W
C10893_GT3-OSL-W
C10893_GT3-DD-W
C10893_GT3-RE-ES-W
C11623_GT3-RE-WW
C11623_GT3-N19-WW
C11624_GT3-XP-WW
C11624_GT3-XP-G-WW
C11624_GT3-OSL-WW
C11624_GT3-DD-WW
C11624_GT3-Z5-WW



Front view



Top view

TYPE	MATERIAL	COLOR / COATING
LENS	PMMA	CLEAR


MECHANICAL DRAWING

PRODUCT GT3

LEDiL®

Plastic moulding general tolerances according to DIN 16901-130 and applies if not otherwise shown in the drawing. Silicone moulding general tolerances according to ISO 3302-1 Class M3 and applies if not otherwise shown in the drawing.

FIRST ANGLE PROJECTION:



This drawing is the property of LEDiL Oy. It may not be copied or otherwise distributed without prior written permission from LEDiL Oy.

SCALE 3:2 | WEIGHT - | A4 SHEET 1/1

See also our general installation guide: www.ledil.com/installation_guide

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (MEASURED):


CREE LED

LED	XB-D
FWHM / FWTM	32.0° / 60.0°
Efficiency	92 %
Peak intensity	1.8 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	

CREE LED

LED	XP-E
FWHM / FWTM	40.0° / 70.0°
Efficiency	89 %
Peak intensity	1.6 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	






CREE LED

LED	XP-G
FWHM / FWTM	46.0° / 78.0°
Efficiency	86 %
Peak intensity	1.3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	





LUMILEDS

LED	LUXEON A
FWHM / FWTM	44.0° / 66.0°
Efficiency	%
LEDs/each optic	1
Light colour	White
Required components:	

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (MEASURED):

LUMILEDS

LED	LUXEON Rebel
FWHM / FWTM	38.0° / 66.0°
Efficiency	85 %
LEDs/each optic	1
Light colour	White
Required components:	

LUMILEDS



LED	LUXEON Rebel ES
FWHM / FWTM	44.0° / 66.0°
Efficiency	85 %
LEDs/each optic	1
Light colour	White
Required components:	

NICHIA

LED	NCSxx19A
FWHM / FWTM	40.0°
Efficiency	86 %
LEDs/each optic	1
Light colour	White
Required components:	

NICHIA

LED	NVSxx19A
FWHM / FWTM	44.0°
Efficiency	86 %
LEDs/each optic	1
Light colour	White
Required components:	

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (MEASURED):

OSRAM
Opto Semiconductors

LED	OSLON Square EC
FWHM / FWTM	36.0° / 63.0°
Efficiency	89 %
Peak intensity	1.8 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	

OSRAM
Opto Semiconductors

LED	OSLON SSL 150
FWHM / FWTM	40.0°
Efficiency	88 %
LEDs/each optic	1
Light colour	White
Required components:	

OSRAM
Opto Semiconductors

LED	OSLON SSL 80
FWHM / FWTM	36.0°
Efficiency	89 %
LEDs/each optic	1
Light colour	White
Required components:	



SEOUL SEMICONDUCTOR

LED	Z5
FWHM / FWTM	40.0°
Efficiency	%
LEDs/each optic	1
Light colour	White
Required components:	




LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (SIMULATED):

NICHIA

LED	NCSxE17A
FWHM / FWTM	28.0° / 52.0°
Efficiency	96 %
Peak intensity	3.2 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy
Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.
228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.
405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support
www.ledil.com/
where_to_buy

Shipping locations
Salo, Finland
Hong Kong, China

Distribution Partners
www.ledil.com/
where_to_buy

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.