This document was generated on 10/25/2022

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 1202530606

Status: Active

Overview: Contrinex Inductive and Photoelectric Sensors

Description: Contrinex Inductive Sensor, 4mm Diameter Smooth Fully Stainless Steel, 3mm Operating Distance, Non-embeddable, NPN, NC, 0.2m 3-wire PUR Cable, 3-pin M8 Connector, 30mm Housing Length



Series image - Reference only

Documents:

Product Specification 1202530601-000 (PDF)
RoHS Certificate of Compliance (PDF)
Datasheet (PDF)

EU ELV
Not Relevant

EU RoHS | **China RoHS**
Compliant

REACH SVHC
Not Reviewed

Halogen-Free Status
Not Reviewed

For more information, please visit Contact US

China ROHS	Green Image
ELV	Not Relevant
RoHS Phthalates	Not Contained

Search Parts in this Series
120253 Series

General	
Product Family	Sensors
Series	120253
IP Rating	IP68, IP69K
Overview	Contrinex Inductive and Photoelectric Sensors
Product Category	Inductive Sensors
Product Name	Contrinex
Taxonomy	Inductive and Photoeletric Sen
Type	Inductive
UPC	191130064342
Physical	
Connection	Cable (PUR 0.2m, 3-wire), Connector (M8, 3-pin)
Length	30mm
Material - Housing	Stainless Steel
Material - Sensing Face	Stainless Steel
Mounting Style	Non-embeddable
Operating Distance	3mm
Output	NC
Sensor Housing Size	4mm dia. (smooth)
Temperature Range - Operating	-25° to +85°C
Electrical	
Polarity	NPN
Switching Frequency	$\leq$ 1200 Hz
Material Info	
Engineering Number	DW-AV-712-04-276
Reference - Drawing Numbers	
Product Specification	1202530601-000

This document was generated on 10/25/2022

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION