This document was generated on 10/25/2022

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 1202530664

Status: Active

Overview: Contrinex Inductive and Photoelectric Sensors

Description: Contrinex Inductive Sensor, M30 Fully Stainless Steel, 20mm Operating Distance, Embeddable, PNP, NC, 4-pin M12 Connector, 63.5mm Housing Length

Documents:

Product Specification 1202530657-000 (PDF)

RoHS Certificate of Compliance (PDF)

Datasheet (PDF)



Series image - Reference only

EU ELV
Not Relevant

EU RoHS | **China RoHS**
Compliant

REACH SVHC
Not Reviewed

Halogen-Free Status
Not Reviewed

For more information, please visit Contact US

China ROHS	Green Image
ELV	Not Relevant
RoHS Phthalates	Not Contained

Search Parts in this Series
120253 Series

General	
Product Family	Sensors
Series	120253
IP Rating	IP68, IP69K
Overview	Contrinex Inductive and Photoelectric Sensors
Product Category	Inductive Sensors
Product Name	Contrinex
Taxonomy	Inductive and Photoeletric Sen
Type	Inductive
UPC	191130065943
Physical	
Connection	Connector (M12, 4-pin)
Length	63.5mm
Material - Housing	Stainless Steel
Material - Sensing Face	Stainless Steel
Mounting Style	Embeddable
Operating Distance	20mm
Output	NC
Sensor Housing Size	M30
Temperature Range - Operating	-25° to +85°C
Electrical	
Polarity	PNP
Switching Frequency	≤ 125 Hz
Material Info	
Engineering Number	DW-LS-704-M30-002
Reference - Drawing Numbers	
Product Specification	1202530657-000

This document was generated on 10/25/2022

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION