LOS-RS

~9.6° spot beam optimized for Osram Oslon Square EC. 14.3 mm high assembly.



TECHNICAL SPECIFICATIONS:

Dimensions	Ø 21.6 mm
Height	14.3 mm
Fastening	glue, pin
ROHS compliant	yes


MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
LXP2-RS	Single lens	PMMA	clear	
LEILA-HLD-OSL	Holder	PC	white	

ORDERING INFORMATION:

Component		Qty in box	MOQ	MPQ	Box weight (kg)
CP12412_LOS-RS » Box size: 480 x 280 x 300 mm	Single lens	1680	336	112	9.1

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.



Tolerances if not otherwise shown According to DIN ISO 2768-1 Linear measures: Up to 30mm class M, otherwise class C. According to DIN ISO 2768-2 Form and position: class L	Ledil Oy Salorankatu 10 FIN 24240 SALO Finland
THIRD ANGLE PROJECTION:	DRAWING TITLE CP12412_LOS-RS
This drawing is the property of LEDiL Oy. It may not be reproduced, copied or communicated without a written agreement with LEDiL Oy."	SIZE A4 / PART NUMBER CP12412
	SCALE 2:1 / WEIGHT - / SHEET 1/1

See also our general installation guide: www.ledil.com/installation_guide


LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (MEASURED):

OSRAM
Opto Semiconductors

LED	OSLON Square EC
FWHM / FWTM	10.0° / 20.0°
Efficiency	94 %
Peak intensity	20.9 cd/lm
LEDs/each optic	1
Light colour	White


Required components:




OSRAM
Opto Semiconductors

LED	OSLON SSL 150
FWHM / FWTM	6.0° / 15.0°
Efficiency	93 %
Peak intensity	40 cd/lm
LEDs/each optic	1
Light colour	White

Required components:






OSRAM
Opto Semiconductors

LED	OSLON SSL 80
FWHM / FWTM	7.0° / 14.0°
Efficiency	93 %
Peak intensity	29.8 cd/lm
LEDs/each optic	1
Light colour	White

Required components:




LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (SIMULATED):

CREE LED


LED	XT-E
FWHM / FWTM	9.9° / 22.0°
Efficiency	94 %
Peak intensity	19.5 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	






LUMILEDS

LED	LUXEON C
FWHM / FWTM	8.0° / 20.0°
Efficiency	94 %
Peak intensity	22.9 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




LUMILEDS

LED	LUXEON CZ
FWHM / FWTM	8.0° / 16.0°
Efficiency	95 %
Peak intensity	35 cd/lm
LEDs/each optic	1
Light colour	Red
Required components:	



OSRAM
Opto Semiconductors

LED	OSLON Square CSSRM2/CSSRM3
FWHM / FWTM	9.8° / 20.0°
Efficiency	94 %
Peak intensity	21.9 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (SIMULATED):


SAMSUNG

LED	LH351B
FWHM / FWTM	12.0° / 25.0°
Efficiency	94 %
Peak intensity	15 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



SEOUL SEMICONDUCTOR

LED	Z5M1/Z5M2
FWHM / FWTM	11.0° / 21.0°
Efficiency	94 %
Peak intensity	20.4 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy
Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.
228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.
405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support
www.ledil.com/
where_to_buy

Shipping locations
Salo, Finland
Hong Kong, China

Distribution Partners
www.ledil.com/
where_to_buy

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.