LARISA-RS-CLIP16

~19° real spot beam. Clip fastening for 1.6 mm thick PCB



TECHNICAL SPECIFICATIONS:

Dimensions	9.9 x 9.9 mm
Height	7.5 mm
Fastening	clips
ROHS compliant	yes

MATERIAL SPECIFICATIONS:


Component	Type	Material	Colour	Finish
LARISA-RS	Single lens	PMMA	clear	
LARISA-HOLDER-CLIP16	Holder	PC	black	

ORDERING INFORMATION:


Component		Qty in box	MOQ	MPQ	Box weight (kg)
CP12939_LARISA-RS-CLIP16 » Box size: 300 x 250 x 250 mm	Single lens	10000	300	100	5.8

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


Designed for the following pin hole dimensions: Hole diameter 1.95mm
Hole distance 8.6mm
PCB thickness 1.6mm




Front view



Isometric view
Scale: 4:1



Top view



Oval beam direction

Bottom view

INDEX	PART NO	DESCRIPTION	MATERIAL	COLOUR
1	-	LARISA lens	PMMA	
2	C12908	LARISA-HOLDER-CLIP16	PC	black

Tolerances if not otherwise shown
According to DIN ISO 2768-1
Linear measures:
Up to 30mm class M, otherwise class C.
According to DIN ISO 2768-2
Form and position: class L

Ledil Oy
Salorankatu 10
FIN 24240 SALO
Finland

THIRD ANGLE PROJECTION:

DRAWING TITLE
LARISA-CLIP16 series

This drawing is the property of LEDiL Oy. It may not be reproduced, copied or communicated without a written agreement with LEDiL Oy.

SIZE A4 | PART NUMBER -

SCALE 4:1 | WEIGHT 0,6 g | SHEET 1/1

See also our general installation guide: www.ledil.com/installation_guide


PHOTOMETRIC DATA (MEASURED):

CREE LED

LED	XD16
FWHM / FWTM	18.0° / 40.0°
Efficiency	80 %
Peak intensity	4.8 cd/lm
LEDs/each optic	1
Light colour	White

Required components:






CREE LED

LED	XQ-E HD
FWHM / FWTM	16.0° / 33.0°
Efficiency	86 %
Peak intensity	6.9 cd/lm
LEDs/each optic	1
Light colour	White

Required components:






CREE LED

LED	XQ-E HI
FWHM / FWTM	11.0° / 28.0°
Efficiency	80 %
Peak intensity	10.7 cd/lm
LEDs/each optic	1
Light colour	White

Required components:






LUMILEDS

LED	LUXEON A
FWHM / FWTM	26.0° / 51.0°
Efficiency	89 %
Peak intensity	3.2 cd/lm
LEDs/each optic	1
Light colour	White

Required components:







LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (MEASURED):

LUMILEDS

LED	LUXEON C
FWHM / FWTM	17.0° / 36.0°
Efficiency	86 %
Peak intensity	6.1 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	





LUMILEDS


LED	LUXEON Rebel
FWHM / FWTM	20.0° / 45.0°
Efficiency	90 %
Peak intensity	4.6 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



LUMILEDS

LED	LUXEON Rebel ES
FWHM / FWTM	24.0° / 53.0°
Efficiency	88 %
Peak intensity	3.2 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	






LUMILEDS

LED	LUXEON Z
FWHM / FWTM	11.0° / 27.0°
Efficiency	85 %
Peak intensity	12.1 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	






LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (MEASURED):

LUMILEDS

LED	LUXEON Z ES
FWHM / FWTM	16.0° / 37.0°
Efficiency	89 %
Peak intensity	6.1 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	






NICHIA

LED	NCSxx19A
FWHM / FWTM	16.0° / 43.0°
Efficiency	84 %
Peak intensity	4.8 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	






NICHIA

LED	NVSxx19A
FWHM / FWTM	21.0° / 52.0°
Efficiency	81 %
Peak intensity	3.1 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	






OSRAM
Opto Semiconductors

LED	OSLON Square EC
FWHM / FWTM	22.0° / 47.0°
Efficiency	86 %
Peak intensity	3.8 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	





LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (MEASURED):

OSRAM
Opto Semiconductors

LED	OSLON SSL 150
FWHM / FWTM	16.0° / 39.0°
Efficiency	87 %
Peak intensity	8.1 cd/lm
LEDs/each optic	1
Light colour	White


Required components:




OSRAM
Opto Semiconductors

LED	OSLON SSL 80
FWHM / FWTM	16.0° / 36.0°
Efficiency	83 %
Peak intensity	6.5 cd/lm
LEDs/each optic	1
Light colour	White


Required components:





PHOTOMETRIC DATA (SIMULATED):

LED	XP-E
FWHM / FWTM	15.0°
Efficiency	92 %
LEDs/each optic	1
Light colour	White
Required components:	



LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy
Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.
228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.
405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support
www.ledil.com/
where_to_buy

Shipping locations
Salo, Finland
Hong Kong, China

Distribution Partners
www.ledil.com/
where_to_buy

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.