VERONICA-O

~55° + 10° oval beam



TECHNICAL SPECIFICATIONS:

Dimensions	Ø 26.0 mm
Height	12.2 mm
Fastening	glue, pin
ROHS compliant	yes


MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
VERONICA-O	Single lens	PMMA	clear	


ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
C13529_VERONICA-O » Box size: 480 x 280 x 300 mm	2240	336	112	11.1


LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.




Isometric view




Bottom view






Front view



PCB suggestion



Top view

INDEX	PART NO	DESCRIPTION	MATERIAL	COLOUR
1	-	VERONICA	PMMA	

Tolerances if not otherwise shown
According to DIN ISO 2768-1
Linear measures:
Up to 30mm class M, otherwise class C.
According to DIN ISO 2768-2
Form and position: class L

Ledil Oy
Salorankatu 10
FIN 24240 SALO
Finland

THIRD ANGLE PROJECTION:

DRAWING TITLE
VERONICA SERIES

This drawing is the property of LEDiL Oy. It may not be reproduced, copied or communicated without a written agreement with LEDiL Oy."

SIZE A4

PART NUMBER -

SCALE 1:1 WEIGHT SHEET 1/1

See also our general installation guide: www.ledil.com/installation_guide


PHOTOMETRIC DATA (MEASURED):

CREE LED

LED	MK-R
FWHM / FWTM	48.0 + 28.0° / 85.0 + 58.0°
Efficiency	80 %
Peak intensity	1.6 cd/lm
LEDs/each optic	1
Light colour	White

Required components:






CREE LED

LED	XHP35 HD
FWHM / FWTM	52.0 + 19.0° / 84.0 + 44.0°
Efficiency	80 %
Peak intensity	2.3 cd/lm
LEDs/each optic	1
Light colour	White

Required components:





CREE LED

LED	XHP35 HI
FWHM / FWTM	53.0 + 16.0° / 82.0 + 38.0°
Efficiency	82 %
Peak intensity	2.9 cd/lm
LEDs/each optic	1
Light colour	White


Required components:




CREE LED

LED	XM-L
FWHM / FWTM	54.0 + 18.0° / 81.0 + 40.0°
Efficiency	83 %
Peak intensity	2.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:





LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):

CREE LED

LED	XM-L2
FWHM / FWTM	54.0 + 18.0° / 81.0 + 41.0°
Efficiency	82 %
Peak intensity	2.4 cd/lm
LEDs/each optic	1
Light colour	White

Required components:






CREE LED

LED	XP-E
FWHM / FWTM	54.0 + 11.0° / 76.0 + 26.0°
Efficiency	83 %
Peak intensity	4.2 cd/lm
LEDs/each optic	1
Light colour	White

Required components:






CREE LED

LED	XP-E2
FWHM / FWTM	54.0 + 11.0° / 76.0 + 27.0°
Efficiency	84 %
Peak intensity	4.2 cd/lm
LEDs/each optic	1
Light colour	White

Required components:






CREE LED

LED	XP-G
FWHM / FWTM	55.0 + 13.0° / 79.0 + 30.0°
Efficiency	83 %
Peak intensity	3.3 cd/lm
LEDs/each optic	1
Light colour	White

Required components:






LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (MEASURED):

CREE LED

LED	XP-G2
FWHM / FWTM	55.0 + 13.0° / 78.0 + 30.0°
Efficiency	84 %
Peak intensity	3.2 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	






CREE LED

LED	XT-E
FWHM / FWTM	54.0 + 15.0° / 79.0 + 33.0°
Efficiency	81 %
Peak intensity	2.9 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	






LUMILEDS

LED	LUXEON A
FWHM / FWTM	54.0 + 15.0° / 79.0 + 33.0°
Efficiency	82 %
Peak intensity	2.9 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	






LUMILEDS

LED	LUXEON M/MX
FWHM / FWTM	49.0 + 28.0° / 84.0 + 57.0°
Efficiency	79 %
Peak intensity	1.6 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	






LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (MEASURED):

LUMILEDS

LED	LUXEON R
FWHM / FWTM	54.0 + 16.0° / 79.0 + 34.0°
Efficiency	81 %
Peak intensity	2.8 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	






LUMILEDS

LED	LUXEON Rebel
FWHM / FWTM	54.0 + 14.0° / 78.0 + 31.0°
Efficiency	82 %
Peak intensity	3.2 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	






LUMILEDS

LED	LUXEON Rebel ES
FWHM / FWTM	54.0 + 17.0° / 80.0 + 34.0°
Efficiency	81 %
Peak intensity	2.7 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	






LUMILEDS

LED	LUXEON V2
FWHM / FWTM	52.0 + 16.0° / 78.0 + 36.0°
Efficiency	90 %
Peak intensity	2.7 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	






LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (MEASURED):

NICHIA


LED	NCSxx19B
FWHM / FWTM	52.0 + 15.0° / 80.0 + 32.0°
Efficiency	80 %
Peak intensity	3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



NICHIA

LED	NVSW219F
FWHM / FWTM	53.0 + 15.0° / 79.0 + 36.0°
Efficiency	91 %
Peak intensity	2.8 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	






NICHIA


LED	NVSW3x9A
FWHM / FWTM	53.0 + 16.0° / 80.0 + 35.0°
Efficiency	80 %
Peak intensity	2.5 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	






NICHIA

LED	NVSxx19A
FWHM / FWTM	53.0 + 18.0° / 80.0 + 36.0°
Efficiency	79 %
Peak intensity	2.5 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	






LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (MEASURED):

NICHIA

LED	NVSxx19B/NVSxx19C
FWHM / FWTM	54.0 + 17.0° / 79.0 + 35.0°
Efficiency	79 %
Peak intensity	2.7 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	






OSRAM
Opto Semiconductors

LED	OSLON Square EC
FWHM / FWTM	54.0 + 14.0° / 79.0 + 32.0°
Efficiency	81 %
Peak intensity	3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	






OSRAM
Opto Semiconductors

LED	OSLON Square PC
FWHM / FWTM	54.0 + 15.0° / 79.0 + 32.0°
Efficiency	81 %
Peak intensity	3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	






OSRAM
Opto Semiconductors

LED	OSLON SSL 150
FWHM / FWTM	54.0 + 11.0° / 76.0 + 24.0°
Efficiency	83 %
Peak intensity	4.2 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	






LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (MEASURED):

SAMSUNG

LED	LH351B
FWHM / FWTM	54.0 + 14.0° / 79.0 + 33.0°
Efficiency	84 %
Peak intensity	2.8 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	






SAMSUNG

LED	LH351Z
FWHM / FWTM	54.0 + 13.0° / 78.0 + 31.0°
Efficiency	83 %
Peak intensity	3.3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	






SEOUL SEMICONDUCTOR

LED	Z5
FWHM / FWTM	54.0 + 13.0° / 77.0 + 28.0°
Efficiency	83 %
Peak intensity	3.6 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	






SEOUL SEMICONDUCTOR

LED	Z5M1/Z5M2
FWHM / FWTM	54.0 + 15.0° / 79.0 + 33.0°
Efficiency	83 %
Peak intensity	3.1 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	





LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):

SEOUL SEMICONDUCTOR

LED	Z8Y22P
FWHM / FWTM	52.0 + 17.0° / 79.0 + 37.0°
Efficiency	77 %
Peak intensity	2.3 cd/lm
LEDs/each optic	1
Light colour	White

Required components:






SEOUL SEMICONDUCTOR

LED	Z8Y50P
FWHM / FWTM	48.0 + 29.0° / 84.0 + 58.0°
Efficiency	73 %
Peak intensity	1.4 cd/lm
LEDs/each optic	1
Light colour	White

Required components:






LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (SIMULATED):


CREE LED

LED	XP-G2 HE
FWHM / FWTM	54.0 + 14.0° / 80.0 + 32.0°
Efficiency	90 %
Peak intensity	2.9 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




NICHIA

LED	NV4WB35AM
FWHM / FWTM	52.0 + 18.0° / 82.0 + 38.0°
Efficiency	91 %
Peak intensity	2.5 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




NICHIA


LED	NVSW519A
FWHM / FWTM	54.0 + 16.0° / 82.0 + 37.0°
Efficiency	91 %
Peak intensity	2.6 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



OSRAM
Opto Semiconductors

LED	OSCONIQ P 7070
FWHM / FWTM	48.0 + 25.0° / 85.0 + 50.0°
Efficiency	85 %
Peak intensity	1.9 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	






PHOTOMETRIC DATA (SIMULATED):


OSRAM
Opto Semiconductors

LED	OSLON Square CSSRM2/CSSRM3
FWHM / FWTM	57.0 + 11.0° / 80.0 + 26.0°
Efficiency	92 %
Peak intensity	3.4 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




SEOUL SEMICONDUCTOR

LED	MJT 3030
FWHM / FWTM	56.0 + 12.0° / 78.0 + 28.0°
Efficiency	90 %
Peak intensity	3.2 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




SEOUL SEMICONDUCTOR

LED	MJT 5050
FWHM / FWTM	50.0 + 30.0° / 87.0 + 68.0°
Efficiency	78 %
Peak intensity	1.4 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



SEOUL SEMICONDUCTOR

LED	Z5M4
FWHM / FWTM	54.0 + 14.0° / 80.0 + 32.0°
Efficiency	90 %
Peak intensity	2.8 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy
Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.
228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.
405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support
www.ledil.com/
where_to_buy

Shipping locations
Salo, Finland
Hong Kong, China

Distribution Partners
www.ledil.com/
where_to_buy

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.