EVA-W

~40° wide beam. Assembly with holder including location pins and installation tape.



TECHNICAL SPECIFICATIONS:

Dimensions	Ø 37.7 mm
Height	17.2 mm
Fastening	tape, pin
ROHS compliant	yes


MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
EVA-W	Single lens	PMMA	clear	
EVA-HLD-PIN	Holder	PC	black	
SPUTNIK-TAPE3	Tape	Acrylic foam	black	

ORDERING INFORMATION:

Component		Qty in box	MOQ	MPQ	Box weight (kg)
CA14309_EVA-W » Box size: 480 x 280 x 300 mm	Single lens	675	90	45	9.7

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.



PART	TYPE	MATERIAL	COLOR / COATING
C10686	EVA-W	PMMA	CLEAR
C14307	EVA-HLD-PIN	PC	BLACK
C15177	SPUTNIK-TAPE3		

See also our general installation guide: www.ledil.com/installation_guide

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):

LUMILEDS

LED	LUXEON M/MX
FWHM / FWTM	45.0° / 73.0°
Efficiency	80 %
Peak intensity	1.3 cd/lm
LEDs/each optic	1
Light colour	White

Required components:






NICHIA

LED	NVSW219F
FWHM / FWTM	35.0° / 66.0°
Efficiency	82 %
Peak intensity	1.9 cd/lm
LEDs/each optic	1
Light colour	White

Required components:






PHOTOMETRIC DATA (SIMULATED):


CREE LED

LED	XHP35.2 HD
FWHM / FWTM	44.0° / 74.0°
Efficiency	78 %
Peak intensity	1.3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




CREE LED

LED	XP-E2
FWHM / FWTM	33.0° / 66.0°
Efficiency	85 %
Peak intensity	2.1 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




NICHIA

LED	NVSxE21A
FWHM / FWTM	37.0° / 69.0°
Efficiency	83 %
Peak intensity	1.8 cd/lm
LEDs/each optic	4
Light colour	White
Required components:	



SEOUL SEMICONDUCTOR

LED	Z8Y22P
FWHM / FWTM	34.0° / 69.0°
Efficiency	95 %
Peak intensity	2 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (SIMULATED):

SEOUL SEMICONDUCTOR

LED	Z8Y50P
FWHM / FWTM	39.0° / 71.0°
Efficiency	82 %
Peak intensity	1.6 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy
Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.
228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.
405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support
www.ledil.com/
where_to_buy

Shipping locations
Salo, Finland
Hong Kong, China

Distribution Partners
www.ledil.com/
where_to_buy

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.