LISA3CSP-W-PIN

~35° wide beam



TECHNICAL SPECIFICATIONS:

Dimensions	Ø 10.0 mm
Height	7.2 mm
Fastening	pin
ROHS compliant	yes


MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
LISA3-W	Single lens	PMMA	clear	
LISA3-HLD2-PIN	Holder	PC	black	

ORDERING INFORMATION:

Component		Qty in box	MOQ	MPQ	Box weight (kg)
FP16609_LISA3CSP-W-PIN » Box size: 310 x 230 x 60 mm	Single lens	2000	300	100	1.3

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.



CP16609_LISA3CSP-W-PIN Datasheet

COMPONENTS

INDEX	PART	REV	TYPE	MATERIAL	COLOR / COATING
1	F16564_LISA3-HLD2-PIN Mechanical model	001		PC	Black
2	F16553_LISA3-W Mechanical model	001		PMMA	Clear

MECHANICAL DRAWING

PRODUCT LISA3

LEDiL®

Plastic moulding general tolerances according to DIN 16901-130 and applies if not otherwise shown in the drawing. Silicone moulding general tolerances according to ISO 3302-1 Class M3 and applies if not otherwise shown in the drawing.

FIRST ANGLE PROJECTION:

This drawing is the property of LEDiL Oy. It may not be copied or otherwise distributed without prior written permission from LEDiL Oy.

SCALE 1:1 | WEIGHT 0,448 g | A3 SHEET 1/1

Notes

PCB or heatsink level.
LED location
Ensure LED fitting from a product specific 3D model available from www.ledil.com
For more details about installation please see LEDiL Installation Guide on www.ledil.com

See also our general installation guide: www.ledil.com/installation_guide


LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (MEASURED):

NICHIA

LED	NCSxE17A
FWHM / FWTM	38.0° / 57.0°
Efficiency	90 %
Peak intensity	2.3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	






NICHIA

LED	NVSxE21A
FWHM / FWTM	39.0° / 59.0°
Efficiency	90 %
Peak intensity	2.1 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	






SAMSUNG

LED	LH151B
FWHM / FWTM	33.0° / 53.0°
Efficiency	87 %
Peak intensity	2.6 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	






SAMSUNG

LED	LH181B
FWHM / FWTM	42.0° / 63.0°
Efficiency	89 %
Peak intensity	1.8 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	






LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (SIMULATED):


LUMILEDS

LED	LUXEON CSP HL1
FWHM / FWTM	32.0° / 48.0°
Efficiency	96 %
Peak intensity	3.1 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




LUMILEDS

LED	LUXEON HL1Z
FWHM / FWTM	38.0° / 56.0 + 55.0°
Efficiency	91 %
Peak intensity	2.3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




LUMILEDS

LED	LUXEON HL2Z
FWHM / FWTM	42.0 + 41.0° / 61.0 + 60.0°
Efficiency	91 %
Peak intensity	2 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



NICHIA

LED	NFSWE11A
FWHM / FWTM	36.0° / 52.0°
Efficiency	85 %
Peak intensity	2.4 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (SIMULATED):

OSRAM
Opto Semiconductors

LED	OSCONIQ C 2424
FWHM / FWTM	46.0° / 66.0°
Efficiency	92 %
Peak intensity	1.7 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



SAMSUNG


LED	LM101B
FWHM / FWTM	41.0°
Efficiency	90 %
Peak intensity	2.1 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	

SAMSUNG

LED	LM231 A/B
FWHM / FWTM	40.0° / 64.0°
Efficiency	91 %
Peak intensity	2.1 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	

SEOUL SEMICONDUCTOR

LED	Z8Y11
FWHM / FWTM	35.0° / 54.0°
Efficiency	87 %
Peak intensity	2.4 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (SIMULATED):


SEOUL SEMICONDUCTOR

LED	Z8Y15
FWHM / FWTM	35.0° / 53.0°
Efficiency	86 %
Peak intensity	2.6 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




SEOUL SEMICONDUCTOR

LED	Z8Y19
FWHM / FWTM	37.0° / 56.0°
Efficiency	87 %
Peak intensity	2.3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



SEOUL SEMICONDUCTOR

LED	Z8Y22
FWHM / FWTM	36.0° / 60.0°
Efficiency	86 %
Peak intensity	2.1 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy
Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.
228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.
405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support
www.ledil.com/
where_to_buy

Shipping locations
Salo, Finland
Hong Kong, China

Distribution Partners
www.ledil.com/
where_to_buy

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.