ILONA-SS

~14° smooth spot beam



TECHNICAL SPECIFICATIONS:

Dimensions	Ø 49.8 mm
Height	29.3 mm
Fastening	socket
ROHS compliant	yes


MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
ILONA-SS	Single lens	PMMA	clear	

ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
C16731_ILONA-SS » Box size: 480 x 280 x 300 mm	264	99	33	9.7

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.



See also our general installation guide: www.ledil.com/installation_guide

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (MEASURED):


bridgelux

LED	V11 HD Gen 8
FWHM / FWTM	22.0° / 41.0°
Efficiency	94 %
Peak intensity	4.8 cd/lm
LEDs/each optic	1
Light colour	White

Required components:

Bender Wirth: 633d Hekla







bridgelux

LED	V6 HD Gen 7
FWHM / FWTM	15.0° / 27.0°
Efficiency	95 %
Peak intensity	11.1 cd/lm
LEDs/each optic	1
Light colour	White

Required components:

Bender Wirth: 634c Hekla






bridgelux

LED	V6 HD Gen 7
FWHM / FWTM	15.0° / 27.0°
Efficiency	96 %
Peak intensity	11.4 cd/lm
LEDs/each optic	1
Light colour	White

Required components:

F15255_HEKLA-SOCKET-C





bridgelux


LED	Vesta DTW 9mm (4W/6W/12W)
FWHM / FWTM	18.0° / 36.0°
Efficiency	93 %
Peak intensity	6.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:

C16142_HEKLA-SOCKET-K

Bender Wirth: 490 Typ L8





LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (MEASURED):


bridgelux


LED	Vesta TW 6mm DP
FWHM / FWTM	14.0° / 28.0°
Efficiency	91 %
Peak intensity	10.3 cd/lm
LEDs/each optic	1
Light colour	White

Required components:

C16142_HEKLA-SOCKET-K

Bender Wirth: 504 Typ L8







CITIZEN

LED	CLU7A2 (LES 4.2mm)
FWHM / FWTM	11.0° / 21.0°
Efficiency	94 %
Peak intensity	18 cd/lm
LEDs/each optic	1
Light colour	White

Required components:

F15255_HEKLA-SOCKET-C







CITIZEN

LED	CLU7B2
FWHM / FWTM	10.0° / 20.0°
Efficiency	94 %
Peak intensity	19.7 cd/lm
LEDs/each optic	1
Light colour	White

Required components:

F15255_HEKLA-SOCKET-C






LUMILEDS

LED	LUXEON CX Plus CoB L08 (Gen2)
FWHM / FWTM	26.0° / 52.0°
Efficiency	93 %
Peak intensity	3 cd/lm
LEDs/each optic	1
Light colour	White

Required components:

Bender Wirth: 637a Hekla





LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):


LUMILEDS

LED	LUXEON CX Plus CoB - HD S01H4
FWHM / FWTM	13.0° / 25.0°
Efficiency	95 %
Peak intensity	13.2 cd/lm
LEDs/each optic	1
Light colour	White

Required components:

Bender Wirth: 634c Hekla







LUMILEDS

LED	LUXEON CX Plus CoB - HD S01H6 / HD S02H6
FWHM / FWTM	14.0° / 27.0°
Efficiency	94 %
Peak intensity	11.7 cd/lm
LEDs/each optic	1
Light colour	White

Required components:

Bender Wirth: 634c Hekla






LUMILEDS

LED	LUXEON CX Plus CoB - HD S04H9
FWHM / FWTM	19.0° / 35.0°
Efficiency	94 %
Peak intensity	6.8 cd/lm
LEDs/each optic	1
Light colour	White

Required components:

Bender Wirth: 634c Hekla






LUMILEDS

LED	LUXEON CX Plus CoB L04 / L05 (Gen2)
FWHM / FWTM	22.0° / 43.0°
Efficiency	94 %
Peak intensity	4.6 cd/lm
LEDs/each optic	1
Light colour	White

Required components:

Bender Wirth: 637a Hekla





LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):

LUMILEDS

LED	LUXEON CX Plus CoB M02 / M03 (Gen2)
FWHM / FWTM	17.0° / 33.0°
Efficiency	94 %
Peak intensity	7.6 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
Bender Wirth: 641a Hekla







LUMILEDS

LED	LUXEON CX Plus CoB S01 (Gen2)
FWHM / FWTM	13.0° / 26.0°
Efficiency	94 %
Peak intensity	12.3 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
Bender Wirth: 634c Hekla







LUMINUS

LED	CXM-3
FWHM / FWTM	11.0° / 20.0°
Efficiency	94 %
Peak intensity	20.2 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F15255_HEKLA-SOCKET-C







LUMINUS

LED	CXM-4
FWHM / FWTM	12.0° / 23.0°
Efficiency	94 %
Peak intensity	15.8 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F15255_HEKLA-SOCKET-C






LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):

OSRAM
Opto Semiconductors

LED	OSTAR Stage (S2WN)
FWHM / FWTM	10.0° / 19.0°
Efficiency	94 %
Peak intensity	22.9 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F15859_HEKLA-SOCKET-I







OSRAM
Opto Semiconductors

LED	OSTAR Stage (S2WP)
FWHM / FWTM	11.0° / 21.0°
Efficiency	94 %
Peak intensity	18.6 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F15859_HEKLA-SOCKET-I






SAMSUNG

LED	LC010T (Tunable White)
FWHM / FWTM	18.0° / 37.0°
Efficiency	94 %
Peak intensity	6.1 cd/lm
LEDs/each optic	1
Light colour	Tunable White

Required components:
C16142_HEKLA-SOCKET-K
Bender Wirth: 501 Typ L8






SEOUL SEMICONDUCTOR

LED	MJT COB LES 14.5
FWHM / FWTM	33.0° / 57.0°
Efficiency	95 %
Peak intensity	2.4 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F17438_HEKLA-G2-I






LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):

SEOUL SEMICONDUCTOR

LED	MJT COB LES 6
FWHM / FWTM	14.0° / 26.0°
Efficiency	96 %
Peak intensity	12.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F17435_HEKLA-G2-C






SEOUL SEMICONDUCTOR

LED	MJT COB LES 9.8
FWHM / FWTM	21.0° / 37.0°
Efficiency	96 %
Peak intensity	5.9 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F17435_HEKLA-G2-C






TRIDONIC

LED	SLE G7 LES09
FWHM / FWTM	18.0° / 34.0°
Efficiency	95 %
Peak intensity	7 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F15255_HEKLA-SOCKET-C







XICATO

LED	XOB 6 mm
FWHM / FWTM	14.0° / 26.0°
Efficiency	94 %
Peak intensity	11.7 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F15255_HEKLA-SOCKET-C





LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):


XICATO

LED	XOB 9.8 mm
FWHM / FWTM	19.0° / 35.0°
Efficiency	94 %
Peak intensity	6.8 cd/lm
LEDs/each optic	1
Light colour	White

Required components:

F15255_HEKLA-SOCKET-C






LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (SIMULATED):


bridgelux

LED	V13 Gen 8
FWHM / FWTM	30.0° / 52.0°
Efficiency	92 %
Peak intensity	3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	
F15859_HEKLA-SOCKET-I	




bridgelux

LED	V4 HD Gen 7
FWHM / FWTM	12.0° / 23.0°
Efficiency	91 %
Peak intensity	15.6 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	
F15253_HEKLA-SOCKET-A	




bridgelux

LED	V9 HD Gen7
FWHM / FWTM	18.0° / 32.0°
Efficiency	94 %
Peak intensity	7.7 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	
F15859_HEKLA-SOCKET-I	



bridgelux

LED	Vero SE 10
FWHM / FWTM	18.0° / 36.0°
Efficiency	94 %
Peak intensity	6.7 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (SIMULATED):


bridgelux

LED	Vero SE 13
FWHM / FWTM	20.0° / 50.0°
Efficiency	91 %
Peak intensity	3.5 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	
C16142_HEKLA-SOCKET-K	




bridgelux

LED	Vesta TW 9mm (9W) DP
FWHM / FWTM	18.0° / 35.0°
Efficiency	86 %
Peak intensity	6.3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	
C16142_HEKLA-SOCKET-K	
Bender Wirth: 489 Typ L8	




CITIZEN

LED	CLL02x/CLU02x (LES10)
FWHM / FWTM	21.0° / 35.0°
Efficiency	87 %
Peak intensity	6.2 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	
F15255_HEKLA-SOCKET-C	



CITIZEN

LED	CLU700/701/702
FWHM / FWTM	14.0° / 25.0°
Efficiency	91 %
Peak intensity	12.9 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	
F15255_HEKLA-SOCKET-C	




LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (SIMULATED):

CITIZEN

LED	CLU712
FWHM / FWTM	18.0° / 33.0°
Efficiency	95 %
Peak intensity	7.6 cd/lm
LEDs/each optic	1
Light colour	White


Required components:
F17438_HEKLA-G2-I



CREE LED

LED	CHA0304
FWHM / FWTM	11.0° / 22.0°
Efficiency	95 %
Peak intensity	18.1 cd/lm
LEDs/each optic	1
Light colour	White


Required components:
F17435_HEKLA-G2-C



CREE LED

LED	CHA0410
FWHM / FWTM	12.0° / 24.0°
Efficiency	95 %
Peak intensity	15.1 cd/lm
LEDs/each optic	1
Light colour	White


Required components:
F17435_HEKLA-G2-C



CREE LED

LED	CMA1303
FWHM / FWTM	12.0° / 24.0°
Efficiency	96 %
Peak intensity	16 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F17439_HEKLA-G2-J




LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (SIMULATED):


LED ENGIN

LED	LZ4-00XX08
FWHM / FWTM	10.0° / 22.0°
Efficiency	95 %
Peak intensity	19.7 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	
F15255_HEKLA-SOCKET-C	




LED ENGIN






LED	LZ4-00XX08
FWHM / FWTM	12.0° / 23.0°
Efficiency	96 %
LEDs/each optic	1
Light colour	IR
Required components:	
F15255_HEKLA-SOCKET-C	




LUMILEDS

LED	LUXEON CoB 1202/1203
FWHM / FWTM	19.0° / 35.0°
Efficiency	93 %
Peak intensity	6.8 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	
F17437_HEKLA-G2-H	



LUMILEDS

LED	LUXEON CoB 1202s
FWHM / FWTM	14.0° / 26.0°
Efficiency	96 %
Peak intensity	12.1 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	
F15858_HEKLA-SOCKET-H	




LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (SIMULATED):


LUMILEDS

LED	LUXEON CoB 1204/1205
FWHM / FWTM	26.0° / 47.0°
Efficiency	93 %
Peak intensity	3.6 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




LUMILEDS


LED	LUXEON CoB 1208
FWHM / FWTM	28.0° / 52.0°
Efficiency	90 %
Peak intensity	2.9 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



LUMILEDS


LED	LUXEON Rubix
FWHM / FWTM	13.0° / 24.0°
Efficiency	95 %
Peak intensity	15.1 cd/lm
LEDs/each optic	4
Light colour	RGBW
Required components:	





NICHIA

LED	COB S-Type (LES 6)
FWHM / FWTM	14.0° / 26.0°
Efficiency	93 %
Peak intensity	12.2 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	
F15848_HEKLA-SOCKET-G	




LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (SIMULATED):


NICHIA

LED	COB S-Type (LES 6)
FWHM / FWTM	14.0° / 26.0°
Efficiency	93 %
Peak intensity	12.1 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	
F15848_HEKLA-SOCKET-G	




NICHIA

LED	COB S-Type (LES 7)
FWHM / FWTM	16.0° / 30.0°
Efficiency	95 %
Peak intensity	10.2 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	
F15848_HEKLA-SOCKET-G	




NICHIA

LED	NFSWE11A
FWHM / FWTM	18.0° / 32.0°
Efficiency	88 %
Peak intensity	7.5 cd/lm
LEDs/each optic	30
Light colour	White
Required components:	
C16142_HEKLA-SOCKET-K	



NICHIA

LED	NJCWL024Z-V1MT: COB L-Type Tunable White
FWHM / FWTM	16.0° / 30.0°
Efficiency	94 %
Peak intensity	9.7 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	
C16142_HEKLA-SOCKET-K	
Bender Wirth: 497 Typ L8	




LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (SIMULATED):


NICHIA

LED	NVCWJ024Z-V1MT: COB J-Type Tunable White
FWHM / FWTM	20.0° / 40.0°
Efficiency	93 %
Peak intensity	5.3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	
C16142_HEKLA-SOCKET-K	
Bender Wirth: 498 Typ L8	




PHILIPS

LED	Fortimo SLM L13 CoB
FWHM / FWTM	24.0° / 46.0°
Efficiency	93 %
Peak intensity	3.9 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	
Bender Wirth: 632a Hekla XL	




PHILIPS

LED	Fortimo SLM L15 CoB
FWHM / FWTM	26.0° / 51.0°
Efficiency	92 %
Peak intensity	3.2 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	
Bender Wirth: 632a Hekla XL	



SAMSUNG

LED	LC003D / LC006D / LC009D / LC013D
FWHM / FWTM	19.0° / 34.0°
Efficiency	87 %
Peak intensity	6.6 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	
F15255_HEKLA-SOCKET-C	




LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (SIMULATED):


SAMSUNG

LED	LC020C
FWHM / FWTM	14.0° / 28.0°
Efficiency	94 %
Peak intensity	11.4 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	
F17438_HEKLA-G2-I	




SAMSUNG

LED	LC020T (Tunable white)
FWHM / FWTM	22.0° / 42.0°
Efficiency	92 %
Peak intensity	4.6 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	
C16142_HEKLA-SOCKET-K	
Bender Wirth: 501 Typ L8	



XICATO

LED	XTM - 9mm LES
FWHM / FWTM	18.0° / 34.0°
Efficiency	94 %
Peak intensity	7.5 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	
C15743_XTM-ADAPTER-50-B	



LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy
Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.
228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.
405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support
www.ledil.com/
where_to_buy

Shipping locations
Salo, Finland
Hong Kong, China

Distribution Partners
www.ledil.com/
where_to_buy

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.