LINDA-UP

~145° + 100° extra wide beam for uplighting



TECHNICAL SPECIFICATIONS:

Dimensions	25.7 x 1140.0 mm
Height	7.8 mm
ROHS compliant	yes


MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
LINDA-UP	Linear lens	PMMA		

ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
F16860_LINDA-UP » Box size: 1185 x 150 x 115 mm	100	100	100	12.6

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.




See also our general installation guide: www.ledil.com/installation_guide

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (MEASURED):

CITIZEN


LED	CLUC11
FWHM / FWTM	Asymmetric
Efficiency	85 %
Peak intensity	0.3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



CREE LED


LED	XP-G3
FWHM / FWTM	Asymmetric
Efficiency	84 %
Peak intensity	0.2 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	





LUMILEDS


LED	LUXEON 3030 2D (Round LES)
FWHM / FWTM	Asymmetric
Efficiency	86 %
Peak intensity	0.3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



NICHIA

LED	NF2W757G-MT (Tunable White)
FWHM / FWTM	Asymmetric
Efficiency	87 %
Peak intensity	0.3 cd/lm
LEDs/each optic	1
Light colour	Tunable White
Required components:	






LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (MEASURED):


NICHIA

LED	NFSW757H
FWHM / FWTM	Asymmetric
Efficiency	88 %
Peak intensity	0.3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




OSRAM

LED	PL-LIN-Z5 1100 280x20
FWHM / FWTM	Asymmetric
Efficiency	82 %
Peak intensity	0.3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




OSRAM

LED	PL-LIN-Z5 2000 280x20
FWHM / FWTM	Asymmetric
Efficiency	80 %
Peak intensity	0.3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



OSRAM
Opto Semiconductors

LED	Duris E 2835
FWHM / FWTM	Asymmetric
Efficiency	82 %
Peak intensity	0.3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (MEASURED):


OSRAM
Opto Semiconductors

LED	Duris E 2835
FWHM / FWTM	Asymmetric
Efficiency	80 %
Peak intensity	0.3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




OSRAM
Opto Semiconductors

LED	Duris E 2835
FWHM / FWTM	Asymmetric
Efficiency	88 %
Peak intensity	0.3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




PHILIPS

LED	Fortimo LED Strip 1ft 1100lm FC HV4 & LV4
FWHM / FWTM	Asymmetric
Efficiency	82 %
Peak intensity	0.3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



PHILIPS

LED	Fortimo LED Strip 1ft 1100lm FC HV5 & LV5
FWHM / FWTM	Asymmetric
Efficiency	88 %
Peak intensity	0.3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (MEASURED):


PHILIPS

LED	Fortimo LED Strip 1ft 650lm FC HV4 & LV4
FWHM / FWTM	Asymmetric
Efficiency	83 %
Peak intensity	0.3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




PHILIPS

LED	Fortimo LED Strip 1ft 650lm FC HV5 & LV5
FWHM / FWTM	Asymmetric
Efficiency	87 %
Peak intensity	0.3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




SAMSUNG

LED	LM28xB Series
FWHM / FWTM	Asymmetric
Efficiency	88 %
Peak intensity	0.3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



SAMSUNG

LED	LM301B
FWHM / FWTM	Asymmetric
Efficiency	87 %
Peak intensity	0.3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (MEASURED):

SAMSUNG

LED	LM561C
FWHM / FWTM	Asymmetric
Efficiency	87 %
Peak intensity	0.3 cd/lm
LEDs/each optic	1
Light colour	White


Required components:



SAMSUNG

LED	LT-H282C
FWHM / FWTM	Asymmetric
Efficiency	86 %
Peak intensity	0.3 cd/lm
LEDs/each optic	1
Light colour	White


Required components:



SAMSUNG

LED	LT-Q282B
FWHM / FWTM	Asymmetric
Efficiency	88 %
Peak intensity	0.3 cd/lm
LEDs/each optic	1
Light colour	White


Required components:



SAMSUNG

LED	LT-S282H
FWHM / FWTM	Asymmetric
Efficiency	87 %
Peak intensity	0.3 cd/lm
LEDs/each optic	1
Light colour	White

Required components:




LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (MEASURED):


SEOUL SEMICONDUCTOR

LED	SEOUL DC 3528
FWHM / FWTM	Asymmetric
Efficiency	88 %
Peak intensity	0.3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




TRIDONIC

LED	LLE 24x280mm 1250lm HV ADV5
FWHM / FWTM	Asymmetric
Efficiency	83 %
Peak intensity	0.3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




TRIDONIC

LED	LLE 24x280mm 650lm HV ADV5
FWHM / FWTM	Asymmetric
Efficiency	83 %
Peak intensity	0.3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



TRIDONIC

LED	LLE FLEX CC 14mm 1250lm ADV1
FWHM / FWTM	Asymmetric
Efficiency	86 %
Peak intensity	0.3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (SIMULATED):


bridgelux

LED	Bridgelux SMD 5050
FWHM / FWTM	Asymmetric
Efficiency	80 %
Peak intensity	0.3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




LUMILEDS

LED	LUXEON CSP HL1
FWHM / FWTM	93.0 + 135.0° / 163.0 + 167.0°
Efficiency	88 %
Peak intensity	0.4 cd/lm
LEDs/each optic	5
Light colour	White
Required components:	




NICHIA

LED	NFSWE11A
FWHM / FWTM	Asymmetric
Efficiency	82 %
Peak intensity	0.3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



OSRAM
Opto Semiconductors

LED	OSLON Square CSSRM2/CSSRM3
FWHM / FWTM	Asymmetric
Efficiency	87 %
Peak intensity	0.3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (SIMULATED):


OSRAM Opto Semiconductors

LED	OSLON Square CSSRM2/CSSRM3
FWHM / FWTM	Asymmetric
Efficiency	89 %
Peak intensity	0.3 cd/lm
LEDs/each optic	1
Light colour	Hyper Red
Required components:	




OSRAM Opto Semiconductors

LED	OSLON Square CSSRM2/CSSRM3
FWHM / FWTM	Asymmetric
Efficiency	87 %
Peak intensity	0.3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




OSRAM Opto Semiconductors

LED	OSLON SSL 150
FWHM / FWTM	Asymmetric
Efficiency	84 %
Peak intensity	0.3 cd/lm
LEDs/each optic	1
Light colour	Far Red
Required components:	



SEOUL SEMICONDUCTOR

LED	SEOUL DC 5050 6V
FWHM / FWTM	Asymmetric
Efficiency	80 %
Peak intensity	0.3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy
Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.
228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.
405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support
www.ledil.com/
where_to_buy

Shipping locations
Salo, Finland
Hong Kong, China

Distribution Partners
www.ledil.com/
where_to_buy

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.