Data sheet

17274.4 SST/SSIK/LED 500V AC/DC



Status display, Display: LED, Mounting type: Plug in, Colour: Black

RAL: 9005

Business data

Article number	17274.4
Article name	SST/SSIK/LED 500V AC/DC
GTIN (EAN)	4044211180423
Colour	Black
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	1.86 g
Weight per piece (including packaging)	1.96 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Product description	Status display

Data sheet

17274.4 SST/SSIK/LED 500V AC/DC

Technical data

Dimensions	
Length	30 mm
Width	6.1 mm
Height	14 mm
Connection data	
Connection principle	Plug in
Materials	
Insulation housing	Polyamide 6.6
Flammability class UL 94	V-0
Working temperature, min.	-40 °C
Working temperature, max.	140 °C
Further technical data	
Mounting type	Plug in
Fuse size	6,3 x 25 / 6,3 x 32 mm
Voltage illuminated display	500 V
Cross-current via illuminated display	< 5 mA
Type of display element (defect display)	LED
Version of fuse cartridge	G fuse 6.3 x 25 / 6.3 x 32
Supply voltage (defect display), min.	500
Supply voltage (defect display), max.	500
Type of voltage (defect display)	AC/DC
Environmental Product Compliance	
REACH Conform	yes
REACH Reference date	2022-06-10
REACH Candidate Substance Note	No
RoHS Conform	yes


Approvals

KEMA KEUR approval	
KEMA KEUR approval	EN 60947-7-3:2009
KEMA KEUR approval granted	yes
KEMA rated voltage	500 V

Data sheet

17274.4 SST/SSIK/LED 500V AC/DC

Media



Accessories