Data sheet

17396.6 SDK 16/1A/1B GR



Feed-through terminal, Screw connection, Mounting type: Mounting surface, Rated cross-section: 16 mm², Colour: Grey

RAL: 7030

Business data

Article number	17396.6
Article name	SDK 16/1A/1B GR
GTIN (EAN)	4044211210618
Colour	Grey
Packaging unit	50
Quantity unit	PC
Weight per piece (not including packaging)	26.91 g
Weight per piece (including packaging)	27.31 g
Unit of weight	G
Customs number	85369010
Country of origin	CZ
Product description	Panel feed-through terminal

Data sheet

17396.6 SDK 16/1A/1B GR

Technical data

Dimensions

Length of outer part	37.2 mm
Length of inner part	9.3 mm
Width of outer part	12 mm
Width of inner part	12 mm
Height of outer part	41.3 mm
Height of inner part	28 mm

Ratings

Rated voltage	400 V
Rated voltage when used without outer spacer plates, and when mounted on a conductive housing panel with use of encapsulation compound or inner partition plates	630 V
Rated voltage when used with outer spacer plates, and when mounted on a conductive housing panel with use of encapsulation compound or inner partition plates	1000 V
Rated current	76 A
Current load, max.	101 A
Rated cross-section	16 mm²
Rated impulse voltage	6 kV
Overvoltage category	III
Contamination degree	3
Maximum power dissipation for nominal condition	2.43 W

Data sheet

17396.6 SDK 16/1A/1B GR

Technical data

Connection data

Connection principle	Screw connection
Number of terminals per pole	2
No. of poles	1
Wire cross-section single-core (rigid) / stranded, min.	1.5 mm²
Wire cross-section single core (rigid)/stranded, max.	25 mm²
Wire cross-section stranded, min.	1.5 mm²
Wire cross-section stranded, max.	25 mm²
Wire cross-section stranded with wire-end ferrules,min.	1.5 mm²
Wire cross-section stranded with wire-end ferrules,max.	16 mm²
Wire cross-section AWG, min.	16
Wire cross-section AWG, max.	4
Stripping length	16 mm
Screw head	Slotted
Screw threading	M 5
Screw head inner part	Cross-head
Screw thread inner part	M 5
Tightening torque, min.	2 Nm
Tightening torque, max.	4 Nm
Screw inner part: tightening torque, min.	2.5 Nm
Screw inner part: tightening torque, max.	3 Nm

Materials

Insulation housing	Polyamide 6.6
Flammability class UL 94	V-0
Working temperature, min.	-40 °C
Working temperature, max.	120 °C

Further technical data

Mounting type	Mounting face
Gauge plug acc. to EN 60 947-1	A7
Sheet thickness min.	1 mm
Sheet thickness max.	6 mm
Sheet thickness when using spacer plates, min.	1 mm
Sheet thickness when using spacer plates, max.	5 mm
Thickness of mounting plate, min.	1
Thickness of mounting plate, max.	6

Data sheet

17396.6 SDK 16/1A/1B GR

Technical data

Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2022-06-10
REACH Candidate Substance Note	No
RoHS Conform	yes

Approvals

Standards and regulations

EAC approval	TR ZU 004/2011
EAC approval granted	yes

cUL Recognized

cUL approval	C22.2 No 158
cUL Usegroup B: rated voltage	300 V
cUL Usegroup B: rated voltage when using the SDK 4-DP spacer plate and the SDK 4-AP adapter plate	600 V
cUL Usegroup B: rated current	5 A
cUL Usegroup B: rated current when using the SDK 4-DP spacer plate and the SDK 4-AP adapter plate	85 A
cUL Usegroup C: rated voltage when using the SDK 4-DP spacer plate and the SDK 4-AP adapter plate	600 V
cUL Usegroup C: rated current when using the SDK 4-DP spacer plate and the SDK 4-AP adapter plate	85 A
cUL Usegroup D: rated voltage	300 V
cUL Usegroup D: rated voltage when using the SDK 4-DP spacer plate	600 V
cUL Usegroup D: rated current	5 A
cUL Usegroup D: rated current when using the SDK 4-DP spacer plate	85 A
cUL wire cross-section single-core (rigid) AWG, min.	16
cUL wire cross-section single-core (rigid) AWG, max.	4
cUL wire cross-section stranded AWG, min.	16
cUL wire cross-section stranded AWG, max.	4
cUL torque, min.	2 Nm
cUL torque, max.	4 Nm
cUL wire material	Cu
cUL Recognized	1

Approvals

KEMA KEUR approval


KEMA KEUR approval	EN 60947-7-1:2009
KEMA KEUR approval granted	yes
KEMA rated voltage with feed-through plate 1-2 mmthickness	100 V
KEMA rated voltage with feed-through plate max. 3-5mm thickness	800 V
KEMA rated voltage with feed-through plate 6 mmthickness	630 V
KEMA conventional thermal current in free air	76 A
KEMA rated impulse voltage (for 250 V without partitions)	6 kV
KEMA wire cross-section, min.	1.5 mm²
KEMA wire cross-section, max.	25 mm²
KEMA torque, max.	2 Nm

Approvals

UL Recognized

UL approval	UL 1059
UL Usegroup B: rated voltage	300 V
UL Usegroup B: rated current when using the SDK 4-DP spacer plate and the SDK 4-AP adapter plate	600 A
UL Usegroup B: rated current	5 A
UL Usegroup B: rated voltage when using the SDK 4-DP spacer plate and the SDK 4-AP adapter plate	85 V
UL Usegroup C: rated voltage when using the SDK 4-DP spacer plate and the SDK 4-AP adapter plate	600 V
UL Usegroup C: rated current when using the SDK 4-DP spacer plate and the SDK 4-AP adapter plate	85 A
UL Usegroup D: rated voltage	300 V
UL Usegroup D: rated voltage when using the SDK 4-DP spacer plate	600 V
UL Usegroup D: rated current	5 A
UL Usegroup D: rated current when using the SDK 4-DP spacer plate	85 A
UL wire cross-section single-core (rigid) AWG, min.	16
UL wire cross-section single-core (rigid) AWG, max.	4
UL wire cross-section stranded AWG, min.	16
UL wire cross-section stranded AWG, max.	4
UL torque, min.	17.7 Lb In.
UL torque, max.	35.4 Lb In.
UL wire material	Cu
UL factory wiring	1
UL field wiring	1
UL Recognized	1

Media





Data sheet

17396.6 SDK 16/1A/1B GR

Accessories

Outer 6-pole adapter plate



Partition plate, Colour: Grey

Article number	Article name	GTIN (EAN)	Packaging unit
17453.6	SDK 16-AP/6 GR	4044211210656	10 ST

Inner mounting screw



Screw, Colour: natural

Article number	Article name	GTIN (EAN)	Packaging unit
17448.6	BS-SDK 10/16 4x14	4044211210083	100 ST

Outer spacer plate



Partition plate, Colour: Grey

Article number	Article name	GTIN (EAN)	Packaging unit
17454.6	SDK 16-DPA GR	4044211210663	50 ST

Set: outer flange plate



Flange plate, Colour: Grey

Article number	Article name	GTIN (EAN)	Packaging unit
17452.6	SDK 16-FP GR	4044211210649	50 ST

Data sheet


17396.6 SDK 16/1A/1B GR

Perforated foam seal

Seal, Colour: Dark grey

Article number	Article name	GTIN (EAN)	Packaging unit
17456.4	SDK 16-SPI/10 DG	4044211210687	100 ST

Quick marking



Terminal marker / Pocket Maxicard, Length: 12 mm, Width: 10 mm, Colour: White

Article number	Article name	GTIN (EAN)	Packaging unit
9433.7	PMC BSTR 10x12/10 WH	4044211155223	100 ST

Screwdriver



Screwdriver with bare blade, Colour: Black-grey

Article number	Article name	GTIN (EAN)	Packaging unit
1087.0	SDB 0,8x4,0	4044211014803	1 ST

Inner partition plate, solder connection



Partition, Width: 6.4 mm, Color: Red

Article number	Article name	GTIN (EAN)	Packaging unit
17455.9	SDK 16-TWI RD	4044211210670	50 ST

Inner moulded plate

Partition plate, Colour: Grey

Article number	Article name	GTIN (EAN)	Packaging unit
17457.6	SDK 16-VPI GR	4044211210694	50 ST