

PCB connector - ZEC 1,5/ 9-LPV-5,0 C2



1898334

<https://www.phoenixcontact.com/us/products/1898334>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



PCB connector, nominal cross section: 1.5 mm², color: green, nominal current: 10 A, rated voltage (III/2): 320 V, contact surface: Tin, type of contact: Female connector, number of potentials: 9, number of rows: 1, number of positions: 9, number of connections: 9, product range: ZEC 1,5/..-LPV, pitch: 5 mm, mounting: Direct plug-in method, conductor/PCB connection direction: 0 °, number of solder pins per potential: 2, plug-in system: ZEC, locking: without, mounting: without, type of packaging: packed in cardboard

Your advantages

- Easy component connection
- Inexpensive direct plug-in connection with just one component

Commercial Data

Item number	1898334
Packing unit	1 pc
Minimum order quantity	50 pc
Note	Made to Order (non-returnable)
Sales Key	A01
Product Key	AACEAA
GTIN	4017918167042
Weight per Piece (including packing)	8 g
Weight per Piece (excluding packing)	6.96 g
Customs tariff number	85366930
Country of origin	GR

PCB connector - ZEC 1,5/ 9-LPV-5,0 C2



1898334

<https://www.phoenixcontact.com/us/products/1898334>

Technical Data

Product properties

Type	PCB connector
Product line	COMBICON Connectors M
Product type	PCB connector
Number of positions	9
Pitch	5 mm
Number of connections	9
Number of rows	1
Mounting flange	without
Number of potentials	9
Solder pins per potential	2

Electrical properties

Nominal current I_N	10 A
Nominal voltage U_N	320 V
Degree of pollution	3
Contact resistance	1.2 mΩ
Rated voltage (III/3)	250 V
Rated surge voltage (III/3)	4 kV
Rated voltage (III/2)	320 V
Rated surge voltage (III/2)	4 kV

Mounting

Mounting type	Direct plug-in method
---------------	-----------------------

Material specifications

Material data - contact

Note	WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201
Contact material	Cu alloy
Metal surface contact area (top layer)	Tin (5 - 7 μm Sn)

Material data - housing

Housing color	green (6021)
Insulating material	PA
Insulating material group	I
CTI according to IEC 60112	600
Flammability rating according to UL 94	V0
Glow wire flammability index GWFI according to EN 60695-2-12	850
Glow wire ignition temperature GWIT according to EN 60695-2-13	775

PCB connector - ZEC 1,5/ 9-LPV-5,0 C2



1898334

<https://www.phoenixcontact.com/us/products/1898334>

Temperature for the ball pressure test according to EN 60695-10-2

125 °C


Notes

Notes on operation

In accordance with IEC 61984, COMBICON connectors have no switching power (COC). During designated use, they must not be plugged in or disconnected when carrying voltage or under load.

Dimensions

Dimensional drawing



Pitch

5 mm

Width [w]

46.37 mm

Height [h]

7 mm

Length [l]

22.9 mm

Installed height

7 mm

Mechanical tests

Insertion and withdrawal forces

Result

Test passed

No. of cycles

20

Insertion strength per pos. approx.

6 N

Withdraw strength per pos. approx.

3 N

Resistance of inscriptions

Specification

IEC 60068-2-70:1995-12

Result

Test passed

Visual inspection

Specification

IEC 60512-2:1985-00

Result

Test passed

Dimension check

Specification

IEC 60512-2:1985-00

Result

Test passed

Electrical tests

Air clearances and creepage distances |

Specification

IEC 60664-1:2007-04

Insulating material group

I

Comparative tracking index (IEC 60112)

CTI 600

Rated insulation voltage (III/3)

250 V

PCB connector - ZEC 1,5/ 9-LPV-5,0 C2



1898334

<https://www.phoenixcontact.com/us/products/1898334>

Rated surge voltage (III/3)	4 kV
minimum clearance value - non-homogenous field (III/3)	3 mm
minimum creepage distance (III/3)	3.2 mm
Rated insulation voltage (III/2)	320 V
Rated surge voltage (III/2)	4 kV
minimum clearance value - non-homogenous field (III/2)	3 mm
minimum creepage distance (III/2)	3 mm
Rated insulation voltage (II/2)	630 V
Rated surge voltage (II/2)	4 kV
minimum clearance value - non-homogenous field (II/2)	3 mm
minimum creepage distance (II/2)	3.2 mm

Environmental and real-life conditions

Vibration test

Specification	IEC 60068-2-6:1995-03
Frequency	10 - 150 - 10 Hz
Sweep speed	1 octave/min
Amplitude	0.35 mm (10 - 60.1 Hz)
Sweep speed	5g (60.1 - 150 Hz)
Test duration per axis	2.5 h

Durability test

Specification	IEC 60512-5:1992-08
Contact resistance R_1	1.2 mΩ
Contact resistance R_2	1.5 mΩ
Insertion/withdrawal cycles	20

Climatic test

Specification	ISO 6988:1985-02
Corrosive stress	0.2 dm ³ SO ₂ on 300 dm ³ /40 °C/1 cycle
Thermal stress	100 °C/168 h
Power-frequency withstand voltage	2.21 kV

Ambient conditions

Ambient temperature (operation)	-40 °C ... 100 °C (dependent on the derating curve)
Ambient temperature (storage/transport)	-40 °C ... 70 °C
Relative humidity (storage/transport)	30 % ... 70 %
Ambient temperature (assembly)	-5 °C ... 100 °C

Packaging specifications

Type of packaging	packed in cardboard
-------------------	---------------------

PCB connector - ZEC 1,5/ 9-LPV-5,0 C2


1898334

<https://www.phoenixcontact.com/us/products/1898334>



Drawings

Dimensional drawing



PCB connector - ZEC 1,5/ 9-LPV-5,0 C2

1898334

<https://www.phoenixcontact.com/us/products/1898334>



Approvals

	CB IECEx CB Scheme Approval ID: DE1-51128			
	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
	1000 V	10 A	-	-

EAC EAC Approval ID: B.01687				
--	--	--	--	--

cULus cULus Recognized Approval ID: E60425-19941110				
	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
Use group B				
	300 V	10 A	-	-
Use group D				
	300 V	10 A	-	-

VDE VDE Gutachten mit Fertigungsüberwachung Approval ID: 40020343				
	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
	250 V	10 A	-	-

PCB connector - ZEC 1,5/ 9-LPV-5,0 C2



1898334

<https://www.phoenixcontact.com/us/products/1898334>

Classifications

ECLASS

ECLASS-9.0	27440402
ECLASS-10.0.1	27440402
ECLASS-11.0	27460201

ETIM

ETIM 8.0	EC002637
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

PCB connector - ZEC 1,5/ 9-LPV-5,0 C2



1898334

<https://www.phoenixcontact.com/us/products/1898334>

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2022 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com