# Data sheet

## 2049.2 SKA 5x20

Screw cap

### Business data

| | |
|---|---|
| Article number | 2049.2 |
| Article name | SKA 5x20 |
| GTIN (EAN) | 4044211048556 |
| Packaging unit | 20 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 4.15 g |
| Weight per piece (including packaging) | 4.25 g |
| Unit of weight | G |
| Customs number | 85389099 |
| Country of origin | EU |
| Product description | Screw cap |

# Data sheet

## 2049.2 SKA 5x20

## Technical data

### Further technical data

| | |
|---|---|
| End plate required | ✓ |

### Environmental Product Compliance

| | |
|---|---|
| REACH Conform | yes |
| REACH Reference date | 2022-06-10 |
| REACH Candidate Substance Note | No |
| RoHS Conform | yes |

# Data sheet
## 2049.2 SKA 5x20

### Media

# Data sheet
## 2049.2 SKA 5x20

## Accessories

### ##INVERSE##CONTA-CONNECT



Fused terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm², Width: 12.2 mm, Colour: Black

| Article number | Article name | GTIN (EAN) | Packaging unit |
|---|---|---|---|
| 1004.4 | SK 1/35 24V AC LED(RD) PA-G BK | 4044211129989 | 20 ST |



Fused terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm², Width: 12.2 mm, Colour: Black

| Article number | Article name | GTIN (EAN) | Packaging unit |
|---|---|---|---|
| 1119.4 | SK 1/35 48V AC LED(RD) PA-G BK | 4044211130008 | 20 ST |



Fused terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm², Width: 12.2 mm, Colour: Black

| Article number | Article name | GTIN (EAN) | Packaging unit |
|---|---|---|---|
| 1375.4 | SK 1/35 230V AC G PA-G BK | 4044211129941 | 20 ST |



Fused terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm², Width: 12.2 mm, Colour: Black

| Article number | Article name | GTIN (EAN) | Packaging unit |
|---|---|---|---|
| 1380.4 | SK 1/35 24V DC LED(RD) PA-G BK | 4044211129972 | 20 ST |



Fused terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm², Width: 12.2 mm, Colour: Black

| Article number | Article name | GTIN (EAN) | Packaging unit |
|---|---|---|---|
| 1367.4 | SK 1/35 PA-G BK | 4044211128555 | 20 ST |



Fused terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm², Width: 12.2 mm, Colour: Black

| Article number | Article name | GTIN (EAN) | Packaging unit |
|---|---|---|---|
| 1067.4 | SK 1/35 48V DC LED(RD) PA-G BK | 4044211129996 | 20 ST |

# Data sheet

## 2049.2 SKA 5x20

### ##INVERSE##CONTA-CONNECT



Fused terminal with screw cap for indicator fuses 5x25 mm, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm², Width: 12.2 mm, Colour: Black

| Article number | Article name | GTIN (EAN) | Packaging unit |
|---|---|---|---|
| 1368.4 | SK 1/35 m.K. PA-G BK | 4044211129811 | 20 ST |



Fused terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm², Width: 12.2 mm, Colour: Black

| Article number | Article name | GTIN (EAN) | Packaging unit |
|---|---|---|---|
| 1376.4 | SK 1/35 115V AC G PA-G BK | 4044211129958 | 20 ST |