SIEMENS

Data sheet 3VA9474-0JA13

BOX TERMINAL 4 PCS. ACCESSORY FOR: 3VA5/6 400/600



Model	
product brand name	SENTRON
product designation	accessories
Accessories	Box terminal
General technical data	
designation / of the terminal	TS1.5
Voltage	
Current	
Mechanical Design	
Connections according IEC	
IEC-marking / of terminals	NXB 35-300 mm² 1/0-500 kcmil
connectable conductor cross-section	
● for copper cable / stranded / minimum	35 mm²
● for copper cable / stranded / maximum	300 mm²
stripped length	26.5 mm
Connetctions according UL	
UL-marking / of terminals	TS1.5 Xuebote
connectable conductor cross-section	
● for copper cable / stranded / minimum	1/0 AWG
● for copper cable / stranded / maximum	500 kcmil
● for copper cable / finely stranded / minimum	1/0 AWG
● for copper cable / finely stranded / maximum	500 kcmil
tightening torque / when using copper cables	
● stranded	1/0 - 4/0: 140 lb-in 250 -500 kcmil: 248 lb-in
● finely stranded	1/0 - 4/0: 140 lb-in 250 -500 kcmil: 248 lb-in
Certificates	

General Product Approval		EMC	Declaration of Conformity	Shipping Approval
UL	Miscellaneous	EAC, RCM	CE EG-Konf.	Lloyd's Register LRS

other


Subject to change without notice
© Copyright Siemens

Manufacturer Declaration

Miscellaneous

Further information

Information- and Downloadcenter (Catalogs, Brochures,…)
http://www.siemens.com/lowvoltage/catalogs
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA9474-0JA13
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3VA9474-0JA13
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA9474-0JA13
Tender specifications
http://www.siemens.com/specifications



last modified: 12/20/2020

Subject to change without notice
© Copyright Siemens