



NTS SERIES PRODUCT SPECIFICATION

NTS系列产品规范

				PR: Charles Wan DATE: 2020-03-19	 TE Connectivity Shanghai, China		
C	Update detail of 3.6.22 and rated voltage	L.G	2021-10-22	CHK: Evan Jiang DATE:2020-03-19			
B	Correct typo of approval date	C.W	2020-10-09				
A	Initial Released	C.W	2020-03-19	APP: Ivan Yin DATE:2020-03-19	Document No.: 108-101662	LOC: ES	REV: C
LTR	REVISION RECORD	PR	DATE				

CONTENT

1.	Scope 适用范围	3
1.1	Content 内容.....	3
1.2	Qualification 鉴定	4
2.	APPLICABLE Documents 适用文件	4
2.1	Usable document 使用文件	4
2.2	TE specifications 泰科电子规范	4
2.3	Other specifications 其他规范	4
3.	Requirement 要求	4
3.1	Design and Construction 设计和结构	4
3.2	Material 材料.....	4
3.3	Test parameters and tolerances 测试参数与公差.....	4
3.4	Ratings 等级	4
3.5	General Performance and Test description 通用性能和试验描述.....	4
3.6	TESTS REQUIREMENT AND METHOD SUMMARY 测试要求及方法	5
3.7	Test sequence 试验顺序	6
4.	QUALITY 质量	12
4.1	Qualification test 鉴定	12
4.2	Requalification test 重新鉴定.....	12
4.3	Acceptance 验收	12
4.4	Quality conformance inspection 质量合格检验.....	12

1. SCOPE 适用范围

1.1. Content 内容

This specification covers performance, tests and quality requirements for the TE Connectivity (TE) NTS Series Connector System. The product described in this document has not been fully tested to ensure conformance to the requirements outlined herein. TE Connectivity makes no representation or warranty, express or implied that the product will comply with these requirements. Further, TE Connectivity reserves the right these requirements based on the results of additional testing and evaluation. Contact TE Connectivity Engineering for further information. If necessary, This document will become the Product Specification at successful completion of testing. 本规范适用于NTS 系列产品(以下简称NTS series) 的性能, 测试和质量要求。

a. 本规范适用但不仅限于以下零件号: X =1, 2, 3, 4 refers to A,B,C,D keys.

2350890-X 1-2350890-X	NTS 20Pos.plugin housing assembly
2350891-X	NTS 20Pos. tab housing assembly, Inline version
1-2350891-X 2-2350891-X	NTS 20Pos. tab housing assembly, flange version
2350943-1 2350943-2	NTS 20Pos. fix ring
2366494-X 1-2366494-X	NTS 48Pos. plug housing assembly
2366509-X	NTS 48Pos. tab housing assembly, Inline
1-2366509-X 2-2366509-X	NTS 48Pos. tab housing assembly, Flange
2366517-X	NTS 48Pos. fix ring

b. Backshells are sold separately.

1.2. Qualification 鉴定

When tests are performed, the following specifications and standards shall be used. All inspections shall be performed using the applicable inspection plan and product drawing.

本测试规范依照下面的规范及标准执行。所有的检验应依照合适的检验计划及产品图纸执行。

2. APPLICABLE DOCUMENTS 适用文件

2.1. Usable document 使用文件

In the event of conflict between the requirements of this specification and the drawing, the drawing shall take precedent.

在本规范的要求与图纸发生冲突时，以产品图纸为准。在本规范的要求与参考文件发生冲突时，以本规范为准。

2.2. TE specifications 泰科电子规范

- 109-1: General Requirements for Testing
- 0425-021-0000: HDP20 Series Performance and Application Characteristics
- 114-151001: Application Specification for DEUTSCH Size 16 S&F Pin & Socket
- 114-151003: Application Specification for DEUTSCH Size 20 S&F Pin & Socket
- 408-151008: Instruction Guide DEUTSCH Removal Tool DT-RT1

2.3. Other specifications 其他规范

- SAE J2030: Heavy-Duty Electrical Connector Performance Standard
- SAE J1455: Recommended Environmental Practices for Electronic Equipment Design in Heavy-Duty Vehicle Applications
- DIN 40050-9: Road Vehicles Degrees of protection (IP Code)
- EIA-364: Electrical Connector/Socket Test Procedures Including Environmental Classifications
- IEC-60529: Degrees of Protection Provided by Enclosures (IP Code)
- SAE J1128: Low Voltage Primary Cable
- USCAR-2 REVISION 6

3. REQUIREMENT 要求

3.1. Design and Construction 设计和结构

Products must meet the design, construction and physical dimensions specified in the applicable product drawings.

产品必须满足产品图纸上的设计，结构和尺寸要求。

3.2. Material 材料

Description of the material sees the related product drawings.

材料描述见相关产品图纸。

3.3. Test parameters and tolerances 测试参数与公差

Table 1: Test parameters and tolerances

Requirement 要求	Tolerance 公差
Ambient temperature 环境温度	23°C ± 5°C
Relative humidity 相对湿度	45% to 75%
Atmospheric pressure 大气压力	96kPa ± 10kPa

3.4. Ratings 等级

A. Operating Temperature / 工作温度: -40~125°C

B. Rated voltage / 额定工作电压: 24 V

C. Application / 产品应用: Under hood 发动机舱

D. Current (A): See Table 1

Table 1		
Connector Loading	Wire Size AWG [mm ²]	
	16 [1.0]	20 [.50]
All Circuits Energized	13.0	7.5

E. Ingress Protection (IP) Level: IPX8 and IPX9K (with rear protection, such as backshell)

3.5. General Performance and Test description 通用性能和试验描述

The product is designed to meet the electrical, mechanical and environmental performance requirements specified in Para.4. All testes must be performed at the test condition of the TE test specification 109-1 unless otherwise specified.

产品应能满足段落4中的电气，机械和环境等性能要求。所有试验均需按照TE规范109-1中的测试条件进行，除非另有说明。

3.6. Test Requirements and Procedures Summary 测试要求及方法

Unless otherwise specified, all tests shall be performed at ambient environmental conditions.

Table 2

Test Description	Requirement	Procedure
3.6.1 Examination of Product	Meets requirements of product drawing. The connectors shall be correctly constructed, marked, and show good quality and workmanship.	SAE J2030 6.1 Visual inspection of product before and after unmating connectors for conditions such as torn seals, cracked plastic, evidence of fluid or dust ingress in sealed connector systems, arcing, charring, melting, or anything that affects the performance or serviceability of the product as deemed by a qualified engineer.
ELECTRICAL		
3.6.2 Low Level Contact Resistance	Acceptance criteria Initial Maximum resistance: 16# terminal: 6 mΩ 20# terminal: 10 mΩ Final Maximum resistance 16# terminal: 10 mΩ 20# terminal: 16 mΩ	SAE J2030 6.2 Test with applied voltage not exceeding 20 mV open circuit and the test current shall be limited to 100 mA. The resistance of a cable equal in length to that of the two measuring points shall be subtracted from the measured values. The cable used shall be from the same batch of cable as used for the connector wiring. Measurements shall be taken after thermal equilibrium at current levels.
3.6.3 Insulation Resistance	The insulation resistance shall be greater than 20 MΩ.	SAE J2030 6.3 Using a 1000 VDC insulation resistance test measurement device or equivalent, check insulation resistance between each contact to each adjacent contact or housing edge.
MECHANICAL		
3.6.4 Connector Retention	The connector shall remain coupled after the specified pulling force is applied. There shall be no evidence of cracking, distortion, or detrimental damage to the connector following the test.	USCAR 5.4.2 Samples should be tested with connector primary locking mechanism (without CPA) fully engaged. Retention force must be >110 Newtons, the load shall be applied for 30s.
3.6.5 Drop Test	There shall be no evidence of cracking, distortion or detrimental damage to the connector following the test. Small chips and dents that do not adversely affect the connector shall be disregarded.	SAE J2030 6.17 The free end of the cord or cable, which shall be 1500 mm ± 25 mm long, shall be fixed to a wall at a height of 750 mm ± 25 mm above a concrete floor. The specimen shall be held so that the cord or cable is horizontal and allowed to fall to a concrete floor eight times. Wire the sample (unmated connector) according to its application (TPA on position). Rotate the specimens through approximately 45 degrees at its fixing each time.
3.6.6 Durability	No evidence of damage to the contacts, contact plating, connector housing, or seals which may be detrimental to reliable connector performance.	SAE J2030 6.11 The connector shall be mated and unmated for a total of 20 complete cycles at room temperature.

Table 2

Test Description	Requirement	Procedure											
3.6.7 Maintenance Aging	Shall meet visual requirements and show no physical damage.	SAE J2030 6.6 with a deviation using 5 cycles Subject at least 10% of the cavities to 5 cycles of inserting and removing its respective contact. The five cycles shall also include any disassembly required to remove the contacts. The connectors shall be mated and unmated during each cycle. Insertion and removal shall be performed using manufacturer's recommended practice.											
3.6.8 Mating / Unmating Forces	Required force to mate the plug and receptacle pair and engage latching mechanism shall not exceed 135 N. Required force to separate the plug and receptacle pair and fully disengage latching mechanism shall not exceed 135 N.	SAE J2030 6.9 and 6.10 For connectors without mechanical assist, test the maximum required force to mate the plug and receptacle pair and engage the latching mechanism. The force is not to exceed 135 N. For connectors without mechanical assist, test the maximum force required to separate the plug and receptacle with the latch mechanism fully disengaged. The force is not to exceed 135 N.											
3.6.9 Mismatching	Polarization and different keys shall resist a minimum of 178 N axial force without damage.	SAE J2030 6.21 Connectors with two or more contacts shall be keyed or of such a design that any intended polarization is not defeated by improper assembly during installation.											
3.6.10 Shock	No discontinuity in excess of 1.0 microsecond at 100 mA during the last hour of each axis. Shall meet visual requirements, show no physical damage, and meet requirements of additional tests as needed.	SAE J2030 6.16 10 cycles of 1/2 sine pulses, 50 g, 11 millisecond duration X, Y, and Z axis are to be tested. Monitor for discontinuity greater than 10 Ω in excess of 1.0 microsecond at 100 mA. Connector under test to be fixed to the shock plane with the wire harness fixed to non-shocked objects no closer than 100 mm and not farther than 300 mm from the rear of the connector.											
3.6.11 Terminal – Connector insertion force	Insertion: 1. Inserting force: 30N max. 2. The forward stop push-through force $F \geq 50N$	USCAR-2 5.4.1 Terminal –Connector insertion											
3.6.12 Terminal Retention in Connector	The terminal shall maintain its original position in the connector throughout the test. The terminals shall withstand the minimum force specified. <table border="1"> <thead> <tr> <th rowspan="2">Contact Size</th><th colspan="2">Minimum Pull Out Force(N)</th></tr> <tr> <th>utilize 2nd lock</th><th>no 2nd lock*</th></tr> </thead> <tbody> <tr> <td>16</td><td>111</td><td>80</td></tr> <tr> <td>20</td><td>89</td><td>65</td></tr> </tbody> </table>	Contact Size	Minimum Pull Out Force(N)		utilize 2nd lock	no 2nd lock*	16	111	80	20	89	65	SAE J2030 6.18 with a deviation using The contacts shall be subjected to a direct pull. The minimum value shall be applied for 15s. The pull is to be exerted on the conductor by means of a tension-testing machine or equivalent to prevent sudden or jerking force during test. NOTE: Secondary-locking devices should be utilized if available.
Contact Size	Minimum Pull Out Force(N)												
	utilize 2nd lock	no 2nd lock*											
16	111	80											
20	89	65											

Table 2

Test Description	Requirement	Procedure																														
3.6.13 Terminal pull force	Pull force after temperature /Humidity cycling <table><tr><th>Contact Size</th><th>Minimum Pull Out Force</th></tr><tr><td></td><td>N</td></tr><tr><td>16</td><td>80</td></tr><tr><td>20</td><td>65</td></tr></table>	Contact Size	Minimum Pull Out Force		N	16	80	20	65	Adjust the force tester to pull the terminal straight back from the connector. Straight back force is critical to avoid side loads and binding which can affect force measurements. Increase the pullout force at a uniform rate not to exceed 50mm/min, until pullout occurs.																						
Contact Size	Minimum Pull Out Force																															
	N																															
16	80																															
20	65																															
3.6.14 Vibration	There shall be no discontinuity in excess of 1.0 microsecond at 20 mV and 100 mA during the last hour of each axis. Shall meet visual requirements, show no physical damage, and meet requirements of additional tests as needed.	J2030 6.15 Connectors under test shall be fixed to the vibrating plane with the wire harness fixed to non-vibrating objects no closer than 10 cm [4 in.] and not farther than 30 cm [12 in.] from the rear of the connector. <table><tr><th>Parameter</th><th>Requirement</th></tr><tr><td>Sine Sweep</td><td>10 to 2000 Hz</td></tr><tr><td>Initial Displacement</td><td>0.07 in [1.78 mm] DA</td></tr><tr><td>Maximum Acceleration</td><td>20 G's</td></tr><tr><td>Test Duration</td><td>24 hours</td></tr><tr><td>Time Per Axis X, Y, Z</td><td>8 hours</td></tr><tr><td>Test Current (first 3 hours each axis)</td><td>See Following Table</td></tr><tr><td>Monitor for Discontinuity (last hour each axis)</td><td>-</td></tr></table> Test Currents <table><tr><th>Contact Size</th><th>Wire Gauge AWG [mm²]</th><th>Test Current (Amps)</th></tr><tr><td rowspan="3">16</td><td>16 [1.5-1.0]</td><td>10.0</td></tr><tr><td>18[0.75]</td><td>8.0</td></tr><tr><td>20[0.5]</td><td>5.0</td></tr><tr><td rowspan="2">20</td><td>16 [1.5-1.0]</td><td rowspan="2">5.0</td></tr><tr><td>20 [0.50]</td></tr></table>	Parameter	Requirement	Sine Sweep	10 to 2000 Hz	Initial Displacement	0.07 in [1.78 mm] DA	Maximum Acceleration	20 G's	Test Duration	24 hours	Time Per Axis X, Y, Z	8 hours	Test Current (first 3 hours each axis)	See Following Table	Monitor for Discontinuity (last hour each axis)	-	Contact Size	Wire Gauge AWG [mm²]	Test Current (Amps)	16	16 [1.5-1.0]	10.0	18[0.75]	8.0	20[0.5]	5.0	20	16 [1.5-1.0]	5.0	20 [0.50]
Parameter	Requirement																															
Sine Sweep	10 to 2000 Hz																															
Initial Displacement	0.07 in [1.78 mm] DA																															
Maximum Acceleration	20 G's																															
Test Duration	24 hours																															
Time Per Axis X, Y, Z	8 hours																															
Test Current (first 3 hours each axis)	See Following Table																															
Monitor for Discontinuity (last hour each axis)	-																															
Contact Size	Wire Gauge AWG [mm²]	Test Current (Amps)																														
16	16 [1.5-1.0]	10.0																														
	18[0.75]	8.0																														
	20[0.5]	5.0																														
20	16 [1.5-1.0]	5.0																														
	20 [0.50]																															
ENVIRONMENTAL																																
3.6.15 Fluid Immersion	There shall be no evidence of cracking, distortion, or detrimental damage to the connector following the test.	J2030 6.14 Subject each sample group to one fluid only. The wired mated connectors shall be submerged in the fluids below at the temperatures listed. Each connector shall be submerged for five minutes, then removed from the fluid to air dry for 24 hours. This cycle is to be completed a total of five cycles. <table><tr><th>Fluid</th><th>Temperature ±3°C</th></tr><tr><td>Motor Oil 30 weight</td><td>+60</td></tr><tr><td>Brake Fluid (disc type 1)</td><td>+60</td></tr><tr><td>50/50 Antifreeze/Water mixture</td><td>+60</td></tr><tr><td>Transmission Oil 90 weight</td><td>+60</td></tr></table>	Fluid	Temperature ±3°C	Motor Oil 30 weight	+60	Brake Fluid (disc type 1)	+60	50/50 Antifreeze/Water mixture	+60	Transmission Oil 90 weight	+60																				
Fluid	Temperature ±3°C																															
Motor Oil 30 weight	+60																															
Brake Fluid (disc type 1)	+60																															
50/50 Antifreeze/Water mixture	+60																															
Transmission Oil 90 weight	+60																															

Table 2

Test Description	Requirement	Procedure
3.6.16 Pressure Spray	There shall be no evidence of water ingress into the connector housing.	USCAR-2 5.6.7 IPX9K The test specifies a spray nozzle that is fed with 80°C water at 80 to 100 bar and a flow rate of 14 to 16 L/min. The nozzle is held 10 to 15 cm from the tested device at angles of 0°, 30°, 60° and 90° for 30 s each. The test device sits on a turntable that rotates.
3.6.17 Pressure/Vacuum Leak	No evidence of water or florescent dye shall be present in the interior of either mated connector	USCAR-2 5.6.6 Pressure/Vacuum Leak air pressure or vacuum 15 seconds Initial:48 kPa Final: 28Kpa
3.6.18 Temperature Life	There shall be no evidence of cracking, distortion, or detrimental damage.	SAE J2030 6.7 The cabled-mated connectors shall be subject to 1000 h at 125 ± 3 °C without current flowing.
3.6.19 Temperature humidity Cycling	No defect, crack, could not affect their fit and function	USCAR-2 5.6.2 Temperature humidity Cycling 40Cycle
3.6.20 Thermal Shock 1	Shall show no evidence of cracking, chipping, or other damage detrimental to the normal operation of the connector.	SAE J2030 6.13 with deviation The cabled-mated connector shall be subjected to 10 cycles of thermal shock. One cycle shall consist of a soak time at -40 °C ambient, then a transition within 2 min to an ambient of 125 °C, with a soak time there and then a transition back to -40 °C ambient within 2 min. The soak times shall be established as the time necessary to bring the internal connector temperature on test to within 5 °C of each of the ambient temperatures.
3.6.21 Thermal Shock 2	No defect, crack, could not affect their fit and function	USCAR-2 5.6.1 Thermal Shock Class 3(-40°C to + 125°C), 99Cycle

Table 2

Test Description	Requirement	Procedure
3.6.22 Water Immersion	Test samples must meet insulation resistance test requirements.	SAE J2030, 6.19 with deviation IPX8 The wired mated connectors shall be placed in an oven at 125 °C ± 3 °C for 1 h then remove and allow recover to room temperature, then place the samples in water with a 5% salt in weight content and 0.1 g/L wetting agent, to a depth of 1 m for 4 hours. Water temperature is to be 23 °C ± 3 °C. Test samples for insulation resistance per SAE J2030 6.3 and visually inspect for moisture inside the connector. The ends of the cable are to be sealed during this test.
3.6.23 IPX8 enhance	No evidence of water or florescent dye shall be present in the interior of either mated connector	Immerse samples in 2m depth,48Hours
3.6.24 Submersion	No evidence of water or florescent dye shall be present in the interior of either mated connector	USCAR-2 5.6.5 Submersion 125°C chamber 2H, 0°C salt water 30 Minute
3.6.25 Visual Examination	No evidence of damage to the contacts, contact plating, connector housing, or seals which may be detrimental to reliable connector performance.	SAE J2030 6.27 Conduct a visual examination for identification of product such as torn seals, cracked plastic, evidence of fluid or dust ingress in sealed connector systems, arcing, charring, melting, or anything that could affect the performance and serviceability of the product.

3.7. Product Qualification and Requalification Test Sequence 试验顺序

Test samples were subjected to the following tests in the order given. Each test group had five mated pair test samples.

Test or Examination	Test Group (a)										
	1	2	3	4	5	6	7	8	9	10	11
	Test Sequence (b)										
Examination of Product	1	1	1	1	1	1	1	1	1	1	1
Terminal –Connector insertion force											2
Fluid Immersion					2						
Maintenance Aging			2								
Pressure/Vacuum Leak						2,5			4,10	4,10	
Water Immersion				2,5							
Insulation Resistance				3,6		3			5,8,11	5,8,11	
Low Level Contact Resistance		2,4,6,8							3,9	3,9	
Thermal Shock 1		3	3								
Thermal Shock 2										6	
Temperature humidity Cycling									6		
Temperature Life	2			4		4					
Vibration		5									
Mating / Unmating Forces			4,6								
Shock		7									
Submersion									12	12	
Pressure Spray						6			13	13	
Durability			5						2	2	
IPX8 enhance								2			
Terminal Retention in Connector			7								4*
Connector Retention	3										
Drop Test							2				
Mismating			8								
Terminal pull force									14		
Visual Examination	4	9	9	7	3	7	3	3	7	7	3

4. QUALITY 质量

4.1. Qualification test 鉴定

Samples must be in accordance with drawings and be taken in a random way in the production in progress.

样件必须与产品图纸一致，并且是生产过程中随机选取的。

4.2. Requalification test 重新鉴定

If changes significantly affecting form, fit, or function are made to the product or to the manufacturing process, product assurance shall coordinate requalification testing, consisting of all or part of the original testing sequence as determined by product engineering.

如果产品或者制造过程中有显著影响外观，装配和功能的设变，质保需要协调按照原先工程部定义的测试顺序，重新验证全部或者部分测试项目。

4.3. Acceptance 验收

Acceptance is based on verification that the product meets the requirements of section 3.6. Failures attributed to equipment, test setup, or operator deficiencies shall not disqualify the product. When product failure occurs, corrective action shall be taken and samples resubmitted for qualification. Testing to confirm corrective action is required before resubmitted.

归咎于测试设备，样件安装或者操作员的失误的失效不应判定产品不合格。当产品失效发生时，需要有纠正措施以及重新提交样件进行验证。在重新验证前，需确认已有纠正措施。

4.4. Quality conformance inspection 质量合格检验

The applicable TE Connectivity quality inspection plan will specify the sampling acceptable quality level to be used. Dimensional and functional requirements shall be in accordance with the applicable product drawing and this specification

TE Connectivity 的质量检验计划将指定适用的质量标准。尺寸和功能要求，应按照适用的产品图纸和本规范。