
Data sheet

2762.2 AP 10 BG



End plate, Width: 2 mm, Colour: Beige

Business data

Article number	2762.2
Article name	AP 10 BG
GTIN (EAN)	4044211054922
Packaging unit	20
Quantity unit	PC
Weight per piece (not including packaging)	2.85 g
Weight per piece (including packaging)	2.9 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Prio-Article	2762.2
Product description	End plate

Data sheet
2762.2 AP 10 BG

Technical data

Dimensions

Length	60.49 mm
Width	2 mm
Min. thickness	2 mm
Height	33.8 mm

Materials

Material	Polyamide 6.6
Flammability class UL 94	V-2
Working temperature, min.	-40 °C
Working temperature, max.	105 °C

Further technical data

Designed as end plate	✓
Snap-on available	✓

Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2022-01-07, 2022-06-10
REACH Candidate Substance Note	No
RoHS Conform	yes


Data sheet
2762.2 AP 10 BG

Media

Data sheet
2762.2 AP 10 BG


Accessories

##INVERSE##CONTA-CONNECT




Fuse-disconnect terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1104.2	SIK 10/LED(RD)/20-30V DC/40-60V AC BG	4044211016753	25 ST




Fuse-disconnect terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1103.2	SIK 10/LED(RD)/12V DC/24V AC BG	4044211016548	25 ST




Fuse-disconnect terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1105.2	SIK 10/LED(RD)/40-60V DC/80-120V AC BG	4044211016906	25 ST




Fuse-disconnect terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1107.2	SIK 10/2 LED´s(RD)/24V DC BG	4044211016920	25 ST



Fuse-disconnect terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1106.2	SIK 10/LED(RD)/115V DC/230V AC BG	4044211016913	25




Fused terminal with disconnect plug, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17042.2	SIK 10/ST BG	4044211155797	25

Data sheet
2762.2 AP 10 BG

##INVERSE##CONTA-CONNECT




Fuse-disconnect terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1101.2	SIK 10 BG	4044211016388	50



Fused terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
17364.4	SIK 10 PA-G BK	4044211178406	50 ST



Fused terminal with disconnect plug, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17044.2	SIK 10/ST/5x20 BG	4044211155827	25 ST