# Data sheet

## 3073.0 QKS G 6



Crimp lug, Fork shape acc. to DIN 46237/C, Max. wire cross-section: 6 mm², Colour: Yellow

**RAL:** 1026

## Business data

| | |
|---|---|
| Article number | 3073.0 |
| Article name | QKS G 6 |
| GTIN (EAN) | 4044211057787 |
| Colour | Yellow |
| Connector shape | Fork shape acc. to DIN 46237/C |
| Product-compliant (according to DIN) | yes |
| Packaging unit | 100 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 2.71 g |
| Weight per piece (including packaging) | 2.72 g |
| Unit of weight | G |
| Customs number | 85369010 |
| Country of origin | TW |
| Product description | Crimp |

# Data sheet

## 3073.0 QKS G 6

## Technical data

### Dimensions

| | |
|---|---|
| Length (input to end of inner fork ring) | 26 mm |
| Outer width of fork | 14 mm |
| Inner width of fork | 8.4 mm |
| Diameter of feed-in funnel | 26 mm |
| Size DIN | C 8 - 6 |

### Connection data

| | |
|---|---|
| Wire cross-section, min. | 4 mm² |
| Wire cross-section, max. | 6 mm² |
| Wire cross-section AWG, min. | 12 |
| Wire cross-section AWG, max. | 10 |

### Materials

| | |
|---|---|
| Connector material | Copper |
| Surface | Tin-plated |
| insul. | Expanded PA insulation |
| Working temperature, min. | -55 °C |
| Working temperature, max. | 105 °C |

### Further technical data

| | |
|---|---|
| Insulation available | ✓ |
| Soldered | ✓ |

### Environmental Product Compliance

| | |
|---|---|
| REACH Conform | yes |
| REACH Reference date | 2022-06-10 |
| REACH Candidate Substance Note | No |
| RoHS Conform | yes |

# Data sheet
## 3073.0 QKS G 6

## Approvals

### Standards and regulations

| | |
|---|---|
| Standards / specifications | DIN EN 13599 |

# Data sheet
## 3073.0 QKS G 6

## Media

# Data sheet
## 3073.0 QKS G 6

### Accessories