
SHEET 1 OF 1




PANEL CUTOUT


PANEL THICKNESS	X
0.75 - 1.25	19.2
1.25 - 2.00	19.4
2.00 - 3.00	19.6




CIRCUIT: SPST

SWITCH FUNCTION	
POS. 1	POS. 2
OFF	ON
OPEN	1-1a







NOTE:
1. DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X = ± 0.4
   X.XX = ± 0.25
3. TERMINAL NUMBERS FOR REF ONLY
4. CONTACT MATERIAL: SILVER
▲5. CONTACT RATINGS:
   ANSI/UL 1054 AND CAN/CSA C22.2 NO. 55 (E194579):
   16A @ 125VAC [UR, cUR]
   10A @ 250VAC [UR, cUR]
   1/3HP 125/250VAC [UR, cUR]
6. CONTACT RESISTANCE: 35mΩ MAX. @ 50VAC
7. INSULATION RESISTANCE: 100MΩ MIN. @ 500VAC
8. DIELECTRIC STRENGTH: 1,500VAC FOR 1 MINUTE
9. ELECTRICAL LIFE: 6,000 CYCLES [UR, cUR]
10. OPERATING TEMPERATURE: -20°C TO 105°C [UR, cUR]
11. ▲ DENOTES CRITICAL PARAMETER

REV	ECO NO	DESCRIPTION	DATE	BY
C	ECO-100449	REMOVE VDE/ENEC RATING AND LOGO	01/10/22	JS

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

E-SWITCH®

OBJECT ID 000001390

TITLE RA111C1900

SCALE	DATE	DR	DWG	REV
2:1	8/12/2014	EBP	38-RA111C1900	C