

SHEET 1 OF 1




PANEL CUTOUT

PANEL THICKNESS	(X) DIMENSION
0.75 - 1.25	19.2
1.25 - 2.00	19.4
2.00 - 3.00	19.6







SWITCH FUNCTION	
POS. 1	POS. 2
	
OFF	ON
OPEN	1-1a



CIRCUIT: SPST





NOTE:
1. DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X = ± 0.4
   X.XX = ± 0.25
3. TERMINAL NUMBERS FOR REF ONLY
4. CONTACT MATERIAL: SILVER
▲5. CONTACT RATINGS: UR, cUR
   10A @ 125VAC / 250VAC
6. CONTACT RESISTANCE: 35mΩ MAX. @ 50VAC
7. INSULATION RESISTANCE: 100MΩ MIN. @ 500VAC
8. DIELECTRIC STRENGTH: 1,500VAC FOR 1 MINUTE
9. ▲ DENOTES CRITICAL PARAMETER

REV	ECO NO	DESCRIPTION	DATE	BY
B	ECO-100450	REMOVE VDE/ENEC RATING AND LOGO	01/10/22	JS

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

E-SWITCH®

OBJECT ID 000001403

TITLE RA1213112R

SCALE	DATE	DR	DWG	REV
2:1	4/7/2015	MW	38-RA1213112R	B