SIEMENS

Data sheet 6AV6671-5CL00-0AX1

Main battery Mobile Panel IWLAN, rechargeable. Further information, Quantity and content: See technical data



Figure similar

General information	
Product type designation	Main battery Mobile Panel IWLAN
Installation type/mounting	
Wall mounting/direct mounting	Yes; in HMI devices, battery compartment
Supply voltage	
Type of supply voltage	DC
Rated value (DC)	7.2 V
Accumulator	
Charge status display	No
Rechargeable	Yes
Capacity	5.1 A·h
Lithium-ion	Yes; ICR18650-26J
Special design	Yes; bent
Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes
cULus	Yes
KC approval	No; unnecessary
EAC (formerly Gost-R)	No
CCC	No
RoHS conformity	Yes
Ambient conditions	
Ambient temperature during operation	
● min.	0 °C; Don't charge below
● max.	45 °C
Ambient temperature during storage/transportation	
● min.	-20 °C; Shelf life at room temperature is 10 years with a capacity loss of 1 % per year
● max.	30 °C; Shelf life at room temperature is 10 years with a capacity loss of 1 % per year
Relative humidity	
● Operation, max.	90 %
Mechanics/material	
Material	
● Plastic	Yes; Enclosure, black
Dimensions	

Subject to change without notice
© Copyright Siemens

Width	75 mm
Height	78 mm
Thickness	33 mm
Weights	
Weight without packaging	320 g
Scope of supply	
Delivery quantity in pieces	1; with ejector
Other	
Merchandise	No
Manufacturer name	BMZ GmbH
Manufacturer's address	Auf dem Stützelberg, 35745 Herborn, Germany
Target devices	for Mobile Panel 277 IWLAN, Mobile Panel 277F IWLAN, Mobile Panel 277 IWLAN V2, Mobile Panel 277F IWLAN V2, Mobile Panel 277F IWLAN (RFID tag)
Note:	Dispose of battery (lithium) properly; hazardous product!

last modified: 12/16/2020

Subject to change without notice
© Copyright Siemens