

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

5011939000

Status:

Active

Overview:

Pico-Clasp Wire-to-Board Connectors

Description:

1.00mm Pitch, Pico-Clasp Female Crimp Terminal, Gold Plating 0.76µm, 28-32 AWG, Reel



Series image - Reference only

Documents:

3D Model	Product Specification 5019390000-PS-001 (PDF)
Drawing (PDF)	Product Specification 5019390000-PS-003 (PDF)
3D Model (PDF)	Product Specification 5019391000-PS-001 (PDF)
Product Specification 5011890000-PS-001 (PDF)	Product Specification 5019391000-PS-003 (PDF)
Product Specification 5011890000-PS-002 (PDF)	Product Specification 5019391000-PS-CHI-001 (PDF)
Product Specification 5011891000-PS-001 (PDF)	Product Specification 5019391000-PS-JAP-001 (PDF)
Product Specification 5011891000-PS-002 (PDF)	Application Specification 5011890000-AS-000 (PDF)
Product Specification 5011891000-PS-JAP-001 (PDF)	Application Specification 5011890000-AS-001 (PDF)
Product Specification 5013300000-PS-002 (PDF)	Application Specification 5013300000-AS-000 (PDF)
Product Specification 5013300000-PS-004 (PDF)	Application Specification 5013300000-AS-001 (PDF)
Product Specification 5013301000-PS-002 (PDF)	Packaging Specification SPK-501193-001-001 (PDF)
Product Specification 5013301000-PS-004 (PDF)	Datasheet (PDF)
Product Specification 5013301000-PS-JAP-002 (PDF)	RoHS Certificate of Compliance (PDF)

General

Product Family	Crimp Terminals
Series	501193
Application	Signal, Wire-to-Board, Wire-to-Wire
Crimp Quality Equipment	Yes
Overview	Pico-Clasp Wire-to-Board Connectors
Product Name	Pico-Clasp
Taxonomy	Crimp Terminals
UPC	193264224258

Physical

Durability (mating cycles max)	30
Gender	Female
Material - Metal	Phosphor Bronze
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Net Weight	22.089/mg
Packaging Type	Reel
Plating min - Mating	0.760µm
Plating min - Termination	0.914µm
Termination Interface: Style	Crimp or Compression
Wire Insulation Diameter	0.80mm max.
Wire Size AWG	28, 30, 32
Wire Size mm²	N/A

Electrical

Current - Maximum per Contact	2.0A
Voltage - Maximum	100V AC (RMS)/DC

Material Info

Reference - Drawing Numbers

Application Specification	5011890000-AS-000, 5011890000-AS-001, 5013300000-AS-000, 5013300000-AS-001
Application Tooling Documents	5780163700ATP-E-000, 5780163700ATP-J-000, 5780163700ATS-000, 5780163700ATS-J-000, ATP-578016-6000E-001, ATP-578016-6000JE-001

EU ELV

Compliant

EU RoHS

Compliant

REACH SVHC

Not Contained Per -
D(2022)4187-DC (10
June 2022)

Halogen-Free

Status

Low-Halogen

For more information, please visit [Contact US](#)

China RoHS

China ROHS	Green Image
ELV	Compliant
RoHS Phthalates	Not Contained

Search Parts in this Series

501193 Series

Use With

Receptacle Housing [501189](#) , [501330](#) , [501939](#)

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description	Product #
Extraction Tool for Pico-Clasp Wire-to-Board Terminals, 28-32 AWG	638131700
Hand Crimp Tool for 1.00mm Wire-to-Board Crimp Terminal, 28-32 AWG Wire	638191500

Crimp Specification
Packaging Specification
Product Specification

Sales Drawing

CS-501193-001-001
SPK-501193-001-001
5011890000-PS-001, 5011890000-PS-002,
5011891000-PS-001, 5011891000-PS-002,
5011891000-PS-JAP-001, 5013300000-PS-002,
5013300000-PS-004, 5013301000-PS-002,
5013301000-PS-004, 5013301000-PS-JAP-002,
5019390000-PS-001, 5019390000-PS-003,
5019391000-PS-001, 5019391000-PS-003,
5019391000-PS-CHI-001, 5019391000-PS-JAP-001
5011930000-SD-000

FineAdjust Applicator for 1.00mm Pitch Wire-to-Board Crimp Terminal	
T2 Terminator Die for 1.00mm Pitch Wire-to-Board Crimp Terminal	
Japan	
Description	Product #
S-1 Applicator for Pico-Clasp Receptacle Terminals, 28-32 AWG	639019400
	639119400
	5780163700

This document was generated on 09/29/2022

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION