SIEMENS

Data sheet 6GK5213-3BB00-2AB2

product description	Preset for PROFINET mode!
	SCALANCE XB213-3 managed Layer 2 IE Switch 13x IEC 62443-4-2 certified; 10/100 Mbps RJ45 ports, 3x MM FO ST port 1x console port, diagnostics LED, redundant power supply, temp. range 0 °C to +60 °C; attachment to DIN rail; default PROFINET



product type designation	**SCALANCE XB213-3**
transfer rate	
transfer rate	10 Mbit/s, 100 Mbit/s
interfaces / for communication / integrated	
number of electrical connections	
● for network components or terminal equipment	13; RJ45
number of 100 Mbit/s ST(BFOC) ports	
● for multimode	3
interfaces / other	
number of electrical connections	
● for operator console	1
● for management purposes	1
● for power supply	1
type of electrical connection	
● for operator console	RJ11
● for management purposes	RJ45
● for power supply	6-pole terminal block
supply voltage, current consumption, power loss	
product component / connection for redundant voltage supply	Yes
type of voltage / 1 / of the supply voltage	DC
● supply voltage / 1 / rated value	24 V
● power loss [W] / 1 / rated value	9.8 W
● supply voltage / 1 / rated value	19.2 ... 28.8 V
● consumed current / 1 / maximum	0.41 A
● type of electrical connection / 1 / for power supply	6-pole terminal block
● product component / 1 / fusing at power supply input	Yes
ambient conditions	
ambient temperature	
● during operation	0 ... 60 °C
● during storage	-40 ... +70 °C
● during transport	-40 ... +70 °C
relative humidity	
● at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP20

Subject to change without notice
© Copyright Siemens

design, dimensions and weights	
design	Box
width	120 mm
height	117 mm
depth	109 mm
net weight	0.5 kg
material / of the enclosure	Plastic
fastening method	
● 35 mm top hat DIN rail mounting	Yes
● wall mounting	No
● S7-300 rail mounting	No
● S7-1500 rail mounting	No
product features, product functions, product components / general	
cascading in the case of a redundant ring / at reconfiguration time of <\~0.3\~s	50
cascading in cases of star topology	any (depending only on signal propagation time)
product functions / management, configuration, engineering	
product function	
● CLI	Yes
● web-based management	Yes
● MIB support	Yes
● TRAPs via email	Yes
● configuration with STEP 7	Yes
● RMON	Yes
● port mirroring	Yes
● multiport mirroring	No
● CoS	Yes
● with IRT / PROFINET IO switch	No
● PROFINET IO diagnosis	Yes
PROFINET conformity class	B
product function / switch-managed	Yes
telegram length / for Ethernet / maximum	1522 byte
protocol / is supported	
● Telnet	Yes
● HTTP	Yes
● HTTPS	Yes
● TFTP	Yes
● FTP	Yes
● BOOTP	No
● DCP	Yes
● LLDP	Yes
● EtherNet/IP	Yes
● SNMP v1	Yes
● SNMP v2	Yes
● SNMP v3	Yes
● IGMP (snooping/querier)	Yes
identification & maintenance function	
● I&M0 - device-specific information	Yes
● I&M1 – higher level designation/location designation	Yes
product functions / diagnostics	
product function	
● port diagnostics	Yes
● statistics Packet Size	Yes
● statistics packet type	Yes
● error statistics	Yes
● SysLog	Yes
● loopback diagnostics	Yes
product functions / VLAN	

Subject to change without notice
© Copyright Siemens

product function	
● VLAN - port based	Yes
● VLAN - protocol-based	No
● VLAN - IP-based	No
● VLAN dynamic	No
product functions / DHCP	
product function	
● DHCP client	Yes
product functions / redundancy	
product function	
● ring redundancy	Yes
● High Speed Redundancy Protocol (HRP)	Yes
● high speed redundancy protocol (HRP) with redundancy manager	Yes
● high speed redundancy protocol (HRP) with standby redundancy	Yes
protocol / is supported / Media Redundancy Protocol (MRP)	Yes
product function	
● media redundancy protocol (MRP) with redundancy manager	Yes
● redundancy procedure STP	Yes
● redundancy procedure RSTP	Yes
● redundancy procedure RSTP+	Yes
● redundancy procedure MSTP	No
● Parallel Redundancy Protocol (PRP)/operation in the PRP-network	Yes
● Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)	No
● passive listening	Yes
product functions / security	
product function	
● IEEE 802.1x (radius)	Yes
● broadcast/multicast/unicast limiter	Yes
● broadcast blocking	Yes
protocol / is supported	
● SSH	Yes
product functions / time	
product function	
● SICLOCK support	Yes
protocol / is supported	
● NTP	Yes
● SNTP	Yes
standards, specifications, approvals	
standard	
● for FM	FM3611: Class 1, Divison 2, Group A, B, C, D / T4, CL.1, Zone 2, GP. IIC, T4
● for hazardous zone	EN 60079-0 : 2006, EN 60079-15: 2005, II 3 G Ex nA II T4 KEMA 07 ATEX 0145X
● for safety / from CSA and UL	UL 60950-1, CSA C22.2 No. 60950-1
● for hazardous zone / from CSA and UL	ANSI / ISA 12.12.01, CSA C22.2 No. 213-M1987, CL. 1 / Div. 2 / GP. A, B, C, D T4, CL. 1 / Zone 2 / GP. IIC, T10
● for emitted interference	EN 61000-6-4 (Class A)
● for interference immunity	EN 61000-6-2
IT security for industrial automation systems / according to IEC 62443-4-2:2019	Yes
standards, specifications, approvals / CE	
certificate of suitability / CE marking	Yes
standards, specifications, approvals / other	
certificate of suitability	EN 61000-6-2, EN 61000-6-4

Subject to change without notice
© Copyright Siemens

● C-Tick	Yes
● railway application in accordance with EN 50155	No
● railway application in accordance with EN 50124-1	No
● KC approval	Yes
further information / internet-Links	
Internet-Link	
● to web page: selection aid TIA Selection Tool	http://www.siemens.com/snst
● to website: Industrial communication	http://www.siemens.com/simatic-net
● to website: Industry Mall	https://mall.industry.siemens.com
● to website: Information and Download Center	http://www.siemens.com/industry/infocenter
● to website: Image database	http://automation.siemens.com/bilddb
● to website: CAx-Download-Manager	http://www.siemens.com/cax
● to website: Industry Online Support	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)
last modified:	12/18/2020

Subject to change without notice
© Copyright Siemens